





ISCAR DEEP DRILLING LINES

Metric Catalog



MACHINING **IN** **TELLIGENTLY**





THE STANDARDS INSTITUTION OF ISRAEL



THE STANDARDS INSTITUTION OF ISRAEL



THE STANDARDS INSTITUTION OF ISRAEL



THE STANDARDS INSTITUTION OF ISRAEL



THE STANDARDS INSTITUTION OF ISRAEL

Quality Standard

ISCAR has been certified by the prestigious Standards Institution, as being in full compliance to ensure delivery of the finest quality goods. Quality control facilities include the metallurgical laboratory, raw metal testing, an online testing procedure and a machining center for tool performance testing and final product inspection. Only the finest products are packaged for entry into ISCAR's inventory.

CONTENTS

DEEP DRILLING BTA SYSTEM

3

GUNDRILLS

103

SOLID CARBIDE DRILLS

139

INDEX

147

NEOTA

NEO ISCAR TOOL ADVISOR

Find The NEOLOGIQAL Tool For Your Application!

- The virtual tool advisor features advanced AI and 'Big Data' analytics
- Supports with complicated machining tasks and challenges
- Offers a wide range of functions and recommendations to operate machining centers
- Features online service 24/7 in more than 30 languages
- Functions according to ISO 13399



Member IMC Group
iscar
www.iscar.com

Learn More...

Download
ISCAR WORLD App




Play Store



App Store



DEEP DRILLING BTA SYSTEM



Contents

BTA System Selection Guide	5
Indexable Drilling Heads	9
TRI-DEEP 16 – 40 mm	
DSD/DDD...FT	9
FINE-BEAM Ø25 – 89 mm	
DSD/DDD...FB	18
ISCAR DEEP-DRILL Ø38 – 293.99 mm	
DSD/DDD-EC/IC	27
Brazed Drilling Heads	46
ISCAR DEEP-DRILL	
DSD/DDD...E0/E1/E2/E3, DDD... E3	46
Counterboring Heads	52
INDEXABLE COUNTERBORING	
DSC-EA/EC/IA/IC, DDC-EA/EC	52
Trepanning Heads	76
INDEXABLE TREPANNING (SPECIAL)	
DSTR EC/IC	76
Drill Tubes	85
TS***, TS-I**, TS-O**	85
TDO-I	88
User Guide	90

Indexable Drill Heads

Applications		STS (Single Tube System)			DTS (Double Tube System)		
		TRIDEEP DEEP DRILLING	FINEBEAM	ISCARDEEPDRILL	TRIDEEP DEEP DRILLING	FINEBEAM	ISCARDEEPDRILL
		DSD-EF/IF...FT	DSD-EF/IF...FB	DSD-EC\IC	DDD...FT	DDD...FB	DDD-EC
drill heads for solid drilling							
drill diameter (mm)		Ø16 - 40	Ø25 - 89	Ø38 - 291.99	Ø18.4 - 40	Ø25 - 65	Ø38 - 183.99
thread types	external 4-start thread	✓	✓	✓	✓	✓	✓
	internal single-start thread	✓	✓	✓	-	-	-
hole tolerance		IT10	IT10	IT10	IT10	IT10	IT10
surface finish Ra (µm)		2	2	3	2	2	3
machines	deep hole drilling machines	✓	✓	✓	✓	✓	✓
	NC machines	-	-	-	✓	✓	✓
	lathes	-	-	-	✓	✓	✓
	machining centers M/C	-	-	-	✓	✓	✓
workpiece materials	P steel	...	...	...	...	...	...
	M stainless	...	...	...	...	...	...
	K cast iron	...	...	...	...	...	...
	N non-ferrous	...	...	...	...	...	...
	S superalloys	..	..	..	..	..	..
	H hard materials (≥40HRC)	..	..	..	..	..	..
insert type		TOGT	NPHT / NPMT	NPMX / TPMX	TOGT	NPHT / NPMT	NPMX / TPMX
plus cartridge and guide pad +1 mm - +5 mm		-	-	✓	-	-	✓
page		9	18	27	10	20	29

... (Excellent) ← → • (Standard)

Brazed Drill Heads

Applications		STS (Single Tube System)			DTS (Double Tube System)
		DSD-E0	DSD-E1	DSD-E2/E3	DDD-E3
brazed drill heads					
drill diameter (mm)		ø8 - 14.79	ø12.6 - 20	ø12.6 - 65	ø18.4 - 65
thread type	external single-start thread	✓	-	-	-
	external 2-start thread	-	ø12.6 - 15.59 mm	ø12.6 - 15.59 mm	-
	external 4-start thread	-	ø15.6 - 20 mm	ø15.6 - 65 mm	✓
hole tolerance		IT9	IT9	IT9	IT9
surface finish Ra (µm)		2	2	2	2
machine	deep hole drilling machines	✓	✓	✓	✓
	NC machines	-	-	-	✓
	lathes	-	-	-	✓
	machining centers M/C	-	-	-	✓
workpiece material	P steel	...	...	...	...
	M stainless	...	...	...	...
	K cast iron	...	...	...	...
	N non-ferrous	...	...	...	...
	S superalloys	..	..	..	..
	H hard materials (≥40HRC)	..	..	..	..
page		46	46	47	48

... (Excellent) ◀ ▶ • (Standard)

Indexable Counterboring Heads

Applications		STS (Single Tube System)				DTS (Double Tube System)	
		DSC - EA	DSC - EC	DSC - IA/IC		DDC - EA/EC	
drill head							
drill diameter (mm)		Ø25 - 39.99	Ø40 - 291.99	Ø25 - 39.99	Ø40 - 293.99	Ø25 - 39.99	Ø40 - 183.99
thread type	external 4-start thread	✓	✓	-	-	✓	✓
	internal single-start thread	-	-	✓	✓	-	-
hole tolerance		IT10	IT10	IT10	IT10	IT10	IT10
surface finish Ra (µm)		2	2	2	2	2	2
machine	deep hole drilling machines	✓	✓	✓	✓	✓	✓
	NC machines	-	-	-	-	✓	✓
	lathes	-	-	-	-	✓	✓
	machining centers M/C	-	-	-	-	✓	✓
workpiece material	P steel	...	...	...	...	...	...
	M stainless	...	...	...	...	...	...
	K cast iron	...	...	...	...	...	...
	N non-ferrous	...	...	...	...	...	...
	S superalloys	..	..	..	..	..	..
	H hard materials (≥40HRC)	..	..	..	..	..	..
insert type		XPMT	TPMX	XPMT	TPMX	XPMT	TPMX
plus cartridge and guide pad +1 mm - +5 mm		-	✓	-	✓	-	✓
page		52	55	60	62	66	69

... (Excellent) ← → • (Standard)

Indexable Trepanning Heads

Applications			STS (Single Tube System)	
drill head			DSTR	
			EC	IC
				
drill diameter (mm)			∅100 - 328	∅100 - 305.99
thread type	external 4-start thread		✓	-
	internal single-start thread		-	✓
hole tolerance			IT10	IT10
surface finish Ra (µm)			2	2
machine	deep hole drilling machines		✓	✓
	lathes		-	-
	machining centers M/C		-	-
workpiece material	P	steel	•••	•••
	M	stainless	•••	•••
	K	cast iron	•••	•••
	N	non-ferrous	•••	•••
	S	superalloys	••	••
	H	hard materials (≥40HRC)	••	••
insert type			TPMX	TPMX
page			76	78


•••(Excellent) ◀▶ •(Standard)

TRI-DEEP 16 – 40 mm DSD/DDD...FT



DSD-EF-FT

Deep Single Tube Drills with
External 4-Start Thread
Connection Carrying Triangular
Inserts (16-40 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	LF	OAL	PL	DCONMS	THOD ⁽³⁾
DSD-EF 16.00-16.70-FT	16.00	16.70	55.00	57.20	2.20	12.60	TS-I0
DSD-EF 16.71-17.70-FT	16.71	17.70	55.00	57.20	2.20	13.60	TS-I1
DSD-EF 17.71-18.90-FT	17.71	18.90	56.00	59.00	3.00	14.50	TS-I2
DSD-EF 18.91-20.00-FT	18.91	20.00	56.00	59.00	3.00	15.50	TS-I3
DSD-EF 20.01-21.80-FT	20.01	21.80	60.00	63.20	3.20	16.00	TS-I4
DSD-EF 21.81-21.99-FT	21.81	21.99	63.50	66.70	3.20	18.00	TS-I5
DSD-EF 22.00-24.10-FT	22.00	24.10	65.50	68.90	3.40	18.00	TS-I5
DSD-EF 24.11-25.00-FT	24.11	25.00	65.50	68.90	3.40	19.50	TS-I6
DSD-EF 25.01-26.40-FT	25.01	26.40	67.50	71.10	3.60	19.50	TS-I6
DSD-EF 26.41-28.00-FT	26.41	28.00	67.50	71.10	3.60	21.00	TS-I7
DSD-EF 28.01-28.70-FT	28.01	28.70	70.00	74.57	4.57	21.00	TS-I7
DSD-EF 28.71-31.00-FT	28.71	31.00	75.00	79.57	4.57	23.50	TS-I8
DSD-EF 31.01-32.00-FT	31.01	32.00	75.00	79.57	4.57	25.50	TS-I9
DSD-EF 32.01-33.30-FT	32.01	33.30	74.50	74.93	5.43	25.50	TS-I9
DSD-EF 33.31-36.20-FT	33.31	36.20	79.50	84.93	5.43	28.00	TS-I10
DSD-EF 36.21-39.60-FT	36.21	39.60	89.50	94.93	5.43	30.00	TS-I11
DSD-EF 39.61-40.00-FT	39.61	40.00	94.50	99.93	5.43	33.00	TS-I12

• Note: Each item in the attached catalog page represents a diameter range • For spare parts, insert information and user guide, see pages 13-17

• Inserts and guide pads to be ordered separately • Ordering example: DSD-EF 16.50-FT

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Tube designation


For inserts, see pages: TOGT-DT (11) • TOGT-GF (11)

For holders, see pages: TS-I** (86)



DSD-IF-FT

Deep Single Tube Drills with
Internal Single-Start Thread
Connection with Triangular
Inserts (16-40 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	LF	OAL	PL	DCONMS	THID ⁽³⁾
DSD-IF 16.01-16.50-FT	16.01	16.50	53.50	55.70	2.20	11.10	TS-O3
DSD-IF 16.51-17.25-FT	16.51	17.25	53.50	55.70	2.20	11.80	TS-O4
DSD-IF 17.26-18.00-FT	17.26	18.00	53.50	55.70	2.20	12.10	TS-O5
DSD-IF 18.01-19.00-FT	18.01	19.00	53.50	56.50	3.00	12.80	TS-O6
DSD-IF 19.01-19.99-FT	19.01	19.99	53.50	56.70	3.20	13.80	TS-O7
DSD-IF 20.00-21.99-FT	20.00	21.99	58.00	61.20	3.20	14.50	TS-O8
DSD-IF 22.00-24.99-FT	22.00	24.99	60.00	63.40	3.40	16.00	TS-O9
DSD-IF 25.00-26.99-FT	25.00	26.99	65.00	68.60	3.60	17.00	TS-O10
DSD-IF 27.00-28.00-FT	27.00	28.00	65.00	68.60	3.60	19.00	TS-O11
DSD-IF 28.01-29.99-FT	28.01	29.99	75.00	79.57	4.57	22.00	TS-O11
DSD-IF 30.00-31.99-FT	30.00	31.99	75.00	79.57	4.57	24.00	TS-O12
DSD-IF 32.00-FT	32.00	32.00	75.00	79.57	4.57	26.00	TS-O13
DSD-IF 32.01-33.99-FT	32.01	33.99	74.50	79.90	5.40	26.00	TS-O13
DSD-IF 34.00-36.99-FT	34.00	36.99	89.50	94.90	5.40	27.00	TS-O14
DSD-IF 37.00-39.00-FT	37.00	39.00	94.50	99.90	5.40	30.00	TS-O15
DSD-IF 39.01-39.99-FT	39.01	39.99	94.50	99.90	5.40	30.00	TS-O15
DSD-IF 40.00-40.00-FT	40.00	40.00	99.50	104.90	5.40	33.00	TS-O16

• Note: Each item in the attached catalog page represents a diameter range • For spare parts, insert information and user guide, see pages 13-17

• Inserts and guide pads to be ordered separately • Ordering example: DSD-IF 18.50-FT

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Tube designation


For inserts, see pages: TOGT-DT (11) • TOGT-GF (11)

For holders, see pages: TS-O** (87)



DDD-EF-FT

Deep Double Tube Drills
with External 4-Start Thread
Connection Carrying Triangular
Inserts (18.4-40 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	PL	OAL	DCONMS	THOD ⁽³⁾	THID ⁽⁴⁾
DDD-EF 18.40-20.00-FT	18.40	20.00	3.00	64.00	16.00	TDO-I0	TDI-N0
DDD-EF 20.01-21.80-FT	20.01	21.80	3.20	66.70	18.00	TDO-I1	TDI-N1
DDD-EF 21.81-21.99-FT	21.81	21.99	3.20	66.70	19.50	TDO-I2	TDI-N2
DDD-EF 22.00-24.10-FT	22.00	24.10	3.40	68.90	19.50	TDO-I2	TDI-N2
DDD-EF 24.11-25.00-FT	24.11	25.00	3.40	68.90	21.00	TDO-I3	TDI-N3
DDD-EF 25.01-26.40-FT	25.01	26.40	3.60	71.10	21.00	TDO-I3	TDI-N3
DDD-EF 26.41-28.00-FT	26.41	28.00	3.60	74.10	23.50	TDO-I4	TDI-N4
DDD-EF 28.01-28.70-FT	28.01	28.70	4.60	79.60	23.50	TDO-I4	TDI-N4
DDD-EF 28.71-29.99-FT	28.71	29.99	4.60	79.60	25.50	TDO-I5	TDI-N5
DDD-EF 30.00-31.00-FT	30.00	31.00	4.60	79.60	25.50	TDO-I5	TDI-N5
DDD-EF 31.01-32.00-FT	31.01	32.00	4.60	84.60	28.00	TDO-I6	TDI-N6
DDD-EF 32.01-33.30-FT	32.01	33.30	5.40	84.90	28.00	TDO-I6	TDI-N6
DDD-EF 33.31-36.20-FT	33.31	36.20	5.40	94.90	30.00	TDO-I7	TDI-N7
DDD-EF 36.21-39.00-FT	36.21	39.00	5.40	99.90	33.00	TDO-I8	TDI-N8
DDD-EF 39.01-39.60-FT	39.01	39.60	5.40	99.90	33.00	TDO-I8	TDI-N8
DDD-EF 39.61-40.00-FT	39.61	40.00	5.40	104.90	36.00	TDO-I9	TDI-N9

- Note: Each item in the attached catalog page represents a diameter range.
- For spare parts, insert information and user guide, see pages 13-17
- Inserts and guide pads to be ordered separately
- Ordering example: DDD-EF 18.50-FT

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Outer tube designation

⁽⁴⁾ Inner tube designation

For inserts, see pages: TOGT-DT (11) • TOGT-GF (11)

For holders, see pages: TDO-I (D18.41-65.00) (88)

Universal Marking for Deep Drilling Tools

D- Tool Diameter

Metric- D16.00

Inch- D.630

d- Pilot diameter

Metric- d12.6

Inch- d.496

Tool Style

F- Fixed pocket 3-5 cutting edges

G- Fixed pocket single cutting edge


Thread Type

4ST- Four-start thread single tube

1ST- Single-start thread single tube

4DT- Four-start thread double tube

16- Tube diameter



TOGT-DT

Deep Drilling Inserts with 3 Chip Splitting Cutting Edges, a Positive Rake Chipbreaker and a Wiper



Fig. 1





Fig. 2



Dimensions

Designation	IC	RE	PL	S	Fig.	IC908
TOGT 070304-DT	7.69	0.40	1.95	2.30	1	•
TOGT 080305-DT	8.55	0.50	2.20	2.80	1	•
TOGT 090305-DT	8.32	0.50	3.00	3.00	2	•
TOGT 100305-DT	9.23	0.50	3.20	3.30	2	•
TOGT 110405-DT	10.40	0.50	3.40	3.80	2	•
TOGT 120405-DT	11.59	0.50	3.60	4.30	2	•
TOGT 130408-DT	12.85	0.80	4.57	4.76	2	•
TOGT 140510-DT	16.85	1.00	5.43	5.26	2	•

For tools, see pages: DDD-EF-FT (10) • DSD-EF-FT (9) • DSD-IF-FT (9) • GD-DH (108) • GDH-MKT (110)

TOGT-GF

Deep Drilling Inserts with 3 Chip Splitting Cutting Edges, a Positive Rake Chipbreaker and a Wiper



Fig. 1





Fig. 2



Dimensions

Designation	IC	RE	PL	S	Fig.	IC908
TOGT 070304-GF	7.69	0.40	1.95	2.30	1	•
TOGT 080305-GF	8.55	0.50	2.20	2.80	1	•
TOGT 090305-GF	8.32	0.50	3.00	3.00	2	•
TOGT 100305-GF	9.23	0.50	3.20	3.30	2	•
TOGT 110405-GF	10.40	0.50	3.40	3.80	2	•
TOGT 120405-GF	11.59	0.50	3.60	4.30	2	•
TOGT 130408-GF	12.85	0.80	4.57	4.76	2	•

For tools, see pages: DDD-EF-FT (10) • DSD-EF-FT (9) • DSD-IF-FT (9) • GD-DH (108) • GDH-MKT (110)

Chipbreaker Appearances


		GF	DT
1	rake angle	$a^{\circ}=25^{\circ}$	$a^{\circ}=20^{\circ}$
2	ID mark		



ISCARDEEPPDRILL

GPS


Deep Drilling Solid Carbide Guide Pads



Designation	Dimensions				Tough ↔ Hard		
	OAW	OAL	OAH	RE	IC928	IC950	IC908
GPS-04-16-045-DC ⁽¹⁾	4.00	16.00	1.80	4.50			•
GPS-04-16-050-DC ⁽¹⁾	4.00	16.00	1.80	5.00			•
GPS-04-16-055-DC ⁽¹⁾	4.00	16.00	2.00	5.50	•		•
GPS-05-18-060-DC ⁽¹⁾	5.00	18.00	2.50	6.00	•		•
GPS-05-18-075-DC ⁽¹⁾	5.00	18.00	2.50	7.50	•		•
GPS-06-20-075-DC ⁽¹⁾	6.00	20.00	3.00	7.50			•
GPS-06-20-075	6.00	20.00	3.00	7.50		•	
GPS-06-20-085-DC ⁽¹⁾	6.00	20.00	3.00	8.50	•		•
GPS-06-20-085	6.00	20.00	3.00	8.50		•	
GPS-06-20-100-DC ⁽¹⁾	6.00	20.00	3.00	10.00	•		•
GPS-06-20-100	6.00	20.00	3.00	10.00		•	
GPS-06-20-120-DC ⁽¹⁾	6.00	20.00	3.00	12.00	•		•
GPS-06-20-120	6.00	20.00	3.00	12.00		•	
GPS-07-20-120-DC ⁽¹⁾	7.00	20.00	3.50	12.00	•		•
GPS-07-20-120	7.00	20.00	3.50	12.00		•	
GPS-08-25-155-DC ⁽¹⁾	8.00	25.00	4.50	15.50	•		•
GPS-08-25-155	8.00	25.00	4.50	15.50		•	
GPS-10-30-200-DC ⁽¹⁾	10.00	30.00	4.50	20.00	•		•
GPS-10-30-200	10.00	30.00	4.50	20.00		•	
GPS-10-35-200-DC ⁽¹⁾	10.00	35.00	6.00	20.00	•		•
GPS-10-35-200	10.00	35.00	6.00	20.00		•	
GPS-12-35-250-DC ⁽¹⁾	12.00	35.00	5.50	25.00	•		•
GPS-12-35-250	12.00	35.00	5.50	25.00		•	
GPS-14-40-250-DC ⁽¹⁾	14.00	40.00	7.50	25.00	•		•
GPS-14-40-250	14.00	40.00	7.50	25.00		•	
GPS-18-40-300-DC ⁽¹⁾	18.00	40.00	9.00	30.00	•		•

⁽¹⁾ DC- Double Chamfer

Universal Marking for Deep Drilling Tools



Guide Pad Grade Recommendation


Priority	Oil Coolant			Water Based Coolant		
	1	2	3	1	2	3
ISO-P	IC950	IC908	IC928	IC928	IC908	-
ISO-K	IC950	IC908	IC928	IC928	IC908	-
ISO-M	IC928	IC908	IC950	IC928	IC908	-
ISO-S	IC928	IC908	IC950	IC928	IC908	-

When ordering guide pad clamping screws, below before choosing the screw size, first confirm the drill body design according to the procedure shown.

if the drill head has the protector: use a screw in the new design	if the drill head has no protector: use a screw in the previous design
New design with guide pad protector 	Conventional design without guide pad protector

Spare Parts

Diameter Range	Insert	Insert Clamping Screw	Key	N*m	Solid Carbide Guide Pad	Guide Pad Clamping Screw	Key
14.00-15.99	TOGT 070304-DT/GF	SR 14-560/S M2.5X0.45	T-8/5	1.2	GPS-05-18-060-DC	SR 34-508 M2.2X0.45	T-7/5
16.00-18.00	TOGT 080305-DT/GF		T-8/5	1.2	GPS-05-18-075-DC		
18.01-20.00	TOGT 090305-DT/GF		T-8/5	1.2	GPS-06-20-085-DC		
20.01-21.00	TOGT 100305-DT/GF	SR 34-506 M3X0.5	T-9/5	2.0	GPS-06-20-085-DC		
21.01-21.99	TOGT 100305-DT/GF				GPS-06-20-100-DC		
22.00-25.00	TOGT 110405-DT/GF	SR 14-571/S M3.5X0.6	T-10/5	4.8	GPS-06-20-100-DC	SR 34-508 M2.2X0.45	T-7/5
25.01-28.00	TOGT 120405-DT/GF	SR 14-506 M4X0.7	T-15/5	4.8	GPS-06-20-120-DC		
28.01-29.99	TOGT 130408-DT/GF	SR 16-212/L10 M5X0.8	T20/5	10	GPS-06-20-120-DC		
30.00-32.00	TOGT 130408-DT/GF				GPS-07-20-120-DC		
32.01-39.00	TOGT 140510-DT/GF				GPS-07-20-120-DC	CSTB-3L065 M2.2X0.45	T-9/5
39.01-40.00	TOGT 140510-DT/GF				GPS-08-25-155-DC		

Troubleshooting for Insert Damage
Examples of Trouble with the Cutting Edge


Problem	Cause	Solution	
		Grade	Cutting Conditions / Other
1. Chipping, Fracture	- excessive vibration or impact - torn away built-up edge	use a tough grade	- reduce the feed rate - eliminate the vibration
2. Flaking	excessive vibration or impact	use a tough grade	- reduce the feed rate - eliminate the vibration
3. Flank Wear	- cutting speed too high - inadequate tool toughness	- use a grade with high wear resistance - use a coated grade	- reduce the cutting speed - reduce the feed rate - use coolant properly
4. Crater Wear	- cutting speed too high - feed rate too high - inadequate tool toughness	- use a grade with high wear resistance - use a coated grade	- reduce the cutting speed - reduce the feed rate - use coolant properly
5. Initial Chipping	- inappropriate guide bush or pilot hole - misalignment	use a tough grade	- adjust or change the guide bushing or pilot hole - reduce the feed rate - correct the misalignment






Machining Recommendations for TRIDEEP BTA Drilling Heads

ISO	Material		Condition	Tensile Strength [N/mm²]	Material Group No. ⁽¹⁾	Hardness (HB)	Chipbreaker	Cutting Speed V _c (m/min)	Feed : f (mm/rev)		
									Drill dia. (mm)		
									Ø16-18	Ø18.01-40	
P	non-alloy steel and cast steel, free cutting steel	<0.25% C	annealed	420	1	125	GF	50-100	0.03-0.10	0.03-0.10	
							DT	80-140	0.05-0.10	0.05-0.10	
		≥0.25% C	annealed	650	2	190	GF	50-100	0.03-0.10	0.03-0.10	
							DT	80-140	0.05-0.10	0.05-0.10	
		<0.55% C	quenched and tempered	850	3	250	GF	50-100	0.03-0.10	0.03-0.12	
							DT	80-140	0.05-0.16	0.05-0.20	
		≥0.55% C	annealed	750	4	220	GF	50-100	0.03-0.10	0.03-0.12	
							DT	80-140	0.05-0.16	0.05-0.20	
			quenched and tempered	1000	5	300	GF	50-100	0.03-0.10	0.03-0.12	
							DT	80-140	0.05-0.16	0.05-0.20	
	low alloy and cast steel (less than 5% of alloying elements)	annealed	600	6	200	GF	50-100	0.03-0.10	0.03-0.10		
						DT	80-140	0.05-0.10	0.05-0.10		
		quenched and tempered	930	7	275	GF	50-100	0.03-0.10	0.03-0.10		
						DT	80-140	0.05-0.10	0.05-0.10		
			1000	8	300	GF	50-100	0.03-0.10	0.03-0.10		
						DT	80-140	0.05-0.10	0.05-0.10		
		1200	9	350	GF	50-100	0.03-0.10	0.03-0.10			
					DT	80-140	0.05-0.10	0.05-0.10			
	high alloyed steel, cast steel and tool steel	annealed	680	10	200	GF	50-100	0.03-0.10	0.03-0.12		
						DT	80-120	0.05-0.16	0.05-0.20		
		quenched and tempered	1100	11	325	GF	50-100	0.03-0.10	0.03-0.12		
						DT	80-120	0.05-0.16	0.05-0.20		
	stainless steel and cast steel	ferritic/martensitic	680	12	200	GF	50-100	0.03-0.06	0.03-0.06		
						DT	60-100	0.05-0.10	0.05-0.10		
		Martensitic	820	13	240	GF	50-100	0.03-0.06	0.03-0.06		
						DT	60-100	0.05-0.10	0.05-0.10		
M	stainless steel and cast steel	Austenitic, duplex	600	14	180	GF	50-100	0.03-0.06	0.03-0.06		
						DT	60-100	0.05-0.10	0.05-0.10		
K	grey cast iron (GG)	ferritic/pearlitic		15	180	GF	50-100	0.03-0.15	0.05-0.18		
						DT	80-140	0.05-0.25	0.05-0.3		
		pearlitic/martensitic		16	260	GF	50-100	0.03-0.15	0.05-0.18		
						DT	80-140	0.05-0.25	0.05-0.3		
	nodular cast iron (GGG)	ferritic		17	160	GF	50-100	0.03-0.15	0.05-0.18		
						DT	80-140	0.05-0.25	0.05-0.3		
		pearlitic		18	250	GF	50-100	0.03-0.15	0.05-0.18		
						DT	80-140	0.05-0.25	0.05-0.3		
	malleable cast iron	ferritic		19	130	GF	50-100	0.03-0.15	0.05-0.18		
						DT	80-140	0.05-0.25	0.05-0.3		
		pearlitic		20	230	GF	50-100	0.03-0.15	0.05-0.18		
						DT	80-140	0.05-0.25	0.05-0.3		
N	aluminum-wrought alloys	not hardenable		21	60	GF	80-160	0.03-0.15	0.03-0.015		
						DT	100-200	0.05-0.20	0.05-0.20		
		hardenable		22	100	GF	80-160	0.03-0.15	0.03-0.015		
						DT	100-200	0.05-0.20	0.05-0.20		
	aluminum-cast alloys	≤ 12% Si	not hardenable	23	75	GF	80-160	0.03-0.15	0.03-0.015		
						DT	100-200	0.05-0.20	0.05-0.20		
		hardenable		24	90	GF	80-160	0.03-0.15	0.03-0.015		
						DT	100-200	0.05-0.20	0.05-0.20		
	>12% Si	high temperature		25	130	GF	80-160	0.03-0.15	0.03-0.015		
						DT	100-200	0.05-0.20	0.05-0.20		
		>1% Pb	free cutting		26	110	GF	80-160	0.03-0.15	0.03-0.015	
							DT	100-200	0.05-0.20	0.05-0.20	
	copper alloys		brass		27	90	GF	80-160	0.03-0.15	0.03-0.015	
							DT	100-200	0.05-0.20	0.05-0.20	
		electrolitic copper		28	100	GF	80-160	0.03-0.15	0.03-0.015		
						DT	100-200	0.05-0.20	0.05-0.20		
S	high temp. alloys	Fe based	annealed	31	200	GF	50-100	0.03-0.06	0.03-0.06		
						DT	60-100	0.05-0.10	0.05-0.10		
			hardened	32	280	GF	50-100	0.03-0.06	0.03-0.06		
						DT	60-100	0.05-0.10	0.05-0.10		
		Ni / Co based	annealed	33	250	GF	20-50	0.03-0.06	0.03-0.08		
						DT	20-50	0.04-0.08	0.04-0.10		
			hardened	34	350	GF	20-50	0.03-0.06	0.03-0.08		
						DT	20-50	0.04-0.08	0.04-0.10		
		cast		35	320	GF	20-50	0.03-0.06	0.03-0.08		
						DT	20-50	0.04-0.08	0.04-0.10		
			titanium alloys	pure	400	36		GF	30-60	0.03-0.10	0.03-0.12
								DT	30-60	0.05-0.13	0.05-0.15
alpha+beta alloys hardened	1050	37			GF	30-60	0.03-0.10	0.03-0.12			
					DT	30-60	0.05-0.13	0.05-0.15			
H	hardened steel	≥ 40HRC	hardened	38		GF	40-100	0.03-0.08	0.03-0.08		
						DT	50-100	0.04-0.08	0.04-0.10		






(1) Based on ISO 513 and VDI 3323 standards

Technical Guide

STS - Machine Setting for Single Tube System



DTS - Machine Setting for Double Tube System




The above values should not be used as the exact recommendations.
 They may need modification depending on the machining conditions, materials, etc.




Machine Setup

STS and DTS



- Only used when the workpiece and the tool axis are on the same line.
- Better hole straightness and wear resistance on guide bush are provided compared to the tool rotating system.
- Keep the alignment between guide bush and spindle within 0.02 mm.



- Can be used when the workpiece and the tool axis are not on the same line.
- Keep the alignment between guide bush and spindle within 0.02 mm.


DTS

Positioning of Outer Tube and Guide Bush

Be sure to set the outer tube more than 5.0 mm into the guide bush to properly supply the coolant.

Positioning of Workpiece Material and Guide Bush

Sealing is not required for DTS because of the vacuum effect, but keep the gap between workpiece material and guide bush within 1.0 mm.



Guide Bush


Tolerance

Guide bush tolerance should be G6 in order to keep consistent tool life and cutting accuracy. Diameters for G6 tolerance are shown on the right.

øD (mm)	G6 Tolerance (mm)
16.00 - 18.00	+0.006 - +0.017
18.01 - 30.00	+0.007 - +0.020
30.01 - 40.00	+0.009 - +0.025

Material

Guide Bush Material	System	Advantage
Hardened Steel	workpiece rotating	cost efficient (inexpensive)
Tungsten Carbide	tool rotating workpiece rotating	long life guide bush



Coolant

Temperature

The proper coolant temperature is 30 - 40°C (90 - 100°F). If the temperature exceeds this range, the coolant will deteriorate easily and may shorten tool life and generate poor surface finish.

Filtration

The coolant must be filtered properly in order to protect guide pads and workpiece surface.

Water-Soluble Type

Around 10% (dilution rate 1/10) is recommended for the concentration of water-soluble coolant in order to protect guide pads.

CNC Drilling Cycle Operations

Use the CNC drilling cycle as instructed below in order to optimize the tool performance safely.

	1. Start the CNC cycle operation
	2. Move the oil pressure head and securely seal onto the face of the workpiece a Make sure to position the drill so that the guide pads remain inside the guide bushing when the pressure head is moved towards the workpiece face
	3. Move the BTA drill toward the workpiece b Keep the drill 3 - 5 mm* off the face of the workpiece. * If the machine allows this drill setting in Step 1, move on to Step 4
	4. Start the Cutting 4.1 Activate the coolant supply 4.2 Start the rotation (of the drill, the workpiece, or the drill+workpiece) 4.3 Start the drill feed
	5. Stop the Cutting 5.1 Stop the drill feed 5.2 Stop the rotation 5.3 Stop the coolant supply c Stop the cutting when the drill shoulder is completely through the end face of the workpiece
	6. Return the drill to the starting point
	7. Return the oil pressure head to the starting point




FINE-BEAM Ø25 – 89 mm

DSD/DDD...FB

FINEBEAM

DSD-EF-FB

Deep Single Tube Drills
with External 4-Start
Thread Connection for
High Feed (25-89 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	OAL	PL	DCONMS	DRVS ⁽³⁾	Ts ⁽⁴⁾
DSD-EF 25.00-26.40-FB	25.00	26.40	73.00	3.00	19.50	22.0	TS-I6
DSD-EF 26.41-28.70-FB	26.41	28.70	73.00	3.00	21.00	23.0	TS-I7
DSD-EF 28.71-31.00-FB	28.71	31.00	78.00	3.00	23.50	24.0	TS-I8
DSD-EF 31.01-33.30-FB	31.01	33.30	78.00	3.00	25.50	27.0	TS-I9
DSD-EF 33.31-36.20-FB	33.31	36.20	83.00	3.00	28.00	29.0	TS-I10
DSD-EF 36.21-39.60-FB	36.21	39.60	93.00	3.00	30.00	32.0	TS-I11
DSD-EF 39.61-43.00-FB	39.61	43.00	99.00	4.00	33.00	35.0	TS-I12
DSD-EF 43.01-47.00-FB	43.01	47.00	104.00	4.00	36.00	38.0	TS-I13
DSD-EF 47.01-51.70-FB	47.01	51.70	104.00	4.00	39.00	41.0	TS-I14
DSD-EF 51.71-56.20-FB	51.71	56.20	114.00	4.00	43.00	46.0	TS-I15
DSD-EF 56.21-60.60-FB	56.21	60.60	120.00	5.00	47.00	50.0	TS-I16
DSD-EF 60.61-65.00-FB	60.61	65.00	120.00	5.00	51.00	55.0	TS-I17
DSD-EF 65.01-66.99-FB	65.01	66.99	149.00	8.00	52.00	63.0	TS-I18
DSD-EF 67.00-72.99-FB	67.00	72.99	149.00	8.00	58.00	69.0	TS-I19
DSD-EF 73.00-79.99-FB	73.00	79.99	150.00	9.00	63.00	76.0	TS-I20
DSD-EF 80.00-86.99-FB	80.00	86.99	173.00	9.00	70.00	83.0	TS-I21
DSD-EF 87.00-89.00-FB	87.00	89.00	173.00	9.00	77.00	86.0	TS-I22

- For spare parts and insert information, see page 24
- For user guide and quotation form, see pages 25-26, 101-102
- Inserts and guide pads to be ordered separately

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Torque key size

⁽⁴⁾ Tube designation


For inserts, see pages: NPHT (21) • NPMT (22)

For holders, see pages: TS-I** (86)

Wrench Size

Designation	Wrench size DRVS (mm)
DSD-EF 25.00-26.40-FB	22 (.866")
DSD-EF 26.41-28.70-FB	23 (.906")
DSD-EF 28.71-31.00-FB	24 (15/16")
DSD-EF 31.01-33.30-FB	27 (1.063")
DSD-EF 33.31-36.20-FB	29 (1-1/8")
DSD-EF 36.21-39.60-FB	32 (1.260")
DSD-EF 39.61-43.00-FB	35 (1.378")
DSD-EF 43.01-47.00-FB	38 (1-1/2")
DSD-EF 47.01-51.70-FB	41 (1.614")
DSD-EF 51.71-56.20-FB	46 (1.811")
DSD-EF 56.21-60.60-FB	50 (1.968")
DSD-EF 60.61-65.00-FB	55 (2.165")
DSD-EF 65.01-66.99-FB	63 (2.480")
DSD-EF 67.00-72.99-FB	69 (2.717")
DSD-EF 73.00-79.99-FB	76 (2.992")
DSD-EF 80.00-86.99-FB	83 (3.268")
DSD-EF 87.00-89.00-FB	86 (3-3/8")


For diameter DC range larger than 65 mm use hook spanner



FINEBEAM

DSD-IF-FB

Deep Single Tube Drills with Internal Single-Start Thread Connection (25-89 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	OAL	PL	DCONMS	DRVS ⁽³⁾	Ts ⁽⁴⁾
DSD-IF 25.00-26.99-FB	25.00	26.99	73.00	3.00	20.00	19.0	TS-010
DSD-IF 27.00-29.00-FB	27.00	29.00	73.00	3.00	22.00	21.0	TS-011
DSD-IF 29.01-29.99-FB	29.01	29.99	73.00	3.00	22.00	24.0	TS-011
DSD-IF 30.00-31.99-FB	30.00	31.99	78.00	3.00	24.00	24.0	TS-012
DSD-IF 32.00-33.99-FB	32.00	33.99	78.00	3.00	26.00	26.0	TS-013
DSD-IF 34.00-36.99-FB	34.00	36.99	93.00	3.00	27.00	28.0	TS-014
DSD-IF 37.00-39.99-FB	37.00	39.99	98.00	3.00	30.00	30.0	TS-015
DSD-IF 40.00-43.99-FB	40.00	43.99	104.00	4.00	33.00	32.0	TS-016
DSD-IF 44.00-46.99-FB	44.00	46.99	109.00	4.00	37.00	36.0	TS-017
DSD-IF 47.00-51.99-FB	47.00	51.99	109.00	4.00	41.00	36.0	TS-018
DSD-IF 52.00-56.99-FB	52.00	56.99	114.00	4.00	44.00	46.0	TS-019
DSD-IF 57.00-60.99-FB	57.00	60.99	120.00	5.00	49.00	46.0	TS-020
DSD-IF 61.00-65.00-FB	61.00	65.00	120.00	5.00	53.00	54.0	TS-021
DSD-IF 65.01-67.99-FB	65.01	67.99	112.00	8.00	53.00	64.0	TS-021
DSD-IF 68.00-74.99-FB	68.00	74.99	113.00	9.00	59.00	71.0	TS-022
DSD-IF 75.00-80.99-FB	75.00	80.99	143.00	9.00	65.00	77.0	TS-023
DSD-IF 81.00-89.00-FB	81.00	89.00	143.00	9.00	71.00	86.0	TS-024

• For spare parts and insert information, see page 24 • For user guide and quotation form, see pages 25-26, 101-102 • Inserts and guide pads to be ordered separately

• Ordering example: DSD-IF 43.10-FB

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Torque key size

⁽⁴⁾ Tube designation


For inserts, see pages: NPHT (21) • NPMT (22)

For holders, see pages: TS-O** (87)

Wrench Size

Designation	Wrench Size DRVS mm (inch)
DSD-IF 25.00-26.99-FB	19 (3/4")
DSD-IF 27.00-29.00-FB	21 (13/16")
DSD-IF 29.01-31.99-FB	24 (15/16")
DSD-IF 32.00-33.99-FB	26 (1.024")
DSD-IF 34.00-36.99-FB	28 (1.102")
DSD-IF 37.00-39.99-FB	30 (1.181")
DSD-IF 40.00-43.99-FB	32 (1.260")
DSD-IF 44.00-51.99-FB	36 (1.417")
DSD-IF 52.00-60.99-FB	46 (1.811")
DSD-IF 61.00-65.00-FB	54 (2-1/8")
DSD-IF 65.01-67.99-FB	64 (2.520")
DSD-IF 68.00-74.99-FB	71 (2.795")
DSD-IF 75.00-80.99-FB	77 (3")
DSD-IF 81.00-89.00-FB	86 (3-3/8")

For diameter DC range larger than 65mm use hook spanner






FINEBEAM

DDD-EF-FB

Deep Double Tube Drills
with External 4-Start
Thread Connection for
High Feed (25-65 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	OAL	PL	DCONMS	DRVS ⁽³⁾	Ts ⁽⁴⁾	Tsi ⁽⁵⁾
DDD-EF 25.00-26.40-FB	25.00	26.40	73.00	3.00	21.00	22.0	TDO-I3	TDI-N3
DDD-EF 26.41-28.70-FB	26.41	28.70	78.00	3.00	23.50	23.0	TDO-I4	TDI-N4
DDD-EF 28.71-31.00-FB	28.71	31.00	78.00	3.00	25.50	24.0	TDO-I5	TDI-N5
DDD-EF 31.01-33.30-FB	31.01	33.30	83.00	3.00	28.00	27.0	TDO-I6	TDI-N6
DDD-EF 33.31-36.20-FB	33.31	36.20	93.00	3.00	30.00	29.0	TDO-I7	TDI-N7
DDD-EF 36.21-39.60-FB	36.21	39.60	99.00	4.00	33.00	32.0	TDO-I8	TDI-N8
DDD-EF 39.61-43.00-FB	39.61	43.00	104.00	4.00	36.00	35.0	TDO-I9	TDI-N9
DDD-EF 43.01-47.00-FB	43.01	47.00	104.00	4.00	39.00	38.0	TDO-I10	TDI-N10
DDD-EF 47.01-51.70-FB	47.01	51.70	114.00	4.00	43.00	41.0	TDO-I11	TDI-N11
DDD-EF 51.71-56.20-FB	51.71	56.20	120.00	5.00	47.00	46.0	TDO-I12	TDI-N12
DDD-EF 56.21-60.60-FB	56.21	60.60	120.00	5.00	51.00	50.0	TDO-I13	TDI-N13
DDD-EF 60.61-65.00-FB	60.61	65.00	120.00	5.00	51.00	55.0	TDO-I13	TDI-N13

- For spare parts and insert information, see page 24
- For user guide and quotation form see pages 25-26, 101-102
- Inserts and guide pads to be ordered separately
- Ordering example: DDD-EF 43.00-FB

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Torque key size

⁽⁴⁾ Outer tube designation


⁽⁵⁾ Inner tube designation

For inserts, see pages: NPHT (21) • NPMT (22)

For holders, see pages: TDO-I (D18.41-65.00) (88)

Wrench Size

Designation	Wrench Size DRVS mm (inch)
DDD-EF 25.00-26.40-FB	22 (.866")
DDD-EF 26.41-28.70-FB	23 (.906")
DDD-EF 28.71-31.00-FB	24 (15/16")
DDD-EF 31.01-33.30-FB	27 (1.063")
DDD-EF 33.31-36.20-FB	29 (1-1/8")
DDD-EF 36.21-39.60-FB	32 (1.260")
DDD-EF 39.61-43.00-FB	35 (1.378")
DDD-EF 43.01-47.00-FB	38 (1-1/2")
DDD-EF 47.01-51.70-FB	41 (1.614")
DDD-EF 51.71-56.20-FB	46 (1.811")
DDD-EF 56.21-60.60-FB	50 (1.968")
DDD-EF 60.61-65.00-FB	55 (2.165")



Universal Marking for Deep Drilling Tools

D- Tool Diameter

Metric- D25.4

Inch- D1.000

d- pilot diameter

Metric- d19.5

Inch- d.768

Tool Style

F- fixed pocket 3-5 cutting edge

G- fixed pocket single cutting edge


Thread Type

4ST- four-start thread single tube

1ST- single-start thread single tube

4DT- four-start thread double tube


22- tube diameter



FINEBEAM

NPHT

Peripheral Precision Inserts
for Drilling Heads DSD-EF-FB
/ DDD-EF-FB / DSD-IF-FB



Designation	Dimensions				Tough ↔ Hard		
	W1	INSL	S	RE	IC908	IC948	IC806
NPHT 060304R-G-P	6.00	8.00	3.00	0.40	•		
NPHT 070404R-G-P	7.50	10.00	4.00	0.40	•		
NPHT 090404R-G-P	9.00	10.00	4.00	0.40	•		
NPHT 110404R-G-P	11.00	10.00	4.00	0.40	•		
NPHT 130404R-G-P	13.00	10.00	4.00	0.40	•		
NPHT 060308R-G-P	6.00	8.00	3.00	0.80	•	•	•
NPHT 070408R-G-P	7.50	10.00	4.00	0.80	•	•	•
NPHT 090408R-G-P	9.00	10.00	4.00	0.80	•	•	•
NPHT 110408R-G-P	11.00	10.00	4.00	0.80	•	•	•
NPHT 130408R-G-P	13.00	10.00	4.00	0.80	•	•	•
NPHT 060308R-HF-P	6.00	8.00	3.00	0.80	•	•	•
NPHT 070408R-HF-P	7.50	10.00	4.00	0.80	•	•	•
NPHT 090408R-HF-P	9.00	10.00	4.00	0.80	•	•	•
NPHT 110408R-HF-P	11.00	10.00	4.00	0.80	•	•	•
NPHT 130408R-HF-P	13.00	10.00	4.00	0.80	•	•	•


For tools, see pages: DDD-EF-FB (20) • DSD-EF-FB (18) • DSD-IF-FB (19)

	NPHT Peripheral inserts		
	IC948	IC806	IC908
P	•••	••	•
M	•••	••	•
K	•••	••	•
N	•••	••	•
S	••	•••	•
H	••	•••	•

••• First priority
•• Second priority
• Third priority

Chipbreaker Comparison

HF - provides drilling stability
at high feed rates



Insert Description:

NP#T ## ## ## #-##-# IC###

Insert Type:
M – pressed (central & intermediate)
H – grounded (peripheral)

Chipbreaker Type:
G - general
HF – high feed

Insert Position:
P - peripheral
I - intermediate
C - center

grade

thickness

**L - left
R – right**

corner radius size


insert Size



FINEBEAM

NPMT

Internal and Central Inserts for
Drilling Heads DSD-EF-FB
/ DDD-EF-FB



Designation	Dimensions				Tough ↔ Hard		
	W1	INSL	S	RE	IC908	IC948	IC806
NPMT 050304R-G-I	5.50	8.00	3.00	0.40	•	•	•
NPMT 060404R-G-I	6.50	10.00	4.00	0.40	•	•	•
NPMT 080404R-G-I	8.00	10.00	4.00	0.40	•	•	•
NPMT 090404R-G-I	9.50	10.00	4.00	0.40	•	•	•
NPMT 120404R-G-I	12.50	10.00	4.00	0.40	•	•	•
NPMT 050304R-HF-I	5.50	8.00	3.00	0.40	•	•	•
NPMT 060404R-HF-I	6.50	10.00	4.00	0.40	•	•	•
NPMT 080404R-HF-I	8.00	10.00	4.00	0.40	•	•	•
NPMT 090404R-HF-I	9.50	10.00	4.00	0.40	•	•	•
NPMT 120404R-HF-I	12.50	10.00	4.00	0.40	•	•	•
NPMT 050308L-G-C	5.50	8.00	3.00	0.80	•	•	•
NPMT 060408L-G-C	6.50	10.00	4.00	0.80	•	•	•
NPMT 080408L-G-C	8.00	10.00	4.00	0.80	•	•	•
NPMT 090408L-G-C	9.50	10.00	4.00	0.80	•	•	•
NPMT 120408L-G-C	12.50	10.00	4.00	0.80	•	•	•
NPMT 050308L-HF-C	5.50	8.00	3.00	0.80	•	•	•
NPMT 060408L-HF-C	6.50	10.00	4.00	0.80	•	•	•
NPMT 080408L-HF-C	8.00	10.00	4.00	0.80	•	•	•
NPMT 090408L-HF-C	9.50	10.00	4.00	0.80	•	•	•
NPMT 120408L-HF-C	12.50	10.00	4.00	0.80	•	•	•


For tools, see pages: DDD-EF-FB (20) • DSD-EF-FB (18) • DSD-IF-FB (19)

	NPMT intermediate/central inserts		
	IC948	IC806	IC908
P	•••	••	•
M	•••	••	•
K	•••	••	•
N	•••	••	•
S	••	•••	•
H	••	•••	•

- First priority
- Second priority
- Third priority

Chipbreaker Comparison

HF - provides drilling stability
at high feed rates



Insert Description:

Chipbreaker Type:

G - general
HF - high feed

NP#T ## ## ## #-##-# IC###

Insert Type:

M - pressed (central & intermediate)
H - grounded (peripheral)

thickness

L - left
R - right

Insert Position:


P - peripheral
I - intermediate
C - center

grade

ISCARDEEPDRILL

GPS


Deep Drilling Solid Carbide Guide Pads



Designation	Dimensions				Tough → Hard		
	OAW	OAL	OAH	RE	IC928	IC950	IC908
GPS-04-16-045-DC ⁽¹⁾	4.00	16.00	1.80	4.50			•
GPS-04-16-050-DC ⁽¹⁾	4.00	16.00	1.80	5.00			•
GPS-04-16-055-DC ⁽¹⁾	4.00	16.00	2.00	5.50	•		•
GPS-05-18-060-DC ⁽¹⁾	5.00	18.00	2.50	6.00	•		•
GPS-05-18-075-DC ⁽¹⁾	5.00	18.00	2.50	7.50	•		•
GPS-06-20-075-DC ⁽¹⁾	6.00	20.00	3.00	7.50			•
GPS-06-20-075	6.00	20.00	3.00	7.50		•	
GPS-06-20-085-DC ⁽¹⁾	6.00	20.00	3.00	8.50	•		•
GPS-06-20-085	6.00	20.00	3.00	8.50		•	
GPS-06-20-100-DC ⁽¹⁾	6.00	20.00	3.00	10.00	•		•
GPS-06-20-100	6.00	20.00	3.00	10.00		•	
GPS-06-20-120-DC ⁽¹⁾	6.00	20.00	3.00	12.00	•		•
GPS-06-20-120	6.00	20.00	3.00	12.00		•	
GPS-07-20-120-DC ⁽¹⁾	7.00	20.00	3.50	12.00	•		•
GPS-07-20-120	7.00	20.00	3.50	12.00		•	
GPS-08-25-155-DC ⁽¹⁾	8.00	25.00	4.50	15.50	•		•
GPS-08-25-155	8.00	25.00	4.50	15.50		•	
GPS-10-30-200-DC ⁽¹⁾	10.00	30.00	4.50	20.00	•		•
GPS-10-30-200	10.00	30.00	4.50	20.00		•	
GPS-10-35-200-DC ⁽¹⁾	10.00	35.00	6.00	20.00	•		•
GPS-10-35-200	10.00	35.00	6.00	20.00		•	
GPS-12-35-250-DC ⁽¹⁾	12.00	35.00	5.50	25.00	•		•
GPS-12-35-250	12.00	35.00	5.50	25.00		•	
GPS-14-40-250-DC ⁽¹⁾	14.00	40.00	7.50	25.00	•		•
GPS-14-40-250	14.00	40.00	7.50	25.00		•	
GPS-18-40-300-DC ⁽¹⁾	18.00	40.00	9.00	30.00	•		•


⁽¹⁾ DC - Double Chamfer

Universal Marking for Deep Drilling Tools



Guide Pad Grade Recommendation

Priority	Oil Coolant			Water Based Coolant		
	1	2	3	1	2	3
ISO-P	IC950	IC908	IC928	IC928	IC908	-
ISO-K	IC950	IC908	IC928	IC928	IC908	-
ISO-M	IC928	IC908	IC950	IC928	IC908	-
ISO-S	IC928	IC908	IC950	IC928	IC908	-




	Tool Diameter		Dimensions (mm)				Solid Carbide
	Min	Max	OAW	OAL	RE	OAH	Description
FINEBEAM	25.00	29.99	6	20	12	3	GPS-06-20-120-DC
	30.00	39.00	7	20	12	3.5	GPS-07-20-120-DC
	39.01	45.00	8	25	15.5	4.5	GPS-08-25-155-DC
	45.01	57.00	10	30	20	4.5	GPS-10-30-200-DC
	57.01	89.00	12	35	25	5.5	GPS-12-35-250-DC


FINEBEAM

DSD-EF-FB / DDD-EF-FB / DSD-IF-FB

Spare Parts List



Drill Diameter	Insert									Guide Pad		
	Peripheral Insert	Screw	Key	Intermediate Insert	Screw	Key	Central Insert	Screw	Key		Screw	Key
25.00 - 28.00	NPHT 060308R-G-P	SR11201753-2	T-7/5	NPMT 050304R-G-I	SR11201753-2	T-7/5	NPMT 050308L-G-C	SR11201753-2	T-7/5	GPS-06	SR11201753-1	T-7/5
	NPHT 060308R-HF-P	SR11201753-2	T-7/5	NPMT 050304R-HF-I	SR11201753-2	T-7/5	NPMT 050308L-HF-C	SR11201753-2	T-7/5	GPS-06	SR11201753-1	T-7/5
28.01 - 29.99	NPHT 060308R-G-P	SR11201753-2	T-7/5	NPMT 050304R-G-I	SR11201753-2	T-7/5	NPMT 060408L-G-C	SR 14-560-HG	T-8/5	GPS-06	SR11201753-1	T-7/5
	NPHT 060308R-HF-P	SR11201753-2	T-7/5	NPMT 050304R-HF-I	SR11201753-2	T-7/5	NPMT 060408L-HF-C	SR 14-560-HG	T-8/5	GPS-06	SR11201753-1	T-7/5
30.00 - 35.00	NPHT 070408R-G-P	SR 14-560-HG	T-8/5	NPMT 060404R-G-I	SR 14-560-HG	T-8/5	NPMT 060408L-G-C	SR 14-560-HG	T-8/5	GPS-07	SR11201753-4	T-9/5
	NPHT 070408R-HF-P	SR 14-560-HG	T-8/5	NPMT 060404R-HF-I	SR 14-560-HG	T-8/5	NPMT 060408L-HF-C	SR 14-560-HG	T-8/5	GPS-07	SR11201753-4	T-9/5
35.01 - 38.00	NPHT 070408R-G-P	SR 14-560-HG	T-8/5	NPMT 060404R-G-I	SR 14-560-HG	T-8/5	NPMT 080408L-G-C	SR 14-560-HG	T-8/5	GPS-07	SR11201753-4	T-9/5
	NPHT 070408R-HF-P	SR 14-560-HG	T-8/5	NPMT 060404R-HF-I	SR 14-560-HG	T-8/5	NPMT 080408L-HF-C	SR 14-560-HG	T-8/5	GPS-07	SR11201753-4	T-9/5
38.01 - 39.00	NPHT 090408R-G-P	SR 14-560-HG	T-8/5	NPMT 060404R-G-I	SR 14-560-HG	T-8/5	NPMT 080408L-G-C	SR 14-560-HG	T-8/5	GPS-07	SR11201753-4	T-9/5
	NPHT 090408R-HF-P	SR 14-560-HG	T-8/5	NPMT 060404R-HF-I	SR 14-560-HG	T-8/5	NPMT 080408L-HF-C	SR 14-560-HG	T-8/5	GPS-07	SR11201753-4	T-9/5
39.01 - 41.00	NPHT 090408R-G-P	SR 14-560-HG	T-8/5	NPMT 060404R-G-I	SR 14-560-HG	T-8/5	NPMT 080408L-G-C	SR 14-560-HG	T-8/5	GPS-08	SR11201753-4	T-9/5
	NPHT 090408R-HF-P	SR 14-560-HG	T-8/5	NPMT 060404R-HF-I	SR 14-560-HG	T-8/5	NPMT 080408L-HF-C	SR 14-560-HG	T-8/5	GPS-08	SR11201753-4	T-9/5
41.01 - 44.00	NPHT 090408R-G-P	SR 14-560-HG	T-8/5	NPMT 080404R-G-I	SR 14-560-HG	T-8/5	NPMT 080408L-G-C	SR 14-560-HG	T-8/5	GPS-08	SR11201753-4	T-9/5
	NPHT 090408R-HF-P	SR 14-560-HG	T-8/5	NPMT 080404R-HF-I	SR 14-560-HG	T-8/5	NPMT 080408L-HF-C	SR 14-560-HG	T-8/5	GPS-08	SR11201753-4	T-9/5
44.01 - 45.00	NPHT 090408R-G-P	SR 14-560-HG	T-8/5	NPMT 080404R-G-I	SR 14-560-HG	T-8/5	NPMT 090408L-G-C	SR 14-560-HG	T-8/5	GPS-08	SR11201753-4	T-9/5
	NPHT 090408R-HF-P	SR 14-560-HG	T-8/5	NPMT 080404R-HF-I	SR 14-560-HG	T-8/5	NPMT 090408L-HF-C	SR 14-560-HG	T-8/5	GPS-08	SR11201753-4	T-9/5
45.01 - 47.00	NPHT 090408R-G-P	SR 14-560-HG	T-8/5	NPMT 080404R-G-I	SR 14-560-HG	T-8/5	NPMT 090408L-G-C	SR 14-560-HG	T-8/5	GPS-10	SR11201753-6	T-15/5
	NPHT 090408R-HF-P	SR 14-560-HG	T-8/5	NPMT 080404R-HF-I	SR 14-560-HG	T-8/5	NPMT 090408L-HF-C	SR 14-560-HG	T-8/5	GPS-10	SR11201753-6	T-15/5
47.01 - 51.00	NPHT 110408R-G-P	SR 14-560-HG	T-8/5	NPMT 080404R-G-I	SR 14-560-HG	T-8/5	NPMT 090408L-G-C	SR 14-560-HG	T-8/5	GPS-10	SR11201753-6	T-15/5
	NPHT 110408R-HF-P	SR 14-560-HG	T-8/5	NPMT 080404R-HF-I	SR 14-560-HG	T-8/5	NPMT 090408L-HF-C	SR 14-560-HG	T-8/5	GPS-10	SR11201753-6	T-15/5
51.01 - 54.00	NPHT 110408R-G-P	SR 14-560-HG	T-8/5	NPMT 090404R-G-I	SR 14-560-HG	T-8/5	NPMT 090408L-G-C	SR 14-560-HG	T-8/5	GPS-10	SR11201753-6	T-15/5
	NPHT 110408R-HF-P	SR 14-560-HG	T-8/5	NPMT 090404R-HF-I	SR 14-560-HG	T-8/5	NPMT 090408L-HF-C	SR 14-560-HG	T-8/5	GPS-10	SR11201753-6	T-15/5
54.01 - 57.00	NPHT 110408R-G-P	SR 14-560-HG	T-8/5	NPMT 090404R-G-I	SR 14-560-HG	T-8/5	NPMT 120408L-G-C	SR 14-560-HG	T-8/5	GPS-10	SR11201753-6	T-15/5
	NPHT 110408R-HF-P	SR 14-560-HG	T-8/5	NPMT 090404R-HF-I	SR 14-560-HG	T-8/5	NPMT 120408L-HF-C	SR 14-560-HG	T-8/5	GPS-10	SR11201753-6	T-15/5
57.01 - 60.00	NPHT 110408R-G-P	SR 14-560-HG	T-8/5	NPMT 090404R-G-I	SR 14-560-HG	T-8/5	NPMT 120408L-G-C	SR 14-560-HG	T-8/5	GPS-12	SR11201753-6	T-15/5
	NPHT 110408R-HF-P	SR 14-560-HG	T-8/5	NPMT 090404R-HF-I	SR 14-560-HG	T-8/5	NPMT 120408L-HF-C	SR 14-560-HG	T-8/5	GPS-12	SR11201753-6	T-15/5
60.01 - 64.00	NPHT 130408R-G-P	SR 14-560-HG	T-8/5	NPMT 090404R-G-I	SR 14-560-HG	T-8/5	NPMT 120408L-G-C	SR 14-560-HG	T-8/5	GPS-12	SR11201753-6	T-15/5
	NPHT 130408R-HF-P	SR 14-560-HG	T-8/5	NPMT 090404R-HF-I	SR 14-560-HG	T-8/5	NPMT 120408L-HF-C	SR 14-560-HG	T-8/5	GPS-12	SR11201753-6	T-15/5
64.01 - 65.00	NPHT 130408R-G-P	SR 14-560-HG	T-8/5	NPMT 120404R-G-I	SR 14-560-HG	T-8/5	NPMT 120408L-G-C	SR 14-560-HG	T-8/5	GPS-12	SR11201753-6	T-15/5
	NPHT 130408R-HF-P	SR 14-560-HG	T-8/5	NPMT 120404R-HF-I	SR 14-560-HG	T-8/5	NPMT 120408L-HF-C	SR 14-560-HG	T-8/5	GPS-12	SR11201753-6	T-15/5



Tool Dia		Insert						Guide Pad		Wrench	
Min	Max	Center	Inner 1	Inner 2	Inner 3	Peripheral	Screw X 5 pcs	GPS X 2 pcs	Screw X 2 pcs	Insert	Pad
65.01	71.00	NPMT09....L**-C	NPMT08....R**-I	NPMT08....R**-I	NPMT06....R**-I	NPHT11....R**-P	SR 14-560-HG	GPS12	SR 11201753-6	T-8/5	T-15/5
71.01	83.00				NPMT08....R**-I	NPHT13....R**-P					
83.01	90.00	NPMT12....L**-C	NPMT08....R**-I	NPMT08....R**-I	NPMT08....R**-I	NPHT13....R**-P					



Machining Recommendations for FINEBEAM Drills


ISO	Material		Condition	Tensile Strength [N/mm ²]	Material Group No. ⁽¹⁾	Hardness (HB)	Chipbreaker	Cutting Speed V _c (m/min)	Feed : f (mm/rev)	
									Drill Dia. (mm)	
									25.00 - 43.00	43.01 - 89.00
P	non-alloy steel and cast steel, free cutting steel	<0.25% C	annealed	420	1	125	HF	70-130	0.11-0.41	0.14-0.45
							G	70-130	0.10-0.30	0.12-0.35
		≥0.25% C	annealed	650	2	190	HF	70-130	0.11-0.41	0.14-0.45
							G	70-130	0.10-0.30	0.12-0.35
		<0.55% C	quenched and tempered	850	3	250	HF	70-130	0.11-0.41	0.14-0.45
							G	70-130	0.10-0.30	0.12-0.35
		≥0.55% C	annealed	750	4	220	HF	70-130	0.11-0.41	0.14-0.45
								G	70-130	0.10-0.30
			quenched and tempered	1000	5	300	HF	70-130	0.11-0.41	0.14-0.45
							G	70-130	0.10-0.30	0.12-0.35
	low alloy and cast steel (less than 5% of alloying elements)	annealed	600	6	200	HF	70-120	0.11-0.41	0.20-0.45	
						G	70-120	0.10-0.30	0.12-0.35	
			quenched and tempered	930	7	275	HF	55-110	0.11-0.41	0.20-0.45
							G	60-120	0.10-0.30	0.12-0.35
		1000		8	300	HF	55-110	0.11-0.41	0.20-0.45	
						G	60-120	0.10-0.30	0.12-0.35	
		1200	9	350	HF	55-110	0.11-0.41	0.20-0.45		
						G	60-120	0.10-0.30	0.12-0.35	
		high alloyed steel, cast steel and tool steel	annealed	680	10	200	HF	55-110	0.11-0.38	0.20-0.40
							G	70-130	0.10-0.30	0.12-0.35
	quenched and tempered		1100	11	325	HF	55-110	0.11-0.38	0.20-0.40	
						G	70-130	0.10-0.30	0.12-0.35	
	stainless steel and cast steel	ferritic/martensitic	680	12	200	HF	40-110	0.11-0.41	0.20-0.45	
						G	70-130	0.10-0.30	0.12-0.35	
		martensitic	820	13	240	HF	40-110	0.11-0.41	0.20-0.45	
						G	70-130	0.10-0.30	0.12-0.35	
M	stainless steel and cast steel	austenitic, duplex	600	14	180	HF	40-110	0.11-0.41	0.20-0.45	
K	grey cast iron (GG)	ferritic/pearlitic		15	180	G	70-130	0.10-0.30	0.12-0.35	
		pearlitic/martensitic		16	260	HF	50-110	0.11-0.38	0.24-0.41	
						G	50-110	0.10-0.25	0.12-0.35	
	nodular cast iron (GGG)	ferritic		17	160	HF	50-110	0.11-0.38	0.24-0.41	
					G	50-110	0.10-0.25	0.12-0.35		
		pearlitic		18	250	HF	50-110	0.11-0.38	0.24-0.41	
						G	50-110	0.10-0.25	0.12-0.35	
	malleable cast iron	ferritic		19	130	HF	50-110	0.11-0.38	0.24-0.41	
					G	50-110	0.10-0.25	0.12-0.35		
		pearlitic		20	230	HF	50-110	0.11-0.38	0.24-0.41	
						G	50-110	0.10-0.25	0.12-0.35	
N	aluminum-wrought alloys	not hardenable		21	60	HF	65-150	0.09-0.33	0.24-0.35	
					G	65-130	0.10-0.25	0.12-0.35		
		hardenable		22	100	HF	65-150	0.09-0.33	0.24-0.35	
						G	65-130	0.08-0.23	0.12-0.27	
	aluminum-cast alloys	not hardenable		23	75	HF	65-150	0.09-0.33	0.24-0.35	
					G	65-130	0.08-0.23	0.12-0.27		
		≤ 12% Si				HF	65-150	0.09-0.33	0.24-0.35	
					G	65-130	0.08-0.23	0.12-0.27		
		hardenable		24	90	HF	65-150	0.09-0.33	0.24-0.35	
						G	65-130	0.08-0.23	0.12-0.27	
	copper alloys	>12% Si	high temperature	25	130	HF	65-150	0.09-0.33	0.24-0.35	
						G	65-130	0.08-0.23	0.12-0.27	
>1% Pb		free cutting	26	110	HF	65-150	0.09-0.33	0.24-0.35		
					G	65-130	0.08-0.23	0.12-0.27		
brass			27	90	HF	65-150	0.09-0.33	0.24-0.35		
					G	65-130	0.08-0.23	0.12-0.27		
		electrolitic copper		28	100	HF	65-150	0.09-0.33	0.24-0.35	
						G	65-130	0.08-0.23	0.12-0.27	
S	high temp. alloys	Fe based	annealed	31	200	HF	20-55	0.09-0.30	0.20-0.33	
						G	20-50	0.08-0.23	0.12-0.27	
			hardened		32	280	HF	20-55	0.09-0.30	0.20-0.33
							G	20-50	0.08-0.23	0.12-0.27
		Ni / Co based	annealed	33	250	HF	20-55	0.09-0.30	0.20-0.33	
						G	20-50	0.08-0.23	0.12-0.27	
			hardened		34	350	HF	20-55	0.09-0.30	0.20-0.33
							G	20-50	0.08-0.23	0.12-0.27
	titanium alloys	cast		35	320	HF	20-55	0.09-0.30	0.20-0.33	
						G	20-50	0.08-0.23	0.12-0.27	
		pure	400	36		HF	30-60	0.09-0.30	0.20-0.33	
						G	30-60	0.08-0.23	0.12-0.27	
H	hardened steel ≥ 40HRC	hardened	1050	37		HF	30-60	0.09-0.30	0.20-0.33	
						G	30-60	0.08-0.23	0.12-0.27	

⁽¹⁾ Based on ISO 513 and VDI 3323 standards




Technical Guide

STS - Setting guidelines for cutting loads, fluid pressure and flow rate during STS operation



DTS - Setting guidelines for cutting loads, fluid pressure and flow rate during DTS operation



The above values should not be used as the exact recommendations. They may need modification depending on the machining conditions, materials, etc.


ISCAR DEEP-DRILL Ø38 – 293.99 mm

DSD/DDD-EC/IC

ISCAR DEEP DRILL

DSD-EC

Deep Single Tube Drills
with External 4-Start
Thread Connection and
Cartridges (38-292 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	OAL	LF	DCONMS	Ts ⁽³⁾
DSD-EC 38.00-39.60	38.00	39.60	90.00	85.00	30.00	TS-I11
DSD-EC 39.61-43.00	39.61	43.00	91.00	85.00	33.00	TS-I12
DSD-EC 43.01-47.00	43.01	47.00	101.00	95.00	36.00	TS-I13
DSD-EC 47.01-51.70	47.01	51.70	102.00	95.00	39.00	TS-I14
DSD-EC 51.71-56.20	51.71	56.20	107.00	100.00	43.00	TS-I15
DSD-EC 56.21-60.60	56.21	60.60	118.00	110.00	47.00	TS-I16
DSD-EC 60.61-64.99	60.61	64.99	119.00	110.00	51.00	TS-I17
DSD-EC 65.00-66.99	65.00	66.99	159.00	150.00	52.00	TS-I18
DSD-EC 67.00-72.99	67.00	72.99	159.00	150.00	58.00	TS-I19
DSD-EC 73.00-79.99	73.00	79.99	160.00	150.00	63.00	TS-I20
DSD-EC 80.00-86.99	80.00	86.99	191.00	180.00	70.00	TS-I21
DSD-EC 87.00-99.99	87.00	99.99	193.00	180.00	77.00	TS-I22
DSD-EC 100.00-106.99	100.00	106.99	193.00	180.00	89.00	TS-I23
DSD-EC 107.00-111.99	107.00	111.99	197.00	180.00	89.00	TS-I23
DSD-EC 112.00-123.99	112.00	123.99	221.00	205.00	101.00	TS-I24
DSD-EC 124.00-135.99	124.00	135.99	222.00	205.00	113.00	TS-I25
DSD-EC 136.00-147.99	136.00	147.99	223.00	205.00	125.00	TS-I26
DSD-EC 148.00-159.99	148.00	159.99	245.00	225.00	137.00	TS-I27
DSD-EC 160.00-168.99	160.00	168.99	246.00	225.00	149.00	TS-I28
DSD-EC 169.00-171.99	169.00	171.99	246.00	225.00	149.00	TS-I28
DSD-EC 172.00-183.99	172.00	183.99	247.00	225.00	161.00	TS-I29
DSD-EC 184.00-195.99	184.00	195.99	267.00	245.00	173.00	TS-I30
DSD-EC 196.00-207.99	196.00	207.99	270.00	245.00	185.00	TS-I31
DSD-EC 208.00-219.99	208.00	219.99	271.00	245.00	197.00	TS-I32
DSD-EC 220.00-231.99	220.00	231.99	293.00	265.00	208.00	TS-I33
DSD-EC 232.00-232.99	232.00	232.99	293.00	265.00	220.00	TS-I34
DSD-EC 233.00-243.99	233.00	243.99	294.00	265.00	220.00	TS-I34
DSD-EC 244.00-255.99	244.00	255.99	294.00	265.00	232.00	TS-I35
DSD-EC 256.00-267.99	256.00	267.99	322.00	290.00	244.00	TS-I36
DSD-EC 268.00-279.99	268.00	279.99	323.00	290.00	256.00	TS-I37
DSD-EC 280.00-291.99	280.00	291.99	325.00	290.00	268.00	TS-I38

• Important: The specified drilling range using the original outer cartridge and pad may be enlarged by using optional outer cartridges and pads as specified on page 39

• For quotation form and user guide, see pages 101-102, 34-36, 40-45 • For spare parts, see pages 37-38 • Ordering example: DSD-EC 67.30

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Tube designation

For inserts, see pages: NPMX 0803 RB/RG (30) • TPMX (30)


For holders, see pages: TS-I** (86)



ISCARDEEPDRILL

DSD-IC

Deep Single Tube Drills
with Internal Single-Start
Thread Connection and
Cartridges (38-294 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	OAL	LF	DCONMS	TS ⁽³⁾
DSD-IC 38.00-39.99	38.00	39.99	85.00	80.00	30.00	TS-O15
DSD-IC 40.00-43.99	40.00	43.99	86.00	80.00	33.00	TS-O16
DSD-IC 44.00-46.99	44.00	46.99	96.00	90.00	37.00	TS-O17
DSD-IC 47.00-51.99	47.00	51.99	97.00	90.00	41.00	TS-O18
DSD-IC 52.00-56.99	52.00	56.99	107.00	100.00	44.00	TS-O19
DSD-IC 57.00-60.99	57.00	60.99	118.00	110.00	49.00	TS-O20
DSD-IC 61.00-67.99	61.00	67.99	119.00	110.00	53.00	TS-O21
DSD-IC 68.00-74.99	68.00	74.99	129.00	120.00	59.00	TS-O22
DSD-IC 75.00-80.99	75.00	80.99	161.00	150.00	65.00	TS-O23
DSD-IC 81.00-90.99	81.00	90.99	162.00	150.00	71.00	TS-O24
DSD-IC 91.00-98.99	91.00	98.99	162.00	150.00	79.00	TS-O25
DSD-IC 99.00-106.99	99.00	106.99	163.00	150.00	90.00	TS-O26
DSD-IC 107.00-110.99	107.00	110.99	164.00	150.00	90.00	TS-O26
DSD-IC 111.00-122.99	111.00	122.99	165.00	150.00	102.00	TS-O27
DSD-IC 123.00-134.99	123.00	134.99	167.00	150.00	114.00	TS-O28
DSD-IC 135.00-148.99	135.00	148.99	168.00	150.00	126.00	TS-O29
DSD-IC 149.00-161.99	149.00	161.99	170.00	150.00	139.00	TS-O30
DSD-IC 162.00-168.99	162.00	168.99	211.00	190.00	151.00	TS-O31
DSD-IC 169.00-173.99	169.00	173.99	211.00	190.00	151.00	TS-O31
DSD-IC 174.00-185.99	174.00	185.99	213.00	190.00	163.00	TS-O32
DSD-IC 186.00-197.99	186.00	197.99	212.00	190.00	175.00	TS-O33
DSD-IC 198.00-209.99	198.00	209.99	215.00	190.00	187.00	TS-O34
DSD-IC 210.00-221.99	210.00	221.99	217.00	190.00	199.00	TS-O35
DSD-IC 222.00-232.99	222.00	232.99	218.00	190.00	211.00	TS-O36
DSD-IC 233.00-233.99	233.00	233.99	217.00	190.00	211.00	TS-O36
DSD-IC 234.00-245.99	234.00	245.99	219.00	190.00	223.00	TS-O37
DSD-IC 246.00-257.99	246.00	257.99	221.00	190.00	235.00	TS-O38
DSD-IC 258.00-269.99	258.00	269.99	242.00	210.00	245.00	TS-O39
DSD-IC 270.00-281.99	270.00	281.99	244.00	210.00	259.00	TS-O40
DSD-IC 282.00-293.99	282.00	293.99	245.00	210.00	271.00	TS-O41

- Important: The specified drilling range using the original outer cartridge and pad may be enlarged by using optional outer cartridges and pads as specified on page 39
- For spare parts and insert information, see pages 37-38
- For user guide and quotation form, see pages 101-102, 34-36, 40-45
- Ordering example: DSD-IC 67.30

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Tube designation

For inserts, see pages: NPMX 0803 RB/RG (30) • TPMX (30)

For holders, see pages: TS-O** (87)

Universal Marking for Deep Drilling Tools

D- Tool Diameter

Metric- D197.00

Inch- D7.756

d- Pilot Diameter

Metric- d175

Inch- d6.890

Tool Style

K- solid drill cartridge style


Thread Type

4ST- four-start thread single tube

1ST- single-start thread single tube

4DT- four-start thread double tube


178- tube diameter



ISCARDEEPPDRILL

DDD-EC

Deep Double Tube Drills
with External 4-Start
Thread Connection and
Cartridges (38-184 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	OAL	LF	DCONMS	Ts ⁽³⁾	Tsi ⁽⁴⁾
DDD-EC 38.00-39.60	38.00	39.60	90.00	85.00	33.00	TDO-I8	TDI-N8
DDD-EC 39.61-43.00	39.61	43.00	91.00	85.00	36.00	TDO-I9	TDI-N9
DDD-EC 43.01-47.00	43.01	47.00	101.00	95.00	39.00	TDO-I10	TDI-N10
DDD-EC 47.01-51.70	47.01	51.70	102.00	100.00	43.00	TDO-I11	TDI-N11
DDD-EC 51.71-56.20	51.71	56.20	107.00	100.00	47.00	TDO-I12	TDI-N12
DDD-EC 56.21-64.99	56.21	65.00	119.00	110.00	51.00	TDO-I13	TDI-N13
DDD-EC 65.00-66.99	65.00	66.99	159.00	150.00	52.00	TDO-I14	TDI-N14
DDD-EC 67.00-72.99	67.00	72.99	159.00	150.00	58.00	TDO-I15	TDI-N15
DDD-EC 73.00-79.99	73.00	79.99	160.00	150.00	63.00	TDO-I16	TDI-N16
DDD-EC 80.00-86.99	80.00	86.99	191.00	180.00	70.00	TDO-I17	TDI-N17
DDD-EC 87.00-99.99	87.00	99.99	193.00	180.00	77.00	TDO-I18	TDI-N18
DDD-EC 100.00-106.99	100.00	106.99	193.00	180.00	89.00	TDO-I19	TDI-N19
DDD-EC 107.00-111.99	107.00	111.99	197.00	180.00	89.00	TDO-I19	TDI-N19
DDD-EC 112.00-123.99	112.00	123.99	221.00	205.00	101.00	TDO-I20	TDI-N20
DDD-EC 124.00-135.99	124.00	135.99	222.00	205.00	113.00	TDO-I21	TDI-N21
DDD-EC 136.00-147.99	136.00	147.99	223.00	205.00	125.00	TDO-I22	TDI-N22
DDD-EC 148.00-159.99	148.00	159.99	245.00	225.00	137.00	TDO-I23	TDI-N23
DDD-EC 160.00-168.99	160.00	168.99	246.00	225.00	149.00	TDO-I24	TDI-N24
DDD-EC 169.00-171.99	169.00	171.99	246.00	225.00	149.00	TDO-I24	TDI-N24
DDD-EC 172.00-183.99	172.00	183.99	247.00	225.00	161.00	TDO-I25	TDI-N25

- Important: The specified drilling range using the original outer cartridge and pad may be enlarged by using optional outer cartridges and pads as specified on page
- For spare parts and insert information, see pages 37-38 • For user guide and quotation form see pages 101-102, 34-36, 40-45 • Ordering example: DDD-EC 148.00

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Outer tube designation

⁽⁴⁾ Inner tube designation

For inserts, see pages: NPMX 0803 RB/RG (30) • TPMX (30)

For holders, see pages: TDO-I (D18.41-65.00) (88) • TDO-I (D65.00-171.99) (89)

Universal Marking for Deep Drilling Tools

D- Tool Diameter

Metric- D80.0

Inch- D3.150

d- Pilot Diameter

Metric- d70

Inch- d2.756

Tool Style

K- cartridge style solid drill


Thread Type

4ST- four-start thread single tube

1ST- single-start thread single tube

4DT- four-start thread double tube

75- tube diameter






ISCARDEEPDRILL

NPMX 0803 RB/RG

Inserts for Drilling Heads
DSD-EC / DDD-EC / DSD-IC




Designation	Dimensions				Tough ↔ Hard		
	IC	S	RE	L	IC8355	IC908	IC948
NPMX 080304R-B	8.00	3.18	0.40	8.36			•
NPMX 080308R-G	8.00	3.18	0.80	8.36	•	•	•

For tools, see pages: DDD-EC (29) • DSD-EC (27) • DSD-IC (28)

ISCARDEEPDRILL

TPMX







Inserts for Drilling / Counterboring
/ Trepanning Tools



Designation	Dimensions			Tough ↔ Hard			
	IC	S	RE	IC8355	IC908	IC948	IC806
TPMX 140304R-B	8.45	3.50	0.40		•		•
TPMX 140308L-G	8.45	3.50	0.80		•		
TPMX 140308R-B	8.45	3.50	0.80			•	•
TPMX 140308R-DT	8.45	3.50	0.80		•	•	
TPMX 140308R-G	8.45	3.50	0.80	•	•	•	•
TPMX 170404L-BG	10.30	4.00	0.40		•		
TPMX 170404R-B	10.30	4.00	0.40		•		•
TPMX 170408L-DT	10.30	4.00	0.80		•		
TPMX 170408L-G	10.30	4.00	0.80		•	•	
TPMX 170408R-B	10.30	4.00	0.80			•	•
TPMX 170408R-BG	10.30	4.00	0.80		•	•	•
TPMX 170408R-DT	10.30	4.00	0.80		•		
TPMX 170408R-G	10.30	4.00	0.80	•	•	•	•
TPMX 240504L-BG	14.20	5.50	0.40		•		
TPMX 240504R-B	14.20	5.50	0.40		•		•
TPMX 240512L-DT	14.20	5.50	1.20		•		
TPMX 240512L-G	14.20	5.50	1.20		•	•	
TPMX 240512R-B	14.20	5.50	1.20			•	•
TPMX 240512R-BG	14.20	5.50	1.20		•	•	•
TPMX 240512R-DT	14.20	5.50	1.20		•	•	
TPMX 240512R-G	14.20	5.50	1.20	•	•	•	•
TPMX 280708L-BG	17.00	7.50	0.80		•		
TPMX 280708R-B	17.00	7.50	0.80		•		•
TPMX 280716L-G	17.00	7.50	1.60		•	•	
TPMX 280716R-B	17.00	7.50	1.60			•	•
TPMX 280716R-BG	17.00	7.50	1.60		•	•	•
TPMX 280716R-DT	17.00	7.50	1.60		•	•	
TPMX 280716R-G	17.00	7.50	1.60	•	•	•	•

For tools, see pages: DDC-EC (69) • DDD-EC (29) • DSC-EC (55) • DSC-IC (62) • DSD-EC (27) • DSD-IC (28) • DSTR-EC (76) • DSTR-IC (78)


Chipbreaker Selection

Chipbreaker Selection					
G			B		
	versatile			good chip control for heat-resistant alloy	
BG			DT		
	chip control for difficult-to-cut steel			to reduce machine load	

ISCARDEEPDRILL

SGP

Drilling Head Sub-Guide Pads




Designation	OAL	OAW	OAH
SGP-01	10.00	6.00	3.00
SGP-02	10.00	8.00	4.50
SGP-03	10.00	10.00	5.00
SGP-04	20.00	14.00	7.00

- Select an outer cartridge and pad for the required enlarged diameter.

ISCARDEEPDRILL

GPP

Drilling Head Guide
Pad Protectors



Designation	OAL	OAW	OAH
GPP-06	8.00	8.00	4.50
GPP-07	10.00	10.00	6.00
GPP-08	14.00	14.00	7.50
GPP-09	18.00	18.00	9.00

- Select an outer cartridge and pad for the required enlarged diameter.

Recommended claming torque

Insert Screw	
	(N·m)
SR 11201753-2	1
SR 11201753-3	1.3
SR 11201753-7	2.3
SR 11201753-9	3.5
SR 11201753-7	5

Cartridge Screw	
	(N·m)
SR 11201752-1	3.5
SR 11201753-5	2.3
SR 11201753-5	3.5
SR 11201756-7	3
SR 11201756-10	2.2
SR 11201756-11	2.2
SR 11201756-12	3
SR 11201756-15	5

Guide Pad Screw	
	(N·m)
SR 14-571/5	3.5
SR 34-506-C	2.3
LS1206SSS	3






ISCARDEEPCDRILL

GPS


Deep Drilling Solid Carbide Guide Pads



Designation	Dimensions				Tough $\longleftrightarrow$ Hard		
	OAW	OAL	OAH	RE	IC928	IC950	IC908
GPS-04-16-045-DC ⁽¹⁾	4.00	16.00	1.80	4.50			●
GPS-04-16-050-DC ⁽¹⁾	4.00	16.00	1.80	5.00			●
GPS-04-16-055-DC ⁽¹⁾	4.00	16.00	2.00	5.50	●		●
GPS-05-18-060-DC ⁽¹⁾	5.00	18.00	2.50	6.00	●		●
GPS-05-18-075-DC ⁽¹⁾	5.00	18.00	2.50	7.50	●		●
GPS-06-20-075-DC ⁽¹⁾	6.00	20.00	3.00	7.50			●
GPS-06-20-075	6.00	20.00	3.00	7.50		●	
GPS-06-20-085-DC ⁽¹⁾	6.00	20.00	3.00	8.50	●		●
GPS-06-20-085	6.00	20.00	3.00	8.50		●	
GPS-06-20-100-DC ⁽¹⁾	6.00	20.00	3.00	10.00	●		●
GPS-06-20-100	6.00	20.00	3.00	10.00		●	
GPS-06-20-120-DC ⁽¹⁾	6.00	20.00	3.00	12.00	●		●
GPS-06-20-120	6.00	20.00	3.00	12.00		●	
GPS-07-20-120-DC ⁽¹⁾	7.00	20.00	3.50	12.00	●		●
GPS-07-20-120	7.00	20.00	3.50	12.00		●	
GPS-08-25-155-DC ⁽¹⁾	8.00	25.00	4.50	15.50	●		●
GPS-08-25-155	8.00	25.00	4.50	15.50		●	
GPS-10-30-200-DC ⁽¹⁾	10.00	30.00	4.50	20.00	●		●
GPS-10-30-200	10.00	30.00	4.50	20.00		●	
GPS-10-35-200-DC ⁽¹⁾	10.00	35.00	6.00	20.00	●		●
GPS-10-35-200	10.00	35.00	6.00	20.00		●	
GPS-12-35-250-DC ⁽¹⁾	12.00	35.00	5.50	25.00	●		●
GPS-12-35-250	12.00	35.00	5.50	25.00		●	
GPS-14-40-250-DC ⁽¹⁾	14.00	40.00	7.50	25.00	●		●
GPS-14-40-250	14.00	40.00	7.50	25.00		●	
GPS-18-40-300-DC ⁽¹⁾	18.00	40.00	9.00	30.00	●		●

⁽¹⁾ DC - Double Chamfer

Universal Marking for Deep Drilling Tools




Guide Pad Grade Recommendation

Priority	Oil Coolant			Water Based Coolant		
	1	2	3	1	2	3
ISO-P	IC950	IC908	IC928	IC928	IC908	-
ISO-K	IC950	IC908	IC928	IC928	IC908	-
ISO-M	IC928	IC908	IC950	IC928	IC908	-
ISO-S	IC928	IC908	IC950	IC928	IC908	-


ISCARDEEPDRILL

CAOD

Drilling / Boring Head
Peripheral Cartridge



Universal Marking for Deep Drilling Tools



CA - P - DR - 0800 - R

Peripheral Cartridge DR : Drilling
CB : Counter Bore IC L/R HAND


Spare Parts

Designation	Adjustment Screw	Key	Locking Screw	Key	Insert	Insert Clamping Screw
CAOD-080	SR 11201755-4	HW 1.5	SR 11201756-11	HW 2.0	NPMX 0803..R-G	SR 11201753-2
CAOD-0845	SR 11201755-6	HW 2.0	SR 11201756-10	HW 2.5	TPMX 1403..R-G	SR 11201753-3
CAOD-085	SR 11201755-7	HW 1.5	SR 11201756-11	HW 2.0	NPMX 0803..R-G	SR 11201753-2
CAOD-103	SR 11201755-8	HW 2.5	SR 11201756-12	HW 3.0	TPMX 1704..R-G	SR 11201753-7
CAOD-142	SR 11201755-9	HW 2.5	SR 11201756-15	HW 4.0	TPMX 2405..R-G	SR 11201753-9
CAOD-170	SR 11201755-11	HW 3.0	SR 11201756-15	HW 4.0	TPMX 2807..R-G	SR 11201753-10


ISCARDEEPDRILL

CAID

Drilling head Inner Cartridge



Universal Marking for Deep Drilling Tools



CA - I - 0845 - R

Internal Cartridge IC L/R HAND

Spare Parts

Designation	Locking Screw	Key	Insert	Insert Clamping Screw	Key
CAID-080	SR 11201753-5	T-9/51	NPMX 0803..R-G	SR 11201753-2	T-7/51
CAID-0845	SR 11201753-6	T-15/51	TPMX 1403..R-G	SR 11201753-3	T-8/51
CAID-085	SR 11201753-5	T-9/51	NPMX 0803..R-G	SR 11201753-2	T-7/51
CAID-103	SR 11201752-1	T-15/51	TPMX 1704..R-G	SR 11201753-7	T-9/51
CAID-142	SR 11201756-7	HW 3.0	TPMX 2405..R-G	SR 11201753-9	T-15/51
CAID-170	SR 11201756-7	HW 3.0	TPMX 2807..R-G	SR 11201753-10	T-20/51

Chip Form General Information

Chip Form in Deep Hole Drilling

Chip form plays a key role in STS (Single tube system) and DTS (Double tube system) while large-volume and high-pressure coolant do so as well. Because chips are removed through the tube with coolant, proper chip formation is essential for smooth and steady evacuation.

Chip Formation

Chip formation is affected by multiple factors, such as workpiece material, chipbreaker geometry, cutting speed, feed, type of coolant, and coolant temperature. Suitable chip formation depends on cutting operation but is controllable by changing the cutting conditions.

How to Decide the Chip Form



Generally the chip length should be 3 - 4 times its width, but tends to be longer with difficult-to-cut materials. In this case, chip evacuation can be improved by making the chips thinner, which is normally done by reducing the feed rate.

The graph below shows chip formation for different cutting speeds and feeds. Short chips are created by reducing the cutting speed or increasing the feed.



Table 1						
				Central	Intermediate	Peripheral
Cutting Speed: V_c (m/min)	110					
	90					
	70					
	50					
Condition		0.10	0.15	0.20		
		Feed: f (mm/rev)				

From left to right in each box the order is central, intermediate and peripheral chip.





$\varnothing 38.00-106.99 \text{ mm}$




Part positions may vary depending on the drill size.

 $\varnothing 169.00-232.99 \text{ mm}$


Part positions may vary depending on the drill size.

 $\varnothing 107.00-168.99 \text{ mm}$


Part positions may vary depending on the drill size.

 $\varnothing 233.00-291.99 \text{ mm}$


Part positions may vary depending on the drill size.


* For more information regarding the filler please see page 36



Guide Pads

Guide pads are subject to wear, like inserts.

- Each guide pad can be used on two sides. When the first corner wears out 70% of the width, reverse the guide pad to use the second corner.
- Replace with a new guide pad when the second corner wears out.



For higher wear resistance


- High wear-resistant grade.

First recommendation

- Suitable for various workpiece materials.
- Long tool life due to unique substrate and coating.


For higher fracture resistance

- High fracture-resistant grade.



Please replace the filler with the top guide pad when:

- High hole accuracy is required.
- L/D (hole length-to-diameter) ratio is greater than 50:1.
- Drilling a workpiece which has a tail stock hole.
- The DOC required is greater than the range of the peripheral insert for counterboring. *See chart below.






*Maximum DOC of peripheral insert.

Cartridge	DOC (mm)	Guide pad
CAOD-0845	6.4	GPS-08.../GPS-10...
CAOD-103	7.2	GPS-10.../GPS-14...
CAOD-142	10.4	GPS-14.../GPS-18...
CAOD-170	12.0	GPS-18...

For diameter less than 92 mm, the drill head is semi-standard using the top guide pad. Please contact your dealer for further information.


Guide Pad		
	Screw	Key
GPS-05	SR 34-508 M2.2X0.45	T-7/5
GPS-06	SR 11201753-1	T-7/5
GPS-07	SR 11201753-4	T-9/5
GPS-08	SR 11201753-4	T-9/5
GPS-10	SR 11201753-8	T-15/5
GPS-12	SR 11201753-8	T-15/5
GPS-14	SR 11201752-2	T-15/5
GPS-18	SR 11201756-7S	T-15/5


Spare Parts

DSD-EC / DDD-EC / DSD-IC														
Diameter	Peripheral	Qty.	Inner/ Central	Qty.	Guide Pad	Qty.	Guide Pad Protectors	Qty.	Sub Guide Pad	Qty.	Peripheral Insert	Qty.	Inner/ Central Insert	Qty.
38.00-39.99	CAOD-080	1	CAID-080	1	GPS-08-25-155-DC	2	GPP-06	2	SGP-02	1	NPMX 08**R..	1	NPMX 08**R..	1
			CAID-080	1									NPMX 08**R..	1
40.00-44.99	CAOD-0845	1	CAID-080	1	GPS-08-25-155-DC	2	GPP-06	2	SGP-02	1	TPMX 14**R..	1	NPMX 08**R..	1
			CAID-080	1									NPMX 08**R..	1
45.00-47.99	CAOD-0845	1	CAID-080	1	GPS-10-35-200-DC	2	GPP-07	2	SGP-02	1	TPMX 14**R..	1	NPMX 08**R..	1
			CAID-0845	1									TPMX 14**R..	1
48.00-51.99	CAOD-0845	1	CAID-0845	1	GPS-10-35-200-DC	2	GPP-07	2	SGP-02	1	TPMX 14**R..	1	TPMX 14**R..	1
			CAID-0845	1									TPMX 14**R..	1
52.00-54.99	CAOD-103	1	CAID-0845	1	GPS-10-35-200-DC	2	GPP-07	2	SGP-02	1	TPMX 17**R..	1	TPMX 14**R..	1
			CAID-0845	1									TPMX 14**R..	1
55.00-57.99	CAOD-103	1	CAID-0845	1	GPS-10-35-200-DC	2	GPP-07	2	SGP-02	1	TPMX 17**R..	1	TPMX 14**R..	1
			CAID-103	1									TPMX 17**R..	1
58.00-59.99	CAOD-103	1	CAID-103	1	GPS-10-35-200-DC	2	GPP-07	2	SGP-02	1	TPMX 17**R..	1	TPMX 17**R..	1
			CAID-103	1									TPMX 17**R..	1
60.00-63.99	CAOD-103	1	CAID-103	1	GPS-14-40-250-DC	2	GPP-08	2	SGP-02	1	TPMX 17**R..	1	TPMX 17**R..	1
			CAID-103	1									TPMX 17**R..	1
64.00-67.99	CAOD-142	1	CAID-103	1	GPS-14-40-250-DC	2	GPP-08	2	SGP-03	1	TPMX 24**R..	1	TPMX 17**R..	1
			CAID-103	1									TPMX 17**R..	1
68.00-77.99	CAOD-103	1	CAID-142	1	GPS-14-40-250-DC	2	GPP-08	2	SGP-03	1	TPMX 17**R..	1	TPMX 24**R..	1
			CAID-142	1									TPMX 24**R..	1
78.00-84.99	CAOD-142	1	CAID-142	1	GPS-14-40-250-DC	2	GPP-08	2	SGP-03	1	TPMX 24**R..	1	TPMX 24**R..	1
			CAID-142	1									TPMX 24**R..	1
85.00-91.99	CAOD-170	1	CAID-142	1	GPS-14-40-250-DC	2	GPP-08	2	SGP-03	1	TPMX 28**R..	1	TPMX 24**R..	1
			CAID-142	1									TPMX 24**R..	1
92.00-98.99	CAOD-142	1	CAID-170	1	GPS-14-40-250-DC	2	GPP-08	2	SGP-03	1	TPMX 24**R..	1	TPMX 28**R..	1
			CAID-170	1									TPMX 28**R..	1
99.00-106.99	CAOD-170	1	CAID-170	1	GPS-18-40-300-DC	2	GPP-09	2	SGP-04	1	TPMX 28**R..	1	TPMX 28**R..	1
			CAID-170	1									TPMX 28**R..	1
107.00-117.99	CAOD-142	1	CAID-103	3	GPS-18-40-300-DC	2	GPP-09	2	SGP-04	1	TPMX 24**R..	1	TPMX 17**R..	3
			CAID-142	1									TPMX 24**R..	1
118.00-135.99	CAOD-142	1	CAID-142	3	GPS-18-40-300-DC	2	GPP-09	2	SGP-04	1	TPMX 24**R..	1	TPMX 24**R..	3
			CAID-142	1									TPMX 24**R..	1
136.00-144.99	CAOD-142	1	CAID-142	3	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 24**R..	1	TPMX 24**R..	3
			CAID-170	1									TPMX 28**R..	1
145.00-150.99	CAOD-142	1	CAID-142	2	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 24**R..	1	TPMX 24**R..	2
			CAID-170	1									TPMX 28**R..	1
			CAID-170	1									TPMX 28**R..	1
151.00-156.99	CAOD-170	1	CAID-142	2	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 24**R..	2
			CAID-170	1									TPMX 28**R..	1
			CAID-170	1									TPMX 28**R..	1
157.00-162.99	CAOD-170	1	CAID-142	1	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 24**R..	1
			CAID-170	2									TPMX 28**R..	2
			CAID-170	1									TPMX 28**R..	1
163.00-168.99	CAOD-170	1	CAID-170	3	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 28**R..	3
			CAID-170	1									TPMX 28**R..	1
169.00-188.99	CAOD-142	1	CAID-142	5	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 24**R..	1	TPMX 24**R..	5
			CAID-142	1									TPMX 24**R..	1
189.00-196.99	CAOD-142	1	CAID-142	5	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 24**R..	1	TPMX 24**R..	5
			CAID-170	1									TPMX 28**R..	1
197.00-202.99	CAOD-142	1	CAID-142	4	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 24**R..	1	TPMX 24**R..	4
			CAID-170	1									TPMX 28**R..	1
			CAID-170	1									TPMX 28**R..	1
203.00-208.99	CAOD-142	1	CAID-142	3	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 24**R..	1	TPMX 24**R..	3
			CAID-170	2									TPMX 28**R..	2
			CAID-170	1									TPMX 28**R..	1
209.00-214.99	CAOD-170	1	CAID-142	3	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 24**R..	3
			CAID-170	2									TPMX 28**R..	2
			CAID-170	1									TPMX 28**R..	1





Spare Parts

DSD-EC / DDD-EC / DSD-IC														
Diameter	Peripheral	Qty.	Inner/ Central	Qty.	Guide Pad	Qty.	Guide Pad Protectors	Qty.	Sub Guide Pad	Qty.	Peripheral Insert	Qty.	Inner/ Central Insert	Qty.
215.00-220.99	CAOD-170	1	CAID-142	2	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 24**R..	2
			CAID-170	3									TPMX 28**R..	3
			CAID-170	1									TPMX 28**R..	1
221.00-226.99	CAOD-170	1	CAID-142	1	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 24**R..	1
			CAID-170	4									TPMX 28**R..	4
			CAID-170	1									TPMX 28**R..	1
227.00-232.99	CAOD-170	1	CAID-170	5	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 28**R..	5
			CAID-170	1									TPMX 28**R..	1
233.00-247.99	CAOD-142	1	CAID-142	7	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 24**R..	1	TPMX 24**R..	7
			CAID-170	1									TPMX 28**R..	1
248.00-253.99	CAOD-170	1	CAID-142	7	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 24**R..	7
			CAID-170	1									TPMX 28**R..	1
254.00-258.99	CAOD-170	1	CAID-142	6	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 24**R..	6
			CAID-170	1									TPMX 28**R..	1
			CAID-170	1									TPMX 28**R..	1
259.00-264.99	CAOD-170	1	CAID-142	5	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 24**R..	5
			CAID-170	2									TPMX 28**R..	2
			CAID-170	1									TPMX 28**R..	1
265.00-271.99	CAOD-170	1	CAID-142	4	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 24**R..	4
			CAID-170	3									TPMX 28**R..	3
			CAID-170	1									TPMX 28**R..	1
272.00-275.99	CAOD-170	1	CAID-142	3	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 24**R..	3
			CAID-170	4									TPMX 28**R..	4
			CAID-170	1									TPMX 28**R..	1
276.00-284.99	CAOD-170	1	CAID-142	2	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 24**R..	2
			CAID-170	5									TPMX 28**R..	5
			CAID-170	1									TPMX 28**R..	1
285.00-289.99	CAOD-170	1	CAID-142	1	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 24**R..	1
			CAID-170	6									TPMX 28**R..	6
			CAID-170	1									TPMX 28**R..	1
290.00-293.99	CAOD-170	1	CAID-170	7	GPS-18-40-300-DC	4	GPP-09	4	SGP-04	1	TPMX 28**R..	1	TPMX 28**R..	7
			CAID-170	1									TPMX 28**R..	1



(+) Plus Parts for Diameter Enlargement

By exchanging only the peripheral cartridge and guide pads, the original head diameter can be increased up to 5 mm.
(Standard plus parts = 1 mm, 2 mm, 3 mm, 4 mm, 5 mm)

+ Plus						
	+1	+2	+3	+4	+5	
	0.039"	0.079"	0.118"	0.157"	0.197"	

Plus Cartridge - CAOD

Original	+1 mm	+2 mm	+3 mm	+4 mm	+5 mm
CAOD-080	CAOD-080+1	CAOD-080+2	-	-	-
CAOD-0845	CAOD-0845+1	CAOD-0845+2	CAOD-0845+3	-	-
CAOD-103	CAOD-103+1	CAOD-103+2	CAOD-103+3	CAOD-103+4	-
CAOD-142	CAOD-142+1	CAOD-142+2	CAOD-142+3	CAOD-142+4	CAOD-142+5
CAOD-170	CAOD-170+1	CAOD-170+2	CAOD-170+3	CAOD-170+4	CAOD-170+5

Plus Cartridge - CAORC



Original Cartridge	+1 mm	+2 mm	+3 mm	+4 mm	+5 mm
CAORC-0845	CAORC-0845+1	CAORC-0845+2	CAORC-0845+3	-	-
CAORC-103	CAORC-103+1	CAORC-103+2	CAORC-103+3	CAORC-103+4	-
CAORC-142	CAORC-142+1	CAORC-142+2	CAORC-142+3	CAORC-142+4	CAORC-142+5
CAORC-170	CAORC-170+1	CAORC-170+2	CAORC-170+3	CAORC-170+4	CAORC-170+5

Plus Guide Pad

Original Pad	+1 mm	+2 mm	+3 mm	+4 mm	+5 mm
GPS-08-25-155	GPS-08-25-160-DC+1	GPS-08-25-165-DC+2	GPS-08-25-170-DC+3	-	-
GPS-10-35-200	GPS-10-35-205-DC+1	GPS-10-35-210-DC+2	GPS-10-35-215-DC+3	GPS-10-35-220-DC+4	-
GPS-14-40-250	GPS-14-40-255-DC+1	GPS-14-40-260-DC+2	GPS-14-40-265-DC+3	GPS-14-40-270-DC+4	GPS-14-40-275-DC+5
GPS-18-40-300	GPS-18-40-305-DC+1	GPS-18-40-310-DC+2	GPS-18-40-315-DC+3	GPS-18-40-320-DC+4	GPS-18-40-325-DC+5

ISCARDEEPDRILL**CAOD**

Drilling Head Peripheral Cartridge


**Universal Marking for Deep Drilling Tools**

CA - P - DR - 0800 - R

Peripheral Cartridge DR : Drilling CB : Counter Bore IC L/R HAND

Spare Parts

Designation	Adjustment Screw	Key	Locking Screw	Key	Insert	Insert Clamping Screw
CAOD-080+1	SR 11201755-4	HW 1.5	SR 11201756-11	HW 2.0	NPMX 0803..R-G	SR 11201753-2
CAOD-080+2	SR 11201755-4	HW 1.5	SR 11201756-11	HW 2.0	NPMX 0803..R-G	SR 11201753-2
CAOD-085+1	SR 11201755-7	HW 1.5	SR 11201756-11	HW 2.0	NPMX 0803..R-G	SR 11201753-2
CAOD-085+2	SR 11201755-7	HW 1.5	SR 11201756-11	HW 2.0	NPMX 0803..R-G	SR 11201753-2
CAOD-085+3	SR 11201755-7	HW 1.5	SR 11201756-11	HW 2.0	NPMX 0803..R-G	SR 11201753-2
CAOD-103+1	SR 11201755-8	HW 2.5	SR 11201756-12	HW 3.0	TPMX 1704..R-G	SR 11201753-7
CAOD-103+2	SR 11201755-8	HW 2.5	SR 11201756-12	HW 3.0	TPMX 1704..R-G	SR 11201753-7
CAOD-103+3	SR 11201755-8	HW 2.5	SR 11201756-12	HW 3.0	TPMX 1704..R-G	SR 11201753-7
CAOD-103+4	SR 11201755-8	HW 2.5	SR 11201756-12	HW 3.0	TPMX 1704..R-G	SR 11201753-7
CAOD-142+1	SR 11201755-9	HW 2.5	SR 11201756-15	HW 4.0	TPMX 2405..R-G	SR 11201753-9
CAOD-142+2	SR 11201755-9	HW 2.5	SR 11201756-15	HW 4.0	TPMX 2405..R-G	SR 11201753-9
CAOD-142+3	SR 11201755-9	HW 2.5	SR 11201756-15	HW 4.0	TPMX 2405..R-G	SR 11201753-9
CAOD-142+4	SR 11201755-9	HW 2.5	SR 11201756-15	HW 4.0	TPMX 2405..R-G	SR 11201753-9
CAOD-142+5	SR 11201755-9	HW 2.5	SR 11201756-15	HW 4.0	TPMX 2405..R-G	SR 11201753-9
CAOD-170+1	SR 11201755-11	HW 3.0	SR 11201756-15	HW 4.0	TPMX 2807..R-G	SR 11201753-10
CAOD-170+2	SR 11201755-11	HW 3.0	SR 11201756-15	HW 4.0	TPMX 2807..R-G	SR 11201753-10
CAOD-170+3	SR 11201755-11	HW 3.0	SR 11201756-15	HW 4.0	TPMX 2807..R-G	SR 11201753-10
CAOD-170+4	SR 11201755-11	HW 3.0	SR 11201756-15	HW 4.0	TPMX 2807..R-G	SR 11201753-10
CAOD-170+5	SR 11201755-11	HW 3.0	SR 11201756-15	HW 4.0	TPMX 2807..R-G	SR 11201753-10



Deep Hole Drilling Index

Single Tube System

Single Tube System (STS) –

Cooling fluid is induced through the gap between the drill and the hole. Conveying the chips through the tube requires the use of dedicated machines.




Double Tube System

Double Tube System (DTS) -

Cooling fluid is induced between the coaxial tubes, conveying the chips through the inner tube and can be applied on standard machines.



Deep Drilling Heads Identification System





Machining Recommendations

ISO	Material		Condition	Tensile Strength [N/mm²]	Material Group No. ⁽¹⁾	Hardness HB	Chipbreaker		
							Troubleshooting		
							First Choice	Fracture	Wear
P	non-alloy steel and cast steel, free cutting steel	<0.25% C	annealed	420	1	125	G IC908	BG IC806	B IC9025
		≥0.25% C	annealed	650	2	190			
		<0.55% C	quenched and tempered	850	3	250			
		≥0.55% C	annealed	750	4	220			
			quenched and tempered	1000	5	300			
	low alloy and cast steel (less than 5% of alloying elements)		annealed	600	6	200	G IC908	BG IC806	B IC9025
			quenched and tempered	930	7	275			
				1000	8	300			
				1200	9	350			
	high alloyed steel, cast steel and tool steel		annealed	680	10	200	G IC908	BG IC806	B IC9025
			quenched and tempered	1100	11	325	IC908	IC806	IC9025
	stainless steel and cast steel		ferritic/martensitic	680	12	200	G IC908	BG IC806	B IC9025
			martensitic	820	13	240	IC908	IC806	IC9025
M	stainless steel and cast steel	austenitic, duplex	600	14	180	G IC806	B IC908	B IC9025	
K	grey cast iron (GG)	ferritic/pearlitic		15	180	G IC908	G IC806	B IC9025	
		pearlitic/martensitic		16	260				
	nodular cast iron (GGG)	ferritic		17	160				
		pearlitic		18	250				
	malleable cast iron	ferritic		19	130				
		pearlitic		20	230				
N	aluminum-wrought alloys	not hardenable		21	60	G IC908	G IC806	B IC9025	
		hardenable		22	100				
	aluminum- cast alloys	not hardenable		23	75				
		hardenable		24	90				
		>12% Si	high temperature		25				130
	>1% Pb	free cutting		26	110				
		copper alloys	brass		27				90
			electrolitic copper		28				100
	non-metallic	duroplastics, fiber plastics		29					
hard rubber			30						
S	high temp. alloys	Fe based	annealed		31	200	B IC806	B IC908	B IC9025
			hardened		32	280			
		Ni or Co based	annealed		33	250			
			hardened		34	350			
			cast		35	320			
	titanium alloys	pure	400	36					
		alpha+beta alloys hardened	1050	37					
H	hardened steel	hardened 55 HRC		38		B IC806	B IC908	B IC908	
		hardened 60 HRC		39					
	chilled cast iron	cast		40	400				
	cast iron	hardened 55 HRC		41					






⁽¹⁾ Based on ISO 513 and VDI 3323 standards

Indexable Drill Heads DSD-EC, DDD-EC, DSD-IC					
Dia. Range	38.00-39.99	40.00-51.99	52.00-63.99	64.00-84.99	85.00-293.00
V _c (m/min)	Feed Rate f (mm/rev)				
60-120	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
60-120	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
60-120	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
60-120	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
60-120	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
60-100	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
60-100	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
50-100	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
50-100	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
60-120	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
60-120	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
60-110	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
60-110	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
60-110	0.08-0.15	0.1-0.2	0.13-0.23	0.15-0.25	0.18-0.3
80-140	0.20-0.30	0.20-0.30	0.24-0.32	0.24-0.32	0.25-0.40
80-140	0.20-0.30	0.20-0.30	0.24-0.32	0.24-0.32	0.25-0.40
80-140	0.20-0.30	0.20-0.30	0.24-0.32	0.24-0.32	0.25-0.40
80-140	0.20-0.30	0.20-0.30	0.24-0.32	0.24-0.32	0.25-0.40
80-140	0.20-0.30	0.20-0.30	0.24-0.32	0.24-0.32	0.25-0.40
80-140	0.20-0.30	0.20-0.30	0.24-0.32	0.24-0.32	0.25-0.40
100-200	0.08-0.2	0.1-0.25	0.13-0.28	0.15-0.3	0.18-0.33
100-200	0.08-0.2	0.1-0.25	0.13-0.28	0.15-0.3	0.18-0.33
100-200	0.08-0.2	0.1-0.25	0.13-0.28	0.15-0.3	0.18-0.33
100-200	0.08-0.2	0.1-0.25	0.13-0.28	0.15-0.3	0.18-0.33
100-200	0.08-0.2	0.1-0.25	0.13-0.28	0.15-0.3	0.18-0.33
100-200	0.08-0.2	0.1-0.25	0.13-0.28	0.15-0.3	0.18-0.33
100-200	0.08-0.2	0.1-0.25	0.13-0.28	0.15-0.3	0.18-0.33
100-200	0.08-0.2	0.1-0.25	0.13-0.28	0.15-0.3	0.18-0.33
60-130	0.08-0.2	0.1-0.25	0.13-0.28	0.15-0.3	0.18-0.33
60-130	0.08-0.2	0.1-0.25	0.13-0.28	0.15-0.3	0.18-0.33
20-65	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
20-65	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
20-65	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
30-100	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
30-100	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
30-60	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
30-60	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
30-80	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.15-0.28
30-80	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.15-0.28
30-80	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.15-0.28
30-80	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.15-0.28








Technical Guide

Setting guidelines for cutting loads, fluid pressure and flow rate during STS operation




Setting guidelines for cutting loads, fluid pressure and flow rate during DTS operation




Technical Information - Cartridge Style Drill Head Diameter Settings

The drill head diameter is set and inspected with a master insert in our final inspection. However, the inserts in the market have a tolerance fluctuation so each time you index the insert, the diameter must be adjusted as per the following method.


Note: When a corner change is made on the insert, it must be adjusted to the correct size or damage can be caused to the head / body or workpiece material.




1. Remove the inner cartridge to avoid interference with the guide screw




2. The dimensional guide pad must be slid forward to measure the diameter
2.1 Loosen the lock screw and slide the guide pad forward
2.2 Re-tighten the lock screw at the measuring position




3. Measure the diameter with a micrometer. We recommend setting the tool diameter at h8 tolerance to the cutting diameter. If the diameter is incorrect, go to step 4 below. If it's correct, go to step 5 below




4. Adjust the outer cartridge
4.1 First loosen the lock screw of the outer cartridge and then tighten it slightly



4.2 Proceed to adjust the diameter, using the 2 adjustment screws and measure with a micrometer



4.3 When set to the size, re-tighten the lock screw
4.4 Recheck the diameter with a micrometer. If it is still out of tolerance, repeat the procedure from steps 1-4
Note: Please make sure to tighten the lock screw firmly before use. If loose, the cartridge may move and cause serious problems during machining



5. Slide the dimensional guide pad back to the original position and tighten the lock screw
6. Replace the inner cartridge and tighten the lock screw
Note: Please check that all lock screws are firmly tightened, as they may come loose if vibration occurs during drilling




Brazed Drilling Heads

ISCAR DEEP-DRILL DSD/DDD...E0/E1/E2/E3, DDD... E3

ISCAR DEEP DRILL

DSD-E0

Deep Single Tube Drills with External Single Thread Connection and a Brazed Single Tip (8-14.8 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	OAL	DCONMS	PL	Ts ⁽³⁾
DSD-E0 8.00-8.99 NOM 0	8.00	8.99	35.00	6.00	2.00	TS001
DSD-E0 8.00-8.99 NOM 2	8.00	8.99	35.00	6.00	2.00	TS001
DSD-E0 9.00-9.99 NOM 0	9.00	9.99	35.00	7.20	2.00	TS002
DSD-E0 9.00-9.99 NOM 2	9.00	9.99	35.00	7.20	2.00	TS002
DSD-E0 10.00-10.99 NOM 0	10.00	10.99	35.20	7.60	2.20	TS003
DSD-E0 10.00-10.99 NOM 2	10.00	10.99	35.20	7.60	2.20	TS003
DSD-E0 11.00-11.99 NOM 0	11.00	11.99	35.20	8.60	2.20	TS004
DSD-E0 11.00-11.99 NOM 2	11.00	11.99	35.20	8.60	2.20	TS004
DSD-E0 12.00-13.49 NOM 0	12.00	13.49	35.30	9.10	2.30	TS005
DSD-E0 12.00-13.49 NOM 2	12.00	13.49	35.30	9.10	2.30	TS005
DSD-E0 13.50-14.79 NOM 0	13.50	14.79	35.40	10.80	2.40	TS006
DSD-E0 13.50-14.79 NOM 2	13.50	14.79	35.40	10.80	2.40	TS006

- The drill tip is supplied in a grade that is suitable to machine the material group indicated in the drill head designation: P-Steel, M-Stainless Steel, K-Cast Iron.
- For user guide and quotation form, see pages 90-91, 96-102 • Ordering example: DSD-E0 11.30 DT-PO

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum


⁽³⁾ Tube designation

For holders, see pages: TS*** (85)

ISCAR DEEP DRILL

DSD-E1

Deep Single Tube Drills with External 2 and 4 Start Thread Connections and a Single Brazed Tip (12.6-20 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	OAL	DCONMS	PL	Threads ⁽³⁾	Ts ⁽⁴⁾
DSD-E1 12.60-13.60 NOM 0	12.60	13.60	42.50	9.60	2.30	2	TS-I01
DSD-E1 12.60-13.60 NOM 2	12.60	13.60	42.50	9.60	2.30	2	TS-I01
DSD-E1 13.61-14.60 NOM 0	13.61	14.60	42.70	10.60	2.40	2	TS-I02
DSD-E1 13.61-14.60 NOM 2	13.61	14.60	42.70	10.60	2.40	2	TS-I02
DSD-E1 14.61-15.59 NOM 0	14.61	15.59	42.70	11.60	3.00	2	TS-I03
DSD-E1 14.61-15.59 NOM 2	14.61	15.59	42.70	11.60	3.00	2	TS-I03
DSD-E1 15.60-16.70 NOM 0	15.60	16.70	42.70	11.60	2.40	4	TS-I0
DSD-E1 15.60-16.70 NOM 2	15.60	16.70	42.70	11.60	2.40	4	TS-I0
DSD-E1 16.71-17.70 NOM 0	16.71	17.70	43.20	13.60	3.00	4	TS-I1
DSD-E1 16.71-17.70 NOM 2	16.71	17.70	43.20	13.60	3.00	4	TS-I1
DSD-E1 17.71-18.90 NOM 0	17.71	18.90	43.60	14.50	3.30	4	TS-I2
DSD-E1 17.71-18.90 NOM 2	17.71	18.90	43.60	14.50	3.30	4	TS-I2
DSD-E1 18.91-20.00 NOM 0	18.91	20.00	43.60	15.50	3.30	4	TS-I3
DSD-E1 18.91-20.00 NOM 2	18.91	20.00	43.60	15.50	3.30	4	TS-I3

- The drill tip is supplied in a grade that is suitable to machine the material group indicated in the drill head designation: P-Steel, M-Stainless Steel, K-Cast Iron.

- For user guide and quotation form, see pages 90-91, 96-102 • Ordering example: DSD-E1 14.50 DT-PO

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ No. of thread starts

⁽⁴⁾ Tube designation

For holders, see pages: TS-I** (86)

D- Tool diameter

Metric- D8.00

Inch- D.315

d- Pilot diameter

Metric- d6

Inch- d.236

Tool style

A- Single cutting edge

B- Multiple cutting edges

Thread type

1ST- Single start thread single tube


2ST- Two start thread single tube

4ST- Four start thread single tube

4DT- Four start thread double tube

7.1- Tube diameter

Universal Marking for Deep Drilling Tools




D8.00d6
D.315d6.236
A1ST7.1
[Lot No.]



ISCARDEEPPDRILL**DSD-E2/E3**

Deep Single Tube Drills with
External 2 and 4 Start Thread
Connections and 2 or 3
Brazed Tips (12.6-65 dia.)



NOM 0 refers to non-coated drill head, NOM 2 refers to coated drill head.

Designation	DCN ⁽¹⁾	DCX ⁽²⁾	OAL	DCONMS	PL	Threads ⁽³⁾	Ts ⁽⁴⁾
DSD-E2 12.60-13.60 NOM 0	12.60	13.60	43.00	9.60	1.10	2	TS-I01
DSD-E2 12.60-13.60 NOM 2	12.60	13.60	43.00	9.60	1.10	2	TS-I01
DSD-E2 13.61-14.60 NOM 0	13.61	14.60	43.00	10.60	1.20	2	TS-I02
DSD-E2 13.61-14.60 NOM 2	13.61	14.60	43.00	10.60	1.20	2	TS-I02
DSD-E2 14.61-15.59 NOM 0	14.61	15.59	43.00	11.60	1.30	2	TS-I03
DSD-E2 14.61-15.59 NOM 2	14.61	15.59	43.00	11.60	1.30	2	TS-I03
DSD-E3 15.60-16.70 NOM 0	15.60	16.70	43.00	12.60	2.70	4	TS-I0
DSD-E3 15.60-16.70 NOM 2	15.60	16.70	43.00	12.60	2.70	4	TS-I0
DSD-E3 16.71-17.70 NOM 0	16.71	17.70	43.00	13.60	2.70	4	TS-I1
DSD-E3 16.71-17.70 NOM 2	16.71	17.70	43.00	13.60	2.70	4	TS-I1
DSD-E3 17.71-18.90 NOM 0	17.71	18.90	47.00	14.50	2.80	4	TS-I2
DSD-E3 17.71-18.90 NOM 2	17.71	18.90	47.00	14.50	2.80	4	TS-I2
DSD-E3 18.91-20.00 NOM 0	18.91	20.00	47.00	15.50	2.90	4	TS-I3
DSD-E3 18.91-20.00 NOM 2	18.91	20.00	47.00	15.50	2.90	4	TS-I3
DSD-E3 20.01-21.80 NOM 0	20.01	21.80	52.50	16.00	3.20	4	TS-I4
DSD-E3 20.01-21.80 NOM 2	20.01	21.80	52.50	16.00	3.20	4	TS-I4
DSD-E3 21.81-24.10 NOM 0	21.81	24.10	56.00	18.00	3.20	4	TS-I5
DSD-E3 21.81-24.10 NOM 2	21.81	24.10	56.00	18.00	3.20	4	TS-I5
DSD-E3 24.11-26.40 NOM 0	24.11	26.40	57.50	19.50	3.50	4	TS-I6
DSD-E3 24.11-26.40 NOM 2	24.11	26.40	57.50	19.50	3.50	4	TS-I6
DSD-E3 26.41-28.70 NOM 0	26.41	28.70	57.50	21.00	3.70	4	TS-I7
DSD-E3 26.41-28.70 NOM 2	26.41	28.70	57.50	21.00	3.70	4	TS-I7
DSD-E3 28.71-31.00 NOM 0	28.71	31.00	63.50	23.50	4.00	4	TS-I8
DSD-E3 28.71-31.00 NOM 2	28.71	31.00	63.50	23.50	4.00	4	TS-I8
DSD-E3 31.01-33.30 NOM 0	31.01	33.30	63.50	25.50	4.30	4	TS-I9
DSD-E3 31.01-33.30 NOM 2	31.01	33.30	63.50	25.50	4.30	4	TS-I9
DSD-E3 33.31-36.20 NOM 0	33.31	36.20	63.50	28.00	4.50	4	TS-I10
DSD-E3 33.31-36.20 NOM 2	33.31	36.20	63.50	28.00	4.50	4	TS-I10
DSD-E3 36.21-39.60 NOM 0	36.21	39.60	73.50	30.00	4.80	4	TS-I11
DSD-E3 36.21-39.60 NOM 2	36.21	39.60	73.50	30.00	4.80	4	TS-I11
DSD-E3 39.61-43.00 NOM 0	39.61	43.00	73.50	33.00	5.60	4	TS-I12
DSD-E3 39.61-43.00 NOM 2	39.61	43.00	73.50	33.00	5.60	4	TS-I12
DSD-E3 43.01-47.00 NOM 0	43.01	47.00	75.00	36.00	5.40	4	TS-I13
DSD-E3 43.01-47.00 NOM 2	43.01	47.00	75.00	36.00	5.40	4	TS-I13
DSD-E3 47.01-51.70 NOM 0	47.01	51.70	75.00	39.00	6.10	4	TS-I14
DSD-E3 47.01-51.70 NOM 2	47.01	51.70	75.00	39.00	6.10	4	TS-I14
DSD-E3 51.71-56.20 NOM 0	51.71	56.20	82.00	43.00	6.50	4	TS-I15
DSD-E3 51.71-56.20 NOM 2	51.71	56.20	82.00	43.00	6.50	4	TS-I15
DSD-E3 56.21-60.60 NOM 0	56.21	60.60	84.00	47.00	6.60	4	TS-I16
DSD-E3 56.21-60.60 NOM 2	56.21	60.60	84.00	47.00	6.60	4	TS-I16
DSD-E3 60.61-65.00 NOM 0	60.61	65.00	84.00	47.00	7.00	4	TS-I17
DSD-E3 60.61-65.00 NOM 2	60.61	65.00	84.00	47.00	7.00	4	TS-I17

- The drill tip is supplied in a grade that is suitable to machine the material group indicated in the drill head designation: ISO P, K, M, N materials
- For user guide and quotation form, see pages 90-91, 96-102 • Ordering example: DSD-E3 43.30 DT-PO

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Number of thread starts

⁽⁴⁾ Tube designation


For holders, see pages: TS-I** (86)



ISCARDEEPPDRILL

DDD-E3

Deep Double Tube Drills
with External 4 Start Thread
Connection and Brazed
Tips (18.4-65 dia.)



NOM 0 refers to non-coated drill head, NOM 2 refers to coated drill head.

Designation	DCN ⁽¹⁾	DCX ⁽²⁾	OAL	DCONMS	PL	Ts ⁽³⁾	Ts ⁽⁴⁾
DDD-E3 18.41-20.00 NOM 0	18.41	20.00	50.00	16.00	2.90	TDO-I0	TDI-N0
DDD-E3 18.41-20.00 NOM 2	18.41	20.00	50.00	16.00	2.90	TDO-I0	TDI-N0
DDD-E3 20.01-21.80 NOM 0	20.01	21.80	56.00	18.00	3.20	TDO-I1	TDI-N1
DDD-E3 20.01-21.80 NOM 2	20.01	21.80	56.00	18.00	3.20	TDO-I1	TDI-N1
DDD-E3 21.81-24.10 NOM 0	21.81	24.10	56.00	19.50	3.20	TDO-I2	TDI-N2
DDD-E3 21.81-24.10 NOM 2	21.81	24.10	56.00	19.50	3.20	TDO-I2	TDI-N2
DDD-E3 24.11-26.40 NOM 0	24.11	26.40	57.50	21.00	3.50	TDO-I3	TDI-N3
DDD-E3 24.11-26.40 NOM 2	24.11	26.40	57.50	21.00	3.50	TDO-I3	TDI-N3
DDD-E3 26.41-28.70 NOM 0	26.41	28.70	60.50	23.50	3.70	TDO-I4	TDI-N4
DDD-E3 26.41-28.70 NOM 2	26.41	28.70	60.50	23.50	3.70	TDO-I4	TDI-N4
DDD-E3 28.71-31.00 NOM 0	28.71	31.00	63.50	25.50	4.00	TDO-I5	TDI-N5
DDD-E3 28.71-31.00 NOM 2	28.71	31.00	63.50	25.50	4.00	TDO-I5	TDI-N5
DDD-E3 31.01-33.30 NOM 0	31.01	33.30	63.50	28.00	4.10	TDO-I6	TDI-N6
DDD-E3 31.01-33.30 NOM 2	31.01	33.30	63.50	28.00	4.10	TDO-I6	TDI-N6
DDD-E3 33.31-36.20 NOM 0	33.31	36.20	70.50	30.00	4.50	TDO-I7	TDI-N7
DDD-E3 33.31-36.20 NOM 2	33.31	36.20	70.50	30.00	4.50	TDO-I7	TDI-N7
DDD-E3 36.21-39.60 NOM 0	36.21	39.60	73.50	33.00	4.80	TDO-I8	TDI-N8
DDD-E3 36.21-39.60 NOM 2	36.21	39.60	73.50	33.00	4.80	TDO-I8	TDI-N8
DDD-E3 39.61-43.00 NOM 0	39.61	43.00	73.50	36.00	5.30	TDO-I9	TDI-N9
DDD-E3 39.61-43.00 NOM 2	39.61	43.00	73.50	36.00	5.30	TDO-I9	TDI-N9
DDD-E3 43.01-47.00 NOM 0	43.01	47.00	75.00	39.00	5.50	TDO-I10	TDI-N10
DDD-E3 43.01-47.00 NOM 2	43.01	47.00	75.00	39.00	5.50	TDO-I10	TDI-N10
DDD-E3 47.01-51.70 NOM 0	47.01	51.70	79.00	43.00	6.10	TDO-I11	TDI-N11
DDD-E3 47.01-51.70 NOM 2	47.01	51.70	79.00	43.00	6.10	TDO-I11	TDI-N11
DDD-E3 51.71-56.20 NOM 0	51.71	56.20	82.00	47.00	6.50	TDO-I12	TDI-N12
DDD-E3 51.71-56.20 NOM 2	51.71	56.20	82.00	47.00	6.50	TDO-I12	TDI-N12
DDD-E3 56.21-65.00 NOM 0	56.21	65.00	84.00	51.00	6.60	TDO-I13	TDI-N13
DDD-E3 56.21-65.00 NOM 2	56.21	65.00	84.00	51.00	6.60	TDO-I13	TDI-N13

- The drill tip is supplied in a grade that is suitable to machine the material group indicated in the drill head designation: ISO P, K, M, N materials
- NOM 0 refers to non-coated drill head, NOM 2 refers to coated drill head. • Ordering example: DDD-E3 47.10 OT-P0
- For quotation form and user guide, see pages 90-91, 96-102

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Outer tube designation

⁽⁴⁾ Inner tube designation

For holders, see pages: TDO-I (D18.41-65.00) (88)

D- Tool diameter

Metric- D18.40

Inch- D.724

d- Pilot diameter

Metric- d23.5

Inch- d.630

Tool style

A- Single cutting edge

B- Multiple cutting edges

B	multiple cutting edges
BGDD	peripheral tip, inner tip with shorter CB
BDDD	ALL TIPS with shorter CB
BBL	T-land
BBLGDD	T-land & peripheral tip, inner tip with shorter CB
BBLDDD	T-land & ALL TIPS with shorter CB

Thread type

1ST- Single start thread single tube


2ST- Two start thread single tube

4ST- Four start thread single tube

4DT- Four start thread double tube

18- Tube diameter

Universal Marking for Deep Drilling Tools



D18.4d23.5
D.724d.630
BBLGDD4DT18
[Lot No.]

Brazed Drilling Heads



Single Tube System – External Thread

DSD-E0 - Deep single tube drills with external single thread connection and a brazed single tip (8-14.8 dia.)


DSD-E1 - Deep single tube drills with external 2 and 4 start thread connections and a single brazed tip (12.6-20 dia.)

DSD-E2/E3 - Deep single tube drills with external 2 and 4 start thread connections and 2 or 3 brazed tips (12.6-65 dia.)

Double Tube System:

DDD-E3 - Deep double tube drills with external 4 start thread connection and brazed tips (18.4-65 dia.)

Grade of Brazed Heads





Grade of Brazed Heads

DSD-E0

DSD-E0 (MBU style) STS



Ø8 -14.79 mm (Ø.315- .582")




DSD-E2

DSD-E2 (BTU 2tip style) STS



Ø12.60 ~ 20.00 mm (Ø.496" ~ .787")




DSD-E1

DSD-E1 (UTE style) STS



Ø12.60 ~ 20.00 mm (Ø.496" ~ .787")



DSD-E3

DSD-E3 (BTU style) STS




Ø15.60 ~ 65.00mm
(Ø.615" ~ 2.559")

DDD-E3 (ETU style) STS












Ø18.40 ~ 65.00mm
(Ø.725" ~ 2.559")



* indicates the first recommendation

Tool Grades

Application	Grade	Coating		Features	Brazed Drill Heads			
		Main composition	Thickness / mm		DSD-E0	DSD-E1	DSD-E2/E3	DDD-E3
								
PZ/PZT		TiAlCr	2.5	• high wear resistance • suitable for steel, cast iron, and difficult-to-cut material * PZ is for DSD-E0, DSD-E1 * PZT is for DSD-E2/E3, DDD-E3				
P	P10 - P30							
K	K15 - K25							
N	N15 - N25							
S	S15 - S25							
H	H15 - H25							
PZX2T		TiAlCr	2.5	• good balance between wear and chipping resistance • suitable for steel and stainless steel under general cutting conditions				
P	P20 - P30							
M	M25 - M35							
PZN		TiAlCr	2.5	• high fracture resistance • suitable for stainless steel				
M	M30 - M40							
KZ		TiAlCr	2.5	• good balance between wear and fracture resistance				
M	M15 - M25							
K	K10 - K20							
N	N15 - N25							
S	S15 - S25							
H	H15 - H25							
KZK		TiAlCr	2.5	• first choice for heat-resistant alloy under general cutting conditions				
K	K15 - K25							
N	N10 - N20							
S	S15 - S25							
H	H15 - H25							

Note: Being brazed tools, the grade codes represent the grade combination of the brazed carbide tip and guide pad grades
They do not represent the individual grade of carbide tips or guide pads



Counterboring Heads


INDEXABLE COUNTERBORING

DSC-EA/EC/IA/IC, DDC-EA/EC

ISCARDEEPDRILL

DSC-EA

Deep Single Tube Counterbore with Through Hole, External 4 Start Thread and Adjustable Diameter (25-40 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	CHW	LF	DCONMS	TS ⁽³⁾
DSC-EA 25.00-26.40	25.00	26.40	3.5	70.00	19.50	TS-I6
DSC-EA 26.41-28.70	26.41	28.70	3.5	70.00	21.00	TS-I7
DSC-EA 28.71-31.00	28.71	31.00	3.5	75.00	23.50	TS-I8
DSC-EA 31.01-33.30	31.01	33.30	3.5	75.00	25.50	TS-I9
DSC-EA 33.31-36.20	33.31	36.20	3.5	75.00	28.00	TS-I10
DSC-EA 36.21-39.60	36.21	39.60	3.5	90.00	30.00	TS-I11
DSC-EA 39.61-39.99	39.61	39.99	3.5	90.00	33.00	TS-I12

• For user guide and quotation form, see pages 94-102 • Ordering example: DSC-EA 33.20



⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Tube designation

For inserts, see pages: XPMT-45 (53)

For holders, see pages: TS-I** (86)



Spare Parts

DSC-EA

Diameter range						
	Adjustment ball	Adjustment screw	Wrench	Insert	Insert screw	Wrench
25.00-39.99	ADJUST BALL	SR11201755-7	HW 2.5	XPMT 16002-45	SR 11201754-4-4.5	T-9/51

Spare Parts (continued)


DSC-EA

Diameter range															
	Guide Pads	Qty	Lock screw	Qty	Wrench	Sub Guide Pads	Qty	Lock screw	Qty	Wrench	Protectors	Qty	Lock screw	Qty	Wrench
25.00-29.99	GPS-06-20-120-DC	2	SR 34-508	2	T-7/51	SGP-01	1	SR11201753-1	1	T-7/51	-	-	-	-	-
30.00-37.99	GPS-07-20-120-DC	3	CSTB-3L065	3	T-9/51	SGP-01	1	SR11201753-1	1	T-7/51	-	-	-	-	-
38.00-39.99	GPS-08-25-155-DC	3	CSTB-3L065	3	T-9/51	SGP-02	1	SR11201753-4	1	T-9/51	GPP-06	3	SR11201753-4	3	T-9/51

ISCARDEEPDRILL

XPMT-45

Inserts for DSC Boring Heads




Designation	Dimensions		Tough ↔ Hard	
	W1	S	IB55	IC950
XPMT 16002-45	9.50	2.80	•	•

For tools, see pages: DDC-EA (66) • DSC-EA (52) • DSC-IA (60)

ISCARDEEPDRILL

SGP

Drilling Head Sub-Guide Pads




Designation	OAL	OAW	OAH
SGP-01	10.00	6.00	3.00
SGP-02	10.00	8.00	4.50
SGP-03	10.00	10.00	5.00
SGP-04	20.00	14.00	7.00

• Select an outer cartridge and pad for the required enlarged diameter.

ISCARDEEPDRILL

GPP

Drilling Head Guide Pad Protectors



Designation	OAL	OAW	OAH
GPP-06	8.00	8.00	4.50
GPP-07	10.00	10.00	6.00
GPP-08	14.00	14.00	7.50
GPP-09	18.00	18.00	9.00

• Select an outer cartridge and pad for the required enlarged diameter.

Recommended clamping torque

Insert Screw	
	(N·m)
SR 11201753-2	1
SR 11201753-3	1.3
SR 11201753-7	2.3
SR 11201753-9	3.5
SR 11201753-7	5

Cartridge Screw	
	(N·m)
SR 11201752-1	3.5
SR 11201753-5	2.3
SR 11201753-5	3.5
SR 11201756-7	3
SR 11201756-10	2.2
SR 11201756-11	2.2
SR 11201756-12	3
SR 11201756-15	5


Guide Pad Screw	
	(N·m)
SR 14-571/5	3.5
SR 34-506-C	2.3
LS1206SSS	3



ISCAR^{DEEP}DRILL

GPS


Deep Drilling Solid
Carbide Guide Pads



Designation	Dimensions				Tough ↔ Hard		
	OAW	OAL	OAH	RE	IC928	IC950	IC908
GPS-04-16-045-DC ⁽¹⁾	4.00	16.00	1.80	4.50			•
GPS-04-16-050-DC ⁽¹⁾	4.00	16.00	1.80	5.00			•
GPS-04-16-055-DC ⁽¹⁾	4.00	16.00	2.00	5.50	•		•
GPS-05-18-060-DC ⁽¹⁾	5.00	18.00	2.50	6.00	•		•
GPS-05-18-075-DC ⁽¹⁾	5.00	18.00	2.50	7.50	•		•
GPS-06-20-075-DC ⁽¹⁾	6.00	20.00	3.00	7.50			•
GPS-06-20-075	6.00	20.00	3.00	7.50		•	
GPS-06-20-085-DC ⁽¹⁾	6.00	20.00	3.00	8.50	•		•
GPS-06-20-085	6.00	20.00	3.00	8.50		•	
GPS-06-20-100-DC ⁽¹⁾	6.00	20.00	3.00	10.00	•		•
GPS-06-20-100	6.00	20.00	3.00	10.00		•	
GPS-06-20-120-DC ⁽¹⁾	6.00	20.00	3.00	12.00	•		•
GPS-06-20-120	6.00	20.00	3.00	12.00		•	
GPS-07-20-120-DC ⁽¹⁾	7.00	20.00	3.50	12.00	•		•
GPS-07-20-120	7.00	20.00	3.50	12.00		•	
GPS-08-25-155-DC ⁽¹⁾	8.00	25.00	4.50	15.50	•		•
GPS-08-25-155	8.00	25.00	4.50	15.50		•	
GPS-10-30-200-DC ⁽¹⁾	10.00	30.00	4.50	20.00	•		•
GPS-10-30-200	10.00	30.00	4.50	20.00		•	
GPS-10-35-200-DC ⁽¹⁾	10.00	35.00	6.00	20.00	•		•
GPS-10-35-200	10.00	35.00	6.00	20.00		•	
GPS-12-35-250-DC ⁽¹⁾	12.00	35.00	5.50	25.00	•		•
GPS-12-35-250	12.00	35.00	5.50	25.00		•	
GPS-14-40-250-DC ⁽¹⁾	14.00	40.00	7.50	25.00	•		•
GPS-14-40-250	14.00	40.00	7.50	25.00		•	
GPS-18-40-300-DC ⁽¹⁾	18.00	40.00	9.00	30.00	•		•

⁽¹⁾ DC- Double Chamfer

Universal Marking for Deep Drilling Tools




Guide Pad Grade Recommendation

Priority	Oil Coolant			Water Based Coolant		
	1	2	3	1	2	3
ISO-P	IC950	IC908	IC928	IC928	IC908	-
ISO-K	IC950	IC908	IC928	IC928	IC908	-
ISO-M	IC928	IC908	IC950	IC928	IC908	-
ISO-S	IC928	IC908	IC950	IC928	IC908	-

ISCARDEEPCDRILL

DSC-EC

Deep Single Tube Counterbore with Through Hole, External 4 Start Thread Connection and a Cartridge (40-292 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	CHW	CHW_2	LF	DCONMS	Ts ⁽³⁾
DSC-EC 40.00-43.00	40.00	43.00	6.4	4.0	90.00	33.00	TS-I12
DSC-EC 43.01-47.00	43.01	47.00	6.4	4.0	95.00	36.00	TS-I13
DSC-EC 47.01-51.70	47.01	51.70	6.4	4.0	100.00	39.00	TS-I14
DSC-EC 51.71-56.20	51.71	56.20	6.4	4.0	100.00	43.00	TS-I15
DSC-EC 56.21-60.60	56.21	60.60	7.2	4.8	105.00	47.00	TS-I16
DSC-EC 60.61-64.99	60.61	65.00	7.2	4.8	110.00	51.00	TS-I17
DSC-EC 65.00-66.99	65.00	66.99	7.2	4.8	150.00	52.00	TS-I18
DSC-EC 67.00-72.99	67.00	72.99	10.4	6.4	150.00	58.00	TS-I19
DSC-EC 73.00-79.99	73.00	79.99	10.4	6.4	150.00	63.00	TS-I20
DSC-EC 80.00-86.99	80.00	86.99	10.4	6.4	180.00	70.00	TS-I21
DSC-EC 87.00-99.99	87.00	99.99	10.4	6.4	180.00	77.00	TS-I22
DSC-EC 100.00-111.99	100.00	111.99	10.4	6.4	180.00	89.00	TS-I23
DSC-EC 112.00-123.99	112.00	123.99	10.4	6.4	205.00	101.00	TS-I24
DSC-EC 124.00-135.99	124.00	135.99	10.4	6.4	205.00	113.00	TS-I25
DSC-EC 136.00-147.99	136.00	147.99	10.4	6.4	205.00	125.00	TS-I26
DSC-EC 148.00-159.99	148.00	159.99	10.4	6.4	225.00	137.00	TS-I27
DSC-EC 160.00-171.99	160.00	171.99	10.4	6.4	225.00	149.00	TS-I28
DSC-EC 172.00-183.99	172.00	183.99	10.4	6.4	225.00	161.00	TS-I29
DSC-EC 184.00-195.99	184.00	195.99	10.4	6.4	245.00	173.00	TS-I30
DSC-EC 196.00-207.99	196.00	207.99	10.4	6.4	245.00	185.00	TS-I31
DSC-EC 208.00-219.99	208.00	219.99	10.4	6.4	245.00	197.00	TS-I32
DSC-EC 220.00-231.99	220.00	231.99	10.4	6.4	265.00	208.00	TS-I33
DSC-EC 232.00-243.99	232.00	243.99	10.4	6.4	265.00	220.00	TS-I34
DSC-EC 244.00-255.99	244.00	255.99	10.4	6.4	265.00	232.00	TS-I35
DSC-EC 256.00-267.99	256.00	267.99	10.4	6.4	290.00	244.00	TS-I36
DSC-EC 268.00-279.99	268.00	279.99	10.4	6.4	290.00	256.00	TS-I37
DSC-EC 280.00-291.99	280.00	291.99	10.4	6.4	290.00	268.00	TS-I38

- CAOD - Rough boring cartridge (for large D.O.C.), supplied with the cartridge, unless ordered differently
- CAORC - Precision boring cartridge
- For quotation form and user guide, see pages 94-102
- Ordering example: DSC-EC 87.30



⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Tube designation

For inserts, see pages: TPMX (30)


For holders, see pages: TS-I** (86)



ISCARDEEPDRILL

CAORC

Boring Head Peripheral Cartridge




Adjustment Cartridge for Shallow Depth of Cut

Diameter range	Adjustment Cartridge	Adjustment screw (2 pcs)	Wrench	Lock screw	Wrench	Insert	Insert screw	Wrench
40.00-51.99	CAORC-0845	SR11201755-6	HW 2.0	SR11201756-10	HW 2.5	TPMX 1403..L..	SR11201753-3	T-8/53
52.00-66.99	CAORC-103	SR11201755-8	HW 2.5	SR11201756-12	HW 3.0	TPMX 1704..L..	SR11201753-7	T-9/51
67.00-291.99	CAORC-142	SR11201755-9	HW 2.5	SR11201756-15	HW 4.0	TPMX 2405..L..	SR11201753-9	T-15/51

ISCARDEEPDRILL

CAOD

Drilling / Boring Head Peripheral Cartridge



Adjustment Cartridge for Large Depth of Cut

Diameter range	Adjustment Cartridge	Adjustment screw (2 pcs)	Wrench	Lock screw	Wrench	Insert	Insert screw	Wrench
40.00-51.99	CAOD-0845	SR11201755-6	HW 2.0	SR11201756-10	HW 2.5	TPMX 1403..R..	SR11201753-3	T-8/53
52.00-66.99	CAOD-103	SR11201755-8	HW 2.5	SR11201756-12	HW 3.0	TPMX 1704..R..	SR11201753-7	T-9/51
67.00-291.99	CAOD-142	SR11201755-9	HW 2.5	SR11201756-15	HW 4.0	TPMX 2405..R..	SR11201753-9	T-15/51

Guide Pads and Other Spare Parts


DSC-EC

Diameter range	Guide Pads	Qty	Lock screw	Qty	Wrench	Sub Guide Pads	Qty	Lock screw	Qty	Wrench	Protectors	Qty	Lock screw	Qty	Wrench
40.00-45.99	GPS-08-25-155-DC	3	CSTB-3L065	3	T-9/51	SGP-02	1	SR11201753-4	1	T-9/51	GPP-06	3	SR11201753-4	3	T-9/51
46.00-59.99	GPS-10-35-200-DC	3	SR11201753-8	3	T-15/51	SGP-02	1	SR11201753-4	1	T-9/51	GPP-07	3	SR11201753-8	3	T-15/51
60.00-99.99	GPS-14-40-260-DC	3	SR11201752-2	3	T-15/51	SGP-03	1	SR11201753-4	1	T-9/51	GPP-08	3	SR11201752-2	3	T-15/51
100.00-135.99	GPS-18-40-300-DC	3	SR11201756-7S	3	HW 3.0	SGP-04	1	SR11201752-2	1	T-15/51	GPP-09	3	SR11201756-7S	3	HW 3.0
136.00-291.99	GPS-18-40-300-DC	5	SR11201756-7S	5	HW 3.0	SGP-04	1	SR11201752-2	1	T-15/51	GPP-09	5	SR11201756-7S	5	HW 3.0

ISCARDEEPDRILL

TPMX





Inserts for Drilling / Counterboring
/ Trepanning Tools



Designation	Dimensions			Tough ↔ Hard			
	IC	S	RE	IC8355	IC908	IC948	IC806
TPMX 140304R-B	8.45	3.50	0.40		•		•
TPMX 140308L-G	8.45	3.50	0.80		•		
TPMX 140308R-B	8.45	3.50	0.80			•	•
TPMX 140308R-DT	8.45	3.50	0.80		•	•	
TPMX 140308R-G	8.45	3.50	0.80	•	•	•	•
TPMX 170404L-BG	10.30	4.00	0.40		•		
TPMX 170404R-B	10.30	4.00	0.40		•		•
TPMX 170408L-DT	10.30	4.00	0.80		•		
TPMX 170408L-G	10.30	4.00	0.80		•	•	
TPMX 170408R-B	10.30	4.00	0.80			•	•
TPMX 170408R-BG	10.30	4.00	0.80		•	•	•
TPMX 170408R-DT	10.30	4.00	0.80		•	•	
TPMX 170408R-G	10.30	4.00	0.80	•	•	•	•
TPMX 240504L-BG	14.20	5.50	0.40		•		
TPMX 240504R-B	14.20	5.50	0.40		•		•
TPMX 240512L-DT	14.20	5.50	1.20		•		
TPMX 240512L-G	14.20	5.50	1.20		•	•	
TPMX 240512R-B	14.20	5.50	1.20			•	•
TPMX 240512R-BG	14.20	5.50	1.20		•	•	•
TPMX 240512R-DT	14.20	5.50	1.20		•	•	
TPMX 240512R-G	14.20	5.50	1.20	•	•	•	•
TPMX 280708L-BG	17.00	7.50	0.80		•		
TPMX 280708R-B	17.00	7.50	0.80		•		•
TPMX 280716L-G	17.00	7.50	1.60		•	•	
TPMX 280716R-B	17.00	7.50	1.60			•	•
TPMX 280716R-BG	17.00	7.50	1.60		•	•	•
TPMX 280716R-DT	17.00	7.50	1.60		•	•	
TPMX 280716R-G	17.00	7.50	1.60	•	•	•	•

For tools, see pages: DDC-EC (69) • DDD-EC (29) • DSC-EC (55) • DSC-IC (62) • DSD-EC (27) • DSD-IC (28) • DSTR-EC (76) • DSTR-IC (78)


Chipbreaker Selection

Chipbreaker Selection					
G			B		
	versatile			good chip control for heat-resistant alloy	
BG			DT		
	chip control for difficult-to-cut steel			to reduce machine load	



ISCARDEEPPDRILL

SGP
Drilling Head Sub-Guide Pads




Designation	OAL	OAW	OAH
SGP-01	10.00	6.00	3.00
SGP-02	10.00	8.00	4.50
SGP-03	10.00	10.00	5.00
SGP-04	20.00	14.00	7.00

- Select an outer cartridge and pad for the required enlarged diameter.

ISCARDEEPPDRILL

GPP
Drilling Head Guide
Pad Protectors



Designation	OAL	OAW	OAH
GPP-06	8.00	8.00	4.50
GPP-07	10.00	10.00	6.00
GPP-08	14.00	14.00	7.50
GPP-09	18.00	18.00	9.00

- Select an outer cartridge and pad for the required enlarged diameter.

Recommended claming torque

Insert Screw	
	(N·m)
SR 11201753-2	1
SR 11201753-3	1.3
SR 11201753-7	2.3
SR 11201753-9	3.5
SR 11201753-7	5


Cartridge Screw	
	(N·m)
SR 11201752-1	3.5
SR 11201753-5	2.3
SR 11201753-5	3.5
SR 11201756-7	3
SR 11201756-10	2.2
SR 11201756-11	2.2
SR 11201756-12	3
SR 11201756-15	5

Guide Pad Screw	
	(N·m)
SR 14-571/5	3.5
SR 34-506-C	2.3
LS1206SSS	3

ISCARDEEPCDRILL

GPS


Deep Drilling Solid Carbide Guide Pads



Designation	Dimensions				Tough ↔ Hard		
	OAW	OAL	OAH	RE	IC928	IC950	IC908
GPS-04-16-045-DC ⁽¹⁾	4.00	16.00	1.80	4.50			•
GPS-04-16-050-DC ⁽¹⁾	4.00	16.00	1.80	5.00			•
GPS-04-16-055-DC ⁽¹⁾	4.00	16.00	2.00	5.50	•		•
GPS-05-18-060-DC ⁽¹⁾	5.00	18.00	2.50	6.00	•		•
GPS-05-18-075-DC ⁽¹⁾	5.00	18.00	2.50	7.50	•		•
GPS-06-20-075-DC ⁽¹⁾	6.00	20.00	3.00	7.50			•
GPS-06-20-075	6.00	20.00	3.00	7.50		•	
GPS-06-20-085-DC ⁽¹⁾	6.00	20.00	3.00	8.50	•		•
GPS-06-20-085	6.00	20.00	3.00	8.50		•	
GPS-06-20-100-DC ⁽¹⁾	6.00	20.00	3.00	10.00	•		•
GPS-06-20-100	6.00	20.00	3.00	10.00		•	
GPS-06-20-120-DC ⁽¹⁾	6.00	20.00	3.00	12.00	•		•
GPS-06-20-120	6.00	20.00	3.00	12.00		•	
GPS-07-20-120-DC ⁽¹⁾	7.00	20.00	3.50	12.00	•		•
GPS-07-20-120	7.00	20.00	3.50	12.00		•	
GPS-08-25-155-DC ⁽¹⁾	8.00	25.00	4.50	15.50	•		•
GPS-08-25-155	8.00	25.00	4.50	15.50		•	
GPS-10-30-200-DC ⁽¹⁾	10.00	30.00	4.50	20.00	•		•
GPS-10-30-200	10.00	30.00	4.50	20.00		•	
GPS-10-35-200-DC ⁽¹⁾	10.00	35.00	6.00	20.00	•		•
GPS-10-35-200	10.00	35.00	6.00	20.00		•	
GPS-12-35-250-DC ⁽¹⁾	12.00	35.00	5.50	25.00	•		•
GPS-12-35-250	12.00	35.00	5.50	25.00		•	
GPS-14-40-250-DC ⁽¹⁾	14.00	40.00	7.50	25.00	•		•
GPS-14-40-250	14.00	40.00	7.50	25.00		•	
GPS-18-40-300-DC ⁽¹⁾	18.00	40.00	9.00	30.00	•		•

⁽¹⁾ DC - Double Chamfer

Universal Marking for Deep Drilling Tools



Guide Pad Grade Recommendation


Priority	Oil Coolant			Water Based Coolant		
	1	2	3	1	2	3
ISO-P	IC950	IC908	IC928	IC928	IC908	-
ISO-K	IC950	IC908	IC928	IC928	IC908	-
ISO-M	IC928	IC908	IC950	IC928	IC908	-
ISO-S	IC928	IC908	IC950	IC928	IC908	-



ISCARDEEPPDRILL

DSC-IA

Deep Single Tube Counterbore with a Through Hole, Internal Single-Start Thread and Adjustable Diameter (25-40 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	CHW	LF	LSCMS	DCONMS	Ts ⁽³⁾
DSC-IA 25.00-26.99	25.00	26.99	2.8	110.00	25.00	20.00	TS-O10
DSC-IA 27.00-29.99	27.00	29.99	2.8	110.00	25.00	22.00	TS-O11
DSC-IA 30.00-31.99	30.00	31.99	2.8	110.00	25.00	24.00	TS-O12
DSC-IA 32.00-33.99	32.00	33.99	2.8	110.00	25.00	26.00	TS-O13
DSC-IA 34.00-36.99	34.00	36.99	2.8	135.00	40.00	27.00	TS-O14
DSC-IA 37.00-39.99	37.00	39.99	2.8	135.00	40.00	30.00	TS-O15

• For user guide and quotation form, see pages 94-102 • Ordering example: DSC-IA 30.35



(1) Cutting diameter minimum

(2) Cutting diameter maximum

(3) Tube designation

For inserts, see pages: XPMT-45 (53)

For holders, see pages: TS-O** (87)



Spare Parts

DSC-IA

Diameter range	Adjustment ball	Adjustment screw	Wrench	Insert	Insert screw	Wrench
25.00-39.99	ADJUST BALL	SR11201755-7	HW 2.5	XPMT 16002-45	SR 11201754-4-4.5	T-9/51

Spare Parts (continued)

DSC-IA

Diameter range	Guide Pads	Qty	Lock screw	Qty	Wrench	Resin guide pad	Qty	Lock screw	Qty	Wrench
25.00-29.99	GPS-06-20-120-DC	2	SR 34-508	2	T-7/51	RGP01	3	SR11201756-2	6	HW 2.0
30.00-36.99	GPS-07-20-120-DC	3	CSTB-3L065	3	T-9/51	RGP02	3	SR11201756-3	6	HW 2.0
37.00-39.99	GPS-08-25-155-DC	3	CSTB-3L065	3	T-9/51	RGP03	3	SR11201756-4	6	HW 2.5

Universal Marking for Deep Drilling Tools

D- Tool diameter

Metric- D100.00

Inch- D3.937

d- pilot diameter

Metric- d90

Inch- d3.543

Tool style

R- cartridge style counter boring


Thread type

4ST- four-start thread single tube

1ST- single-start thread single tube

4DT- four-start thread double tube


94- tube diameter



ISCARDEEPDRILL

XPMT-45

Inserts for DSC Boring Heads




Designation	Dimensions		Tough ↔ Hard	
	W1	S	IB55	IC950
XPMT 16002-45	9.50	2.80	•	•

For tools, see pages: DDC-EA (66) • DSC-EA (52) • DSC-IA (60)

ISCARDEEPDRILL

GPS


Deep Drilling Solid Carbide Guide Pads



Designation	Dimensions				Tough ↔ Hard		
	OAW	OAL	OAH	RE	IC928	IC950	IC908
GPS-04-16-045-DC ⁽¹⁾	4.00	16.00	1.80	4.50			•
GPS-04-16-050-DC ⁽¹⁾	4.00	16.00	1.80	5.00			•
GPS-04-16-055-DC ⁽¹⁾	4.00	16.00	2.00	5.50	•		•
GPS-05-18-060-DC ⁽¹⁾	5.00	18.00	2.50	6.00	•		•
GPS-05-18-075-DC ⁽¹⁾	5.00	18.00	2.50	7.50	•		•
GPS-06-20-075-DC ⁽¹⁾	6.00	20.00	3.00	7.50			•
GPS-06-20-075	6.00	20.00	3.00	7.50		•	
GPS-06-20-085-DC ⁽¹⁾	6.00	20.00	3.00	8.50	•		•
GPS-06-20-085	6.00	20.00	3.00	8.50		•	
GPS-06-20-100-DC ⁽¹⁾	6.00	20.00	3.00	10.00	•		•
GPS-06-20-100	6.00	20.00	3.00	10.00		•	
GPS-06-20-120-DC ⁽¹⁾	6.00	20.00	3.00	12.00	•		•
GPS-06-20-120	6.00	20.00	3.00	12.00		•	
GPS-07-20-120-DC ⁽¹⁾	7.00	20.00	3.50	12.00	•		•
GPS-07-20-120	7.00	20.00	3.50	12.00		•	
GPS-08-25-155-DC ⁽¹⁾	8.00	25.00	4.50	15.50	•		•
GPS-08-25-155	8.00	25.00	4.50	15.50		•	
GPS-10-30-200-DC ⁽¹⁾	10.00	30.00	4.50	20.00	•		•
GPS-10-30-200	10.00	30.00	4.50	20.00		•	
GPS-10-35-200-DC ⁽¹⁾	10.00	35.00	6.00	20.00	•		•
GPS-10-35-200	10.00	35.00	6.00	20.00		•	
GPS-12-35-250-DC ⁽¹⁾	12.00	35.00	5.50	25.00	•		•
GPS-12-35-250	12.00	35.00	5.50	25.00		•	
GPS-14-40-250-DC ⁽¹⁾	14.00	40.00	7.50	25.00	•		•
GPS-14-40-250	14.00	40.00	7.50	25.00		•	
GPS-18-40-300-DC ⁽¹⁾	18.00	40.00	9.00	30.00	•		•

⁽¹⁾ DC- Double Chamfer

Universal Marking for Deep Drilling Tools



Guide Pad Grade Recommendation


Priority	Oil Coolant			Water Based Coolant		
	1	2	3	1	2	3
ISO-P	IC950	IC908	IC928	IC928	IC908	-
ISO-K	IC950	IC908	IC928	IC928	IC908	-
ISO-M	IC928	IC908	IC950	IC928	IC908	-
ISO-S	IC928	IC908	IC950	IC928	IC908	-



ISCARDEEPPDRILL

DSC-IC

Deep Single Tube Counterbore with a Through Hole, Internal Single Start Thread and a Cartridge (40-294 dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	CHW	CHW_2	LF	DCONMS	Ts ⁽³⁾
DSC-IC 40.00-43.99	40.00	43.99	6.4	4.0	135.00	33.00	TS-O16
DSC-IC 44.00-46.99	44.00	46.99	6.4	4.0	135.00	37.00	TS-O17
DSC-IC 47.00-51.99	47.00	51.99	6.4	4.0	145.00	41.00	TS-O18
DSC-IC 52.00-56.99	52.00	56.99	7.2	4.8	145.00	44.00	TS-O19
DSC-IC 57.00-60.99	57.00	60.99	7.2	4.8	170.00	49.00	TS-O20
DSC-IC 61.00-67.99	61.00	67.99	7.2	4.8	170.00	53.00	TS-O21
DSC-IC 68.00-74.99	68.00	74.99	10.4	6.4	170.00	59.00	TS-O22
DSC-IC 75.00-80.99	75.00	80.99	10.4	6.4	205.00	65.00	TS-O23
DSC-IC 81.00-90.99	81.00	90.99	10.4	6.4	205.00	71.00	TS-O24
DSC-IC 91.00-98.99	91.00	98.99	10.4	6.4	215.00	79.00	TS-O25
DSC-IC 99.00-110.99	99.00	110.99	10.4	6.4	225.00	90.00	TS-O26
DSC-IC 111.00-122.99	111.00	122.99	10.4	6.4	235.00	102.00	TS-O27
DSC-IC 123.00-134.99	123.00	134.99	10.4	6.4	265.00	104.00	TS-O28
DSC-IC 135.00-148.99	135.00	148.99	10.4	6.4	265.00	126.00	TS-O29
DSC-IC 149.00-161.99	149.00	161.99	10.4	6.4	265.00	139.00	TS-O30
DSC-IC 162.00-173.99	162.00	173.99	10.4	6.4	285.00	151.00	TS-O31
DSC-IC 174.00-185.99	174.00	185.99	10.4	6.4	285.00	163.00	TS-O32
DSC-IC 186.00-197.99	186.00	197.99	10.4	6.4	310.00	175.00	TS-O33
DSC-IC 198.00-209.99	198.00	209.99	10.4	6.4	310.00	187.00	TS-O34
DSC-IC 210.00-221.99	210.00	221.99	10.4	6.4	320.00	199.00	TS-O35
DSC-IC 222.00-233.99	222.00	233.99	10.4	6.4	325.00	211.00	TS-O36
DSC-IC 234.00-245.99	234.00	245.99	10.4	6.4	325.00	223.00	TS-O37
DSC-IC 246.00-257.99	246.00	257.99	10.4	6.4	325.00	235.00	TS-O38
DSC-IC 258.00-269.99	258.00	269.99	10.4	6.4	360.00	245.00	TS-O39
DSC-IC 270.00-281.99	270.00	281.99	10.4	6.4	360.00	259.00	TS-O40
DSC-IC 282.00-293.99	282.00	293.99	10.4	6.4	360.00	271.00	TS-O41

- CAOD - Rough boring cartridge (for large D.O.C.) supplied with the cartridge, unless ordered differently
- CAORC - Precision boring cartridge
- For user guide and quotation form, see pages 94-102
- Ordering example: DSC-IC 91.10

⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Tube designation


For inserts, see pages: TPMX (30)

For holders, see pages: TS-O** (87)

ISCARDEEPPDRILL



RGP

Boring Head Resin Pads



Designation	OAL	OAW	OAH
RGP01	40.00	10.00	4.00
RGP02	45.00	12.00	5.00
RGP03	50.00	15.00	5.80
RGP04	70.00	20.00	7.50
RGP05	80.00	30.00	12.50
RGP06	100.00	35.00	15.50
RGP07	120.00	40.00	18.50
RGP08	140.00	50.00	22.50
RGP09	150.00	60.00	23.50
RGP10	150.00	70.00	26.50


- Select an outer cartridge and pad for the required enlarged diameter.



ISCARDEEPDRILL

CAORC

Boring Head Peripheral Cartridge




Adjustment cartridge for shallow depth of cut

Diameter range								
40.00-51.99	CAORC-0845	SR11201755-6	HW 2.0	SR11201756-10	HW 2.5	TPMX 140308L-G	SR11201753-3	T-8/53
52.00-66.99	CAORC-103	SR11201755-8	HW 2.5	SR11201756-12	HW 3.0	TPMX 170408L-G	SR11201753-7	T-9/51
67.00-293.99	CAORC-142	SR11201755-9	HW 2.5	SR11201756-15	HW 4.0	TPMX 240512L-G	SR11201753-9	T-15/51

ISCARDEEPDRILL

CAOD

Drilling / Boring Head
Peripheral Cartridge



Adjustment cartridge for large depth of cut

Diameter range								
40.00-51.99	CAOD-0845	SR11201755-6	HW 2.0	SR11201756-10	HW 2.5	TPMX 140308R-G	SR11201753-3	T-8/53
52.00-66.99	CAOD-103	SR11201755-8	HW 2.5	SR11201756-12	HW 3.0	TPMX 170408R-G	SR11201753-7	T-9/51
67.00-293.99	CAOD-142	SR11201755-9	HW 2.5	SR11201756-15	HW 4.0	TPMX 240512R-G	SR11201753-9	T-15/51

Guide pads

DSC-IC


Diameter range		Qty		Qty			Qty		Qty	
40.00-45.99	GPS-08-25-155-DC	3	CSTB-3L065	3	T-9/51	RGP03	3	SR11201756-4	6	HW 2.5
46.00-56.99	GPS-10-35-200-DC	3	SR11201753-8	3	T-15/51	RGP03	3	SR11201756-4	6	HW 2.5
57.00-59.99	GPS-10-35-200-DC	3	SR11201753-8	3	T-15/51	RGP04	3	SR11201756-5	6	HW 3.0
60.00-80.99	GPS-14-40-250-DC	3	SR11201752-2	3	T-15/51	RGP04	3	SR11201756-5	6	HW 3.0
81.00-90.99	GPS-14-40-250-DC	3	SR11201752-2	3	T-15/51	RGP05	3	SR11201756-6	6	HW 4.0
91.00-99.99	GPS-14-40-250-DC	3	SR11201752-2	3	T-15/51	RGP06	3	SR11201756-6	6	HW 4.0
100.00-122.99	GPS-18-40-300-DC	3	SR11201756-7S	3	HW 3.0	RGP06	3	SR11201756-6	6	HW 4.0
123.00-185.99	GPS-18-40-300-DC	3	SR11201756-7S	3	HW 3.0	RGP07	3	LS0906-20	6	HW 5.0
186.00-209.99	GPS-18-40-300-DC	5	SR11201756-7S	5	HW 3.0	RGP08	3	LS0906-25	6	HW 8.0
210.00-245.99	GPS-18-40-300-DC	5	SR11201756-7S	5	HW 3.0	RGP09	3	LS0906-25	6	HW 8.0
246.00-293.99	GPS-18-40-300-DC	5	SR11201756-7S	5	HW 3.0	RGP10	3	LS0906-25	6	HW 10.0



ISCARDEEPDRILL

TPMX





Inserts for Drilling / Counterboring
/ Trepanning Tools



Designation	Dimensions			Tough ↔ Hard			
	IC	S	RE	IC8355	IC908	IC948	IC806
TPMX 140304R-B	8.45	3.50	0.40		•		•
TPMX 140308L-G	8.45	3.50	0.80		•		
TPMX 140308R-B	8.45	3.50	0.80			•	•
TPMX 140308R-DT	8.45	3.50	0.80		•	•	
TPMX 140308R-G	8.45	3.50	0.80	•	•	•	•
TPMX 170404L-BG	10.30	4.00	0.40		•		
TPMX 170404R-B	10.30	4.00	0.40		•		•
TPMX 170408L-DT	10.30	4.00	0.80		•		
TPMX 170408L-G	10.30	4.00	0.80		•	•	
TPMX 170408R-B	10.30	4.00	0.80			•	•
TPMX 170408R-BG	10.30	4.00	0.80		•	•	•
TPMX 170408R-DT	10.30	4.00	0.80		•	•	
TPMX 170408R-G	10.30	4.00	0.80	•	•	•	•
TPMX 240504L-BG	14.20	5.50	0.40		•		
TPMX 240504R-B	14.20	5.50	0.40		•		•
TPMX 240512L-DT	14.20	5.50	1.20		•		
TPMX 240512L-G	14.20	5.50	1.20		•	•	
TPMX 240512R-B	14.20	5.50	1.20			•	•
TPMX 240512R-BG	14.20	5.50	1.20		•	•	•
TPMX 240512R-DT	14.20	5.50	1.20		•	•	
TPMX 240512R-G	14.20	5.50	1.20	•	•	•	•
TPMX 280708L-BG	17.00	7.50	0.80		•		
TPMX 280708R-B	17.00	7.50	0.80		•		•
TPMX 280716L-G	17.00	7.50	1.60		•	•	
TPMX 280716R-B	17.00	7.50	1.60			•	•
TPMX 280716R-BG	17.00	7.50	1.60		•	•	•
TPMX 280716R-DT	17.00	7.50	1.60		•	•	
TPMX 280716R-G	17.00	7.50	1.60	•	•	•	•

For tools, see pages: DDC-EC (69) • DDD-EC (29) • DSC-EC (55) • DSC-IC (62) • DSD-EC (27) • DSD-IC (28) • DSTR-EC (76) • DSTR-IC (78)


Chipbreaker Selection

Chipbreaker Selection					
G			B		
	versatile			good chip control for heat-resistant alloy	
BG			DT		
	chip control for difficult-to-cut steel			to reduce machine load	

ISCARDEEPCDRILL

GPS


Deep Drilling Solid Carbide Guide Pads



Designation	Dimensions				Tough $\longleftrightarrow$ Hard		
	OAW	OAL	OAH	RE	IC928	IC950	IC908
GPS-04-16-045-DC ⁽¹⁾	4.00	16.00	1.80	4.50			•
GPS-04-16-050-DC ⁽¹⁾	4.00	16.00	1.80	5.00			•
GPS-04-16-055-DC ⁽¹⁾	4.00	16.00	2.00	5.50	•		•
GPS-05-18-060-DC ⁽¹⁾	5.00	18.00	2.50	6.00	•		•
GPS-05-18-075-DC ⁽¹⁾	5.00	18.00	2.50	7.50	•		•
GPS-06-20-075-DC ⁽¹⁾	6.00	20.00	3.00	7.50			•
GPS-06-20-075	6.00	20.00	3.00	7.50		•	
GPS-06-20-085-DC ⁽¹⁾	6.00	20.00	3.00	8.50	•		•
GPS-06-20-085	6.00	20.00	3.00	8.50		•	
GPS-06-20-100-DC ⁽¹⁾	6.00	20.00	3.00	10.00	•		•
GPS-06-20-100	6.00	20.00	3.00	10.00		•	
GPS-06-20-120-DC ⁽¹⁾	6.00	20.00	3.00	12.00	•		•
GPS-06-20-120	6.00	20.00	3.00	12.00		•	
GPS-07-20-120-DC ⁽¹⁾	7.00	20.00	3.50	12.00	•		•
GPS-07-20-120	7.00	20.00	3.50	12.00		•	
GPS-08-25-155-DC ⁽¹⁾	8.00	25.00	4.50	15.50	•		•
GPS-08-25-155	8.00	25.00	4.50	15.50		•	
GPS-10-30-200-DC ⁽¹⁾	10.00	30.00	4.50	20.00	•		•
GPS-10-30-200	10.00	30.00	4.50	20.00		•	
GPS-10-35-200-DC ⁽¹⁾	10.00	35.00	6.00	20.00	•		•
GPS-10-35-200	10.00	35.00	6.00	20.00		•	
GPS-12-35-250-DC ⁽¹⁾	12.00	35.00	5.50	25.00	•		•
GPS-12-35-250	12.00	35.00	5.50	25.00		•	
GPS-14-40-250-DC ⁽¹⁾	14.00	40.00	7.50	25.00	•		•
GPS-14-40-250	14.00	40.00	7.50	25.00		•	
GPS-18-40-300-DC ⁽¹⁾	18.00	40.00	9.00	30.00	•		•

⁽¹⁾ DC - Double Chamfer

Universal Marking for Deep Drilling Tools



Guide Pad Grade Recommendation


Priority	Oil Coolant			Water Based Coolant		
	1	2	3	1	2	3
ISO-P	IC950	IC908	IC928	IC928	IC908	-
ISO-K	IC950	IC908	IC928	IC928	IC908	-
ISO-M	IC928	IC908	IC950	IC928	IC908	-
ISO-S	IC928	IC908	IC950	IC928	IC908	-



ISCARDEEPPDRILL

DDC-EA

Double Tube Counterboring Drills with Outer 4-Start Thread, Cartridges and Adjustable Diameter (25-40 mm dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	APMX	DRVS ⁽³⁾	LF	DCONMS
DDC-EA 25.00-26.40	25.00	26.40	2.80	24.0	72.50	21.00
DDC-EA 26.41-28.70	26.41	28.70	2.80	26.0	72.50	23.50
DDC-EA 28.71-31.00	28.71	31.00	2.80	28.0	75.50	25.50
DDC-EA 31.01-33.30	31.01	33.30	2.80	31.0	75.50	28.00
DDC-EA 33.31-36.20	33.31	36.20	2.80	34.0	75.50	30.00
DDC-EA 36.21-39.60	36.21	39.60	2.80	37.0	90.50	33.00
DDC-EA 39.61-39.99	39.61	39.99	2.80	37.0	90.50	36.00

• For user guide and quotation form, see pages 94-102 • Ordering example: DDC-EA 30.55



⁽¹⁾ Cutting diameter minimum

⁽²⁾ Cutting diameter maximum

⁽³⁾ Wrench size

For inserts, see pages: XPMT-45 (53)

For holders, see pages: TDO-I (D18.41-65.00) (88)



Spare Parts

DDC-EA

Diameter range	Adjustment ball	Adjustment screw	Wrench	Insert	Insert screw	Wrench
25.00-39.99	ADJUST BALL	SR11201755-7	HW 2.5	XPMT 16002-45	SR 11201754-4-4.5	T-9/51

Spare Parts (continued)


DDC-EA

Diameter range	Guide Pads	Qty	Lock screw	Qty	Wrench	Sub Guide Pads	Qty	Lock screw	Qty	Wrench	Protectors	Qty	Lock screw	Qty	Wrench
25.00-29.99	GPS-06-20-120-DC	2	SR 34-508	2	T-7/51	SGP-01	1	SR11201753-1	1	T-7/51	-	-	-	-	-
30.00-37.99	GPS-07-20-120-DC	3	CSTB-3L065	3	T-9/51	SGP-01	1	SR11201753-1	1	T-7/51	-	-	-	-	-
38.00-39.99	GPS-08-25-155-DC	3	CSTB-3L065	3	T-9/51	SGP-02	1	SR11201753-4	1	T-9/51	GPP-06	3	SR11201753-4	3	T-9/51

ISCARDEEPPDRILL

XPMT-45

Inserts for DSC Boring Heads




Designation	Dimensions		Tough	Hard
	W1	S	IB55	IC950
XPMT 16002-45	9.50	2.80	•	•

For tools, see pages: DDC-EA (66) • DSC-EA (52) • DSC-IA (60)

ISCARDEEPPDRILL

SGP

Drilling Head Sub-Guide Pads




Designation	OAL	OAW	OAH
SGP-01	10.00	6.00	3.00
SGP-02	10.00	8.00	4.50
SGP-03	10.00	10.00	5.00
SGP-04	20.00	14.00	7.00

• Select an outer cartridge and pad for the required enlarged diameter.

ISCARDEEPPDRILL

GPP

Drilling Head Guide Pad Protectors



Designation	OAL	OAW	OAH
GPP-06	8.00	8.00	4.50
GPP-07	10.00	10.00	6.00
GPP-08	14.00	14.00	7.50
GPP-09	18.00	18.00	9.00

• Select an outer cartridge and pad for the required enlarged diameter.

Recommended claming torque

Insert Screw	
	(N·m)
SR 11201753-2	1
SR 11201753-3	1.3
SR 11201753-7	2.3
SR 11201753-9	3.5
SR 11201753-7	5

Cartridge Screw	
	(N·m)
SR 11201752-1	3.5
SR 11201753-5	2.3
SR 11201753-5	3.5
SR 11201756-7	3
SR 11201756-10	2.2
SR 11201756-11	2.2
SR 11201756-12	3
SR 11201756-15	5


Guide Pad Screw	
	(N·m)
SR 14-571/5	3.5
SR 34-506-C	2.3
LS1206SSS	3



ISCARDEEPCDRILL

GPS


Deep Drilling Solid Carbide Guide Pads



Designation	Dimensions				Tough $\longleftrightarrow$ Hard		
	OAW	OAL	OAH	RE	IC928	IC950	IC908
GPS-04-16-045-DC ⁽¹⁾	4.00	16.00	1.80	4.50			•
GPS-04-16-050-DC ⁽¹⁾	4.00	16.00	1.80	5.00			•
GPS-04-16-055-DC ⁽¹⁾	4.00	16.00	2.00	5.50	•		•
GPS-05-18-060-DC ⁽¹⁾	5.00	18.00	2.50	6.00	•		•
GPS-05-18-075-DC ⁽¹⁾	5.00	18.00	2.50	7.50	•		•
GPS-06-20-075-DC ⁽¹⁾	6.00	20.00	3.00	7.50			•
GPS-06-20-075	6.00	20.00	3.00	7.50		•	
GPS-06-20-085-DC ⁽¹⁾	6.00	20.00	3.00	8.50	•		•
GPS-06-20-085	6.00	20.00	3.00	8.50		•	
GPS-06-20-100-DC ⁽¹⁾	6.00	20.00	3.00	10.00	•		•
GPS-06-20-100	6.00	20.00	3.00	10.00		•	
GPS-06-20-120-DC ⁽¹⁾	6.00	20.00	3.00	12.00	•		•
GPS-06-20-120	6.00	20.00	3.00	12.00		•	
GPS-07-20-120-DC ⁽¹⁾	7.00	20.00	3.50	12.00	•		•
GPS-07-20-120	7.00	20.00	3.50	12.00		•	
GPS-08-25-155-DC ⁽¹⁾	8.00	25.00	4.50	15.50	•		•
GPS-08-25-155	8.00	25.00	4.50	15.50		•	
GPS-10-30-200-DC ⁽¹⁾	10.00	30.00	4.50	20.00	•		•
GPS-10-30-200	10.00	30.00	4.50	20.00		•	
GPS-10-35-200-DC ⁽¹⁾	10.00	35.00	6.00	20.00	•		•
GPS-10-35-200	10.00	35.00	6.00	20.00		•	
GPS-12-35-250-DC ⁽¹⁾	12.00	35.00	5.50	25.00	•		•
GPS-12-35-250	12.00	35.00	5.50	25.00		•	
GPS-14-40-250-DC ⁽¹⁾	14.00	40.00	7.50	25.00	•		•
GPS-14-40-250	14.00	40.00	7.50	25.00		•	
GPS-18-40-300-DC ⁽¹⁾	18.00	40.00	9.00	30.00	•		•

⁽¹⁾ DC - Double Chamfer

Universal Marking for Deep Drilling Tools




Guide Pad Grade Recommendation

Priority	Oil Coolant			Water Based Coolant		
	1	2	3	1	2	3
ISO-P	IC950	IC908	IC928	IC928	IC908	-
ISO-K	IC950	IC908	IC928	IC928	IC908	-
ISO-M	IC928	IC908	IC950	IC928	IC908	-
ISO-S	IC928	IC908	IC950	IC928	IC908	-

ISCARDEEPPDRILL

DDC-EC

Double Tube Counterboring Drills with Outer 4-Start Thread, Cartridges and Adjustable Diameter (40-184mm dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	DRVS ⁽³⁾	LF	DCONMS	APMX	APMX_2
DDC-EC 40.00-43.00	40.00	43.00	40.0	91.00	36.00	6.40	4.00
DDC-EC 43.01-47.00	43.01	47.00	43.0	95.00	39.00	6.40	4.00
DDC-EC 47.01-51.70	47.01	51.70	48.0	100.00	43.00	6.40	4.00
DDC-EC 51.71-56.20	51.71	56.20	53.0	100.00	47.00	6.40	4.00
DDC-EC 56.21-65.00	56.21	65.00	61.0	110.00	51.00	7.20	4.80
DDC-EC 65.00-66.99	65.00	66.99	63.0	150.00	52.00	7.20	4.80
DDC-EC 67.00-72.99	67.00	72.99	69.0	150.00	58.00	10.40	6.40
DDC-EC 73.00-79.99	73.00	79.99	76.0	150.00	63.00	10.40	6.40
DDC-EC 80.00-86.99	80.00	86.99	83.0	180.00	70.00	10.40	6.40
DDC-EC 87.00-99.99	87.00	99.99	96.0	180.00	77.00	10.40	6.40
DDC-EC 100.00-111.99	100.00	111.99	107.0	180.00	89.00	10.40	6.40
DDC-EC 112.00-123.99	112.00	123.99	119.0	205.00	101.00	10.40	6.40
DDC-EC 124.00-135.99	124.00	135.99	131.0	205.00	113.00	10.40	6.40
DDC-EC 136.00-147.99	136.00	147.99	143.0	205.00	125.00	10.40	6.40
DDC-EC 148.00-159.99	148.00	159.99	155.0	225.00	137.00	10.40	6.40
DDC-EC 160.00-171.99	160.00	171.99	167.0	225.00	149.00	10.40	6.40
DDC-EC 172.00-183.99	172.00	183.99	179.0	225.00	161.00	10.40	6.40

• For user guide and quotation form, see pages 94-102 • Ordering example: DDC-EC 130.35

⁽¹⁾ Cutting diameter minimum



⁽²⁾ Cutting diameter maximum

⁽³⁾ Wrench size

For inserts, see pages: TPMX (30)

For holders, see pages: TDO-I (D18.41-65.00) (88) • TDO-I (D65.00-171.99) (89)






ISCARDEEPCDRILL

CAORC

Boring Head Peripheral Cartridge




Adjustment Cartridge for Shallow Depth of Cut

Diameter Range	Adjustment Cartridge	Adjustment screw (2 pcs)	Wrench	Lock screw	Wrench	Insert	Insert screw	Wrench
40.00-51.99	CAORC-0845	SR11201755-6	HW 2.0	SR11201756-10	HW 2.5	TPMX 140308L-G	SR11201753-3	T-8/53
52.00-66.99	CAORC-103	SR11201755-8	HW 2.5	SR11201756-12	HW 3.0	TPMX 170408L-G	SR11201753-7	T-9/51
67.00-183.99	CAORC-142	SR11201755-9	HW 2.5	SR11201756-15	HW 4.0	TPMX 240512L-G	SR11201753-9	T-15/51

ISCARDEEPCDRILL

CAOD

Drilling / Boring Head Peripheral Cartridge



Adjustment Cartridge for Large Depth of Cut

Diameter Range	Adjustment Cartridge	Adjustment screw (2 pcs)	Wrench	Lock screw	Wrench	Insert	Insert screw	Wrench
40.00-51.99	CAOD-0845	SR11201755-6	HW 2.0	SR11201756-10	HW 2.5	TPMX 140308R-G	SR11201753-3	T-8/53
52.00-66.99	CAOD-103	SR11201755-8	HW 2.5	SR11201756-12	HW 3.0	TPMX 170408R-G	SR11201753-7	T-9/51
67.00-183.99	CAOD-142	SR11201755-9	HW 2.5	SR11201756-15	HW 4.0	TPMX 240512R-G	SR11201753-9	T-15/51

Guide Pads and Other Spare Parts


DDC-EC

Diameter Range	Guide Pads	Qty	Lock screw	Qty	Wrench	Sub Guide Pads	Qty	Lock screw	Qty	Wrench	Protectors	Qty	Lock screw	Qty	Wrench
40.00-45.99	GPS-08-25-155-DC	3	CSTB-3L065	3	T-9/51	SGP-02	3	SR11201753-4	1	T-9/51	GPP-06	3	SR11201753-4	3	T-9/51
46.00-59.99	GPS-10-35-200-DC	3	SR11201753-8	3	T-15/51	SGP-02	3	SR11201753-4	1	T-9/51	GPP-07	3	SR11201753-8	3	T-15/51
60.00-99.99	GPS-14-40-250-DC	3	SR11201752-2	3	T-15/51	SGP-03	3	SR11201753-4	1	T-9/51	GPP-08	3	SR11201752-2	3	T-15/51
100.00-135.99	GPS-18-40-300-DC	3	SR11201756-7S	3	HW 3.0	SGP-04	3	SR11201752-2	1	T-15/51	GPP-09	3	SR11201756-7S	3	HW 3.0
136.00-183.99	GPS-18-40-300-DC	5	SR11201756-7S	5	HW 3.0	SGP-04	5	SR11201752-2	1	T-15/51	GPP-09	5	SR11201756-7S	5	HW 3.0

ISCARDEEPCDRILL

TPMX

Inserts for Drilling / Counterboring
/ Trepanning Tools



Designation	Dimensions			Tough ↔ Hard			
	IC	S	RE	IC8355	IC908	IC948	IC806
TPMX 140304R-B	8.45	3.50	0.40		•		•
TPMX 140308L-G	8.45	3.50	0.80		•		
TPMX 140308R-B	8.45	3.50	0.80			•	•
TPMX 140308R-DT	8.45	3.50	0.80		•	•	
TPMX 140308R-G	8.45	3.50	0.80	•	•	•	•
TPMX 170404L-BG	10.30	4.00	0.40		•		
TPMX 170404R-B	10.30	4.00	0.40		•		•
TPMX 170408L-DT	10.30	4.00	0.80		•		
TPMX 170408L-G	10.30	4.00	0.80		•	•	
TPMX 170408R-B	10.30	4.00	0.80			•	•
TPMX 170408R-BG	10.30	4.00	0.80		•	•	•
TPMX 170408R-DT	10.30	4.00	0.80		•	•	
TPMX 170408R-G	10.30	4.00	0.80	•	•	•	•
TPMX 240504L-BG	14.20	5.50	0.40		•		
TPMX 240504R-B	14.20	5.50	0.40		•		•
TPMX 240512L-DT	14.20	5.50	1.20		•		
TPMX 240512L-G	14.20	5.50	1.20		•	•	
TPMX 240512R-B	14.20	5.50	1.20			•	•
TPMX 240512R-BG	14.20	5.50	1.20		•	•	•
TPMX 240512R-DT	14.20	5.50	1.20		•	•	
TPMX 240512R-G	14.20	5.50	1.20	•	•	•	•
TPMX 280708L-BG	17.00	7.50	0.80		•		
TPMX 280708R-B	17.00	7.50	0.80		•		•
TPMX 280716L-G	17.00	7.50	1.60		•	•	
TPMX 280716R-B	17.00	7.50	1.60			•	•
TPMX 280716R-BG	17.00	7.50	1.60		•	•	•
TPMX 280716R-DT	17.00	7.50	1.60		•	•	
TPMX 280716R-G	17.00	7.50	1.60	•	•	•	•

For tools, see pages: DDC-EC (69) • DDD-EC (29) • DSC-EC (55) • DSC-IC (62) • DSD-EC (27) • DSD-IC (28) • DSTR-EC (76) • DSTR-IC (78)

Chipbreaker Selection


Chipbreaker Selection					
G			B		
	versatile			good chip control for heat-resistant alloy	
BG			DT		
	chip control for difficult-to-cut steel			to reduce machine load	



ISCARDEEPPDRILL

SGP

Drilling Head Sub-Guide Pads




Designation	OAL	OAW	OAH
SGP-01	10.00	6.00	3.00
SGP-02	10.00	8.00	4.50
SGP-03	10.00	10.00	5.00
SGP-04	20.00	14.00	7.00

- Select an outer cartridge and pad for the required enlarged diameter.

ISCARDEEPPDRILL

GPP

Drilling Head Guide Pad Protectors



Designation	OAL	OAW	OAH
GPP-06	8.00	8.00	4.50
GPP-07	10.00	10.00	6.00
GPP-08	14.00	14.00	7.50
GPP-09	18.00	18.00	9.00

- Select an outer cartridge and pad for the required enlarged diameter.

Recommended claming torque

Insert Screw	
	(N·m)
SR 11201753-2	1
SR 11201753-3	1.3
SR 11201753-7	2.3
SR 11201753-9	3.5
SR 11201753-7	5


Cartridge Screw	
	(N·m)
SR 11201752-1	3.5
SR 11201753-5	2.3
SR 11201753-5	3.5
SR 11201756-7	3
SR 11201756-10	2.2
SR 11201756-11	2.2
SR 11201756-12	3
SR 11201756-15	5

Guide Pad Screw	
	(N·m)
SR 14-571/5	3.5
SR 34-506-C	2.3
LS1206SSS	3

ISCARDEEPDRILL

GPS


Deep Drilling Solid Carbide Guide Pads



Designation	Dimensions				Tough ↔ Hard		
	OAW	OAL	OAH	RE	IC928	IC950	IC908
GPS-04-16-045-DC ⁽¹⁾	4.00	16.00	1.80	4.50			•
GPS-04-16-050-DC ⁽¹⁾	4.00	16.00	1.80	5.00			•
GPS-04-16-055-DC ⁽¹⁾	4.00	16.00	2.00	5.50	•		•
GPS-05-18-060-DC ⁽¹⁾	5.00	18.00	2.50	6.00	•		•
GPS-05-18-075-DC ⁽¹⁾	5.00	18.00	2.50	7.50	•		•
GPS-06-20-075-DC ⁽¹⁾	6.00	20.00	3.00	7.50			•
GPS-06-20-075	6.00	20.00	3.00	7.50		•	
GPS-06-20-085-DC ⁽¹⁾	6.00	20.00	3.00	8.50	•		•
GPS-06-20-085	6.00	20.00	3.00	8.50		•	
GPS-06-20-100-DC ⁽¹⁾	6.00	20.00	3.00	10.00	•		•
GPS-06-20-100	6.00	20.00	3.00	10.00		•	
GPS-06-20-120-DC ⁽¹⁾	6.00	20.00	3.00	12.00	•		•
GPS-06-20-120	6.00	20.00	3.00	12.00		•	
GPS-07-20-120-DC ⁽¹⁾	7.00	20.00	3.50	12.00	•		•
GPS-07-20-120	7.00	20.00	3.50	12.00		•	
GPS-08-25-155-DC ⁽¹⁾	8.00	25.00	4.50	15.50	•		•
GPS-08-25-155	8.00	25.00	4.50	15.50		•	
GPS-10-30-200-DC ⁽¹⁾	10.00	30.00	4.50	20.00	•		•
GPS-10-30-200	10.00	30.00	4.50	20.00		•	
GPS-10-35-200-DC ⁽¹⁾	10.00	35.00	6.00	20.00	•		•
GPS-10-35-200	10.00	35.00	6.00	20.00		•	
GPS-12-35-250-DC ⁽¹⁾	12.00	35.00	5.50	25.00	•		•
GPS-12-35-250	12.00	35.00	5.50	25.00		•	
GPS-14-40-250-DC ⁽¹⁾	14.00	40.00	7.50	25.00	•		•
GPS-14-40-250	14.00	40.00	7.50	25.00		•	
GPS-18-40-300-DC ⁽¹⁾	18.00	40.00	9.00	30.00	•		•

⁽¹⁾ DC - Double Chamfer

Universal Marking for Deep Drilling Tools




Guide Pad Grade Recommendation

Priority	Oil Coolant			Water Based Coolant		
	1	2	3	1	2	3
ISO-P	IC950	IC908	IC928	IC928	IC908	-
ISO-K	IC950	IC908	IC928	IC928	IC908	-
ISO-M	IC928	IC908	IC950	IC928	IC908	-
ISO-S	IC928	IC908	IC950	IC928	IC908	-


Technical Information - Cartridge Style Counterboring Head Diameter Settings

The drill head diameter is set and inspected with a master insert in our final inspection. However, the inserts in the market have a tolerance fluctuation so each time you change or index the insert, the diameter must be adjusted as per the following method.

Note: When a corner change is made on the insert, it must be adjusted to the correct size or damage can be caused to the head body or work piece material.




1. The dimensional guide pad must be slid forward to measure the diameter
 - 1.1 Loosen the lock screw and slide the guide pad forward
 - 1.2 Retighten the lock screw at the measuring position




2. Measure the diameter with a micrometer. We recommend setting the tool diameter at h8 tolerance to the cutting diameter


Note: If the diameter is incorrect, go to **step 3**. If it's correct, go to **step 4**




3. Adjust the outer cartridge
 - 3.1 First loosen the lock screw of the outer cartridge and then tighten it slightly



- 3.2 Proceed to adjust the diameter, using the 2 adjustment screws and measure with a micrometer







- 3.3 When set to the size, re-tighten the lock screw
 - 3.4 Recheck the diameter with a micrometer. If it remains out of tolerance, repeat the procedure from step 3.1
- Note:** Please make sure to tighten the lock screw firmly before using. If loose, the cartridge may move and cause serious problems during machining



4. Slide the dimensional guide pad back to the original position and tighten the lock screw
- Please check all the lock screws are firmly tightened as they may come loose if vibration occurs during drilling**

Technical Information - Adjustable Counterboring Head Diameter Settings

Drill diameter is adjusted with an adjust ball for diameter $\varnothing 25 - \varnothing 39.99$ mm with the following method.

 Dimensional guide pad	1. Slide the dimensional guide pad forward and then re-tighten the lock screw at the measuring position
 Head body Adjust ball Insert Adjust screw Wrench	2. Tighten the adjust screw
 Drill Dia. $\varnothing D_c$	3. As the adjust screw moves forward, insert moves in a peripheral direction
 Drill Dia. $\varnothing D_c$	4. Measure the diameter with a micrometer. If the diameter is larger than expected, loosen the adjust screw and insert screw, then re-tighten the insert screw. Repeat the procedure from step 2




Trepanning Heads

INDEXABLE TREPPANNING (SPECIAL) DSTR EC/IC

ISCAR DEEP DRILL

DSTR-EC

Single Tube Trepanning Drills with Outer 4-Start Thread, Cartridges, and Adjustable Diameter (100-328mm dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	APMX	DRVS ⁽³⁾	LF	DCONMS
DSTR-EC 100.00-111.99	100.00	111.99	38.00	107.0	174.00	89.00
DSTR-EC 112.00-123.99	112.00	123.99	38.00	119.0	204.00	101.00
DSTR-EC 124.00-135.99	124.00	135.99	49.50	131.0	204.00	113.00
DSTR-EC 136.00-147.99	136.00	147.99	49.50	143.0	204.00	125.00
DSTR-EC 148.00-159.99	148.00	159.99	49.50	155.0	229.00	137.00
DSTR-EC 160.00-171.99	160.00	171.99	49.50	167.0	229.00	149.00
DSTR-EC 172.00-183.99	172.00	183.99	49.50	179.0	229.00	161.00
DSTR-EC 184.00-195.99	184.00	195.99	49.50	191.0	249.00	173.00
DSTR-EC 196.00-207.99	196.00	207.99	56.50	203.0	249.00	185.00
DSTR-EC 208.00-219.99	208.00	219.99	56.50	215.0	249.00	197.00
DSTR-EC 220.00-231.99	220.00	231.99	56.50	227.0	284.00	208.00
DSTR-EC 232.00-243.99	232.00	243.99	56.50	239.0	284.00	220.00
DSTR-EC 244.00-255.99	244.00	255.99	56.50	251.0	284.00	232.00
DSTR-EC 256.00-267.99	256.00	267.99	56.50	263.0	304.00	244.00
DSTR-EC 268.00-279.99	268.00	279.99	56.50	275.0	304.00	256.00
DSTR-EC 280.00-291.99	280.00	291.99	56.50	287.0	304.00	268.00
DSTR-EC 292.00-303.99	292.00	303.99	56.50	299.0	324.00	280.00
DSTR-EC 304.00-315.99	304.00	315.99	56.50	311.0	324.00	292.00
DSTR-EC 316.00-328.00	316.00	328.00	56.50	323.0	324.00	304.00

• For user guide and quotation form, see pages 94-102 • Ordering example: DSTR-EC 120.55

⁽¹⁾ Cutting diameter minimum



⁽²⁾ Cutting diameter maximum

⁽³⁾ Wrench size

For inserts, see pages: TPMX (30)


For holders, see pages: TS-I** (86)





ISCARDEEPDRILL

CAOD Peripheral Cartridge




Peripheral Cartridge

Diameter Range	Adjustment Cartridge	Adjustment screw (2 pcs)	Wrench	Lock screw	Wrench	Insert	Insert screw	Wrench
100.00-123.99	CAOD-103	SR11201755-8	HW 2.5	SR11201756-12	HW 3.0	TPMX 1704..R..	SR11201753-7	T-9/51
124.00-195.99	CAOD-142	SR11201755-9	HW 2.5	SR11201756-15	HW 4.0	TPMX 2405..R..	SR11201753-9	T-15/51
196.00-328.00	CAOD-170	SR11201755-11	HW 3.0	SR 11201756-15	HW 4.0	TPMX 2807..R..	SR11201753-10	T-20/51

ISCARDEEPDRILL

CAID Inner Cartridge



Inner Cartridge

DSTR-EC / DSTR-IC

Diameter Range	Cartridge	Lock screw	Wrench	Insert	Insert Screw	Wrench
100.00-123.99	CAID-103L	SR11201752-1	T-15/51	TPMX 1704..L..	SR11201753-7	T-9/51
124.00-135.99	CAID-142L	SR11201756-7	HW 3.0	TPMX 2405..L..	SR11201753-9	T-15/51
136.00-328.00	CAID-142L	SR11201756-7	HW 3.0L	TPMX 2405..L..	SR11201753-9	T-15/51

Guide Pads

DSTR-EC / DSTR-IC


Diameter Range	Guide Pads	Qty	Lock screw	Wrench	Guide Pad Protectors	Qty	Lock screw	Wrench	Sub Guide Pad	Qty	Lock screw	Wrench
100.00-135.99	GPS-18-40-300-DC	3	SR11201756-7S	HW 3.0	GPP-09	3	SR11201756-7S	HW 3.0	SGP-04	1	SR11201752-2	T-15/51
136.00-207.99	GPS-18-40-300-DC	3	SR11201756-7S	HW 3.0	GPP-09	3	SR11201756-7S	HW 3.0	SGP-04	1	SR11201752-2	T-15/51
208.00-328.00	GPB-22-50-750	3	SR11201752-2	T-15/51	GPP-10	3	SR11201756-7S	HW 3.0	SGP-04	1	SR11201752-2	T-15/51



ISCARDEEPDRILL

DSTR-IC

Single Tube Trepanning Drills with Inner Single Start Thread, Cartridges and Adjustable Diameter (100-306mm dia.)



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	APMX	DRVS ⁽³⁾	LF	DCONMS
DSTR-IC 100.00-110.99	100.00	110.99	38.00	106.0	139.00	90.00
DSTR-IC 111.00-122.99	111.00	122.99	38.00	118.0	149.00	102.00
DSTR-IC 123.00-123.99	123.00	123.99	38.00	119.0	149.00	114.00
DSTR-IC 124.00-134.99	124.00	134.99	49.50	130.0	149.00	114.00
DSTR-IC 135.00-148.99	135.00	148.99	49.50	144.0	149.00	126.00
DSTR-IC 149.00-161.99	149.00	161.99	49.50	157.0	149.00	139.00
DSTR-IC 162.00-173.99	162.00	173.99	49.50	169.0	169.00	151.00
DSTR-IC 174.00-185.99	174.00	185.99	49.50	181.0	169.00	163.00
DSTR-IC 186.00-195.99	186.00	195.99	49.50	191.0	169.00	175.00
DSTR-IC 196.00-197.99	196.00	197.99	56.50	193.0	169.00	175.00
DSTR-IC 198.00-209.99	198.00	209.99	56.50	205.0	169.00	187.00
DSTR-IC 210.00-221.99	210.00	221.99	56.50	217.0	189.00	199.00
DSTR-IC 222.00-233.99	222.00	233.99	56.50	229.0	189.00	211.00
DSTR-IC 234.00-245.99	234.00	245.99	56.50	241.0	189.00	223.00
DSTR-IC 246.00-257.99	246.00	257.99	56.50	253.0	189.00	235.00
DSTR-IC 258.00-266.99	258.00	266.99	56.50	262.0	209.00	245.00
DSTR-IC 267.00-281.99	267.00	281.99	56.50	277.0	209.00	259.00
DSTR-IC 282.00-293.99	282.00	293.99	56.50	289.0	209.00	271.00
DSTR-IC 294.00-305.99	294.00	305.99	56.50	301.0	209.00	283.00

• For user guide and quotation form, see pages 94-102 • Ordering example: DSTR-IC 120.55

⁽¹⁾ Cutting diameter minimum



⁽²⁾ Cutting diameter maximum

⁽³⁾ Wrench size

For inserts, see pages: TPMX (30)

For holders, see pages: TS-O** (87)






ISCARDEEPDRILL

CAOD

Peripheral Cartridge




Peripheral Cartridge

Diameter Range	Adjustment Cartridge	Adjustment screw (2 pcs)	Wrench	Lock screw	Wrench	Insert	Insert screw	Wrench
100.00-123.99	CAOD-103	SR11201755-8	HW 2.5	SR11201756-12	HW 3.0	TPMX 1704..R..	SR11201753-7	T-9/51
124.00-195.99	CAOD-142	SR11201755-9	HW 2.5	SR11201756-15	HW 4.0	TPMX 2405..R..	SR11201753-9	T-15/51
196.00-305.99	CAOD-170	SR11201755-11	HW 3.0	SR 11201756-15	HW 4.0	TPMX 2807..R..	SR11201753-10	T-20/51

ISCARDEEPDRILL

CAID

Inner Cartridge



Inner Cartridge

Diameter Range	Cartridge	Lock screw	Wrench	Insert	Insert screw	Wrench
100.00-123.99	CAID-103L	SR11201752-1	T-15/51	TPMX 1704..L..	SR11201753-7	T-9/51
124.00-135.99	CAID-142L	SR11201756-7	HW 3.0	TPMX 2405..L..	SR11201753-9	T-15/51
136.00-305.99	CAID-142L	SR11201756-7	HW 3.0L	TPMX 2405..L..	SR11201753-9	T-15/51

Guide Pads

DSTR-EC / DSTR-IC


Diameter Range	Guide Pads	Qty	Lock screw	Wrench	Guide Pad Protectors	Qty	Lock screw	Wrench	Sub Guide Pads	Qty	Lock screw	Wrench
100.00-135.99	GPS-18-40-300-DC	3	SR11201756-7S	HW 3.0	GPP-09	3	SR11201756-7S	HW 3.0	SGP-04	1	SR11201752-2	T-15/51
136.00-207.99	GPS-18-40-300-DC	3	SR11201756-7S	HW 3.0	GPP-09	3	SR11201756-7S	HW 3.0	SGP-04	1	SR11201752-2	T-15/51
208.00-305.99	GPB-22-50-750	3	SR11201752-2	T-15/51	GPP-10	3	SR11201756-7S	HW 3.0	SGP-04	1	SR11201752-2	T-15/51



ISCARDEEPDRILL

TPMX





Inserts for Drilling / Counterboring
/ Trepanning Tools



Designation	Dimensions			Tough ↔ Hard			
	IC	S	RE	IC8355	IC908	IC948	IC806
TPMX 140304R-B	8.45	3.50	0.40		•		•
TPMX 140308L-G	8.45	3.50	0.80		•		
TPMX 140308R-B	8.45	3.50	0.80			•	•
TPMX 140308R-DT	8.45	3.50	0.80		•	•	
TPMX 140308R-G	8.45	3.50	0.80	•	•	•	•
TPMX 170404L-BG	10.30	4.00	0.40		•		
TPMX 170404R-B	10.30	4.00	0.40		•		•
TPMX 170408L-DT	10.30	4.00	0.80		•		
TPMX 170408L-G	10.30	4.00	0.80		•	•	
TPMX 170408R-B	10.30	4.00	0.80			•	•
TPMX 170408R-BG	10.30	4.00	0.80		•	•	•
TPMX 170408R-DT	10.30	4.00	0.80		•	•	
TPMX 170408R-G	10.30	4.00	0.80	•	•	•	•
TPMX 240504L-BG	14.20	5.50	0.40		•		
TPMX 240504R-B	14.20	5.50	0.40		•		•
TPMX 240512L-DT	14.20	5.50	1.20		•		
TPMX 240512L-G	14.20	5.50	1.20		•	•	
TPMX 240512R-B	14.20	5.50	1.20			•	•
TPMX 240512R-BG	14.20	5.50	1.20		•	•	•
TPMX 240512R-DT	14.20	5.50	1.20		•	•	
TPMX 240512R-G	14.20	5.50	1.20	•	•	•	•
TPMX 280708L-BG	17.00	7.50	0.80		•		
TPMX 280708R-B	17.00	7.50	0.80		•		•
TPMX 280716L-G	17.00	7.50	1.60		•	•	
TPMX 280716R-B	17.00	7.50	1.60			•	•
TPMX 280716R-BG	17.00	7.50	1.60		•	•	•
TPMX 280716R-DT	17.00	7.50	1.60		•	•	
TPMX 280716R-G	17.00	7.50	1.60	•	•	•	•

For tools, see pages: DDC-EC (69) • DDD-EC (29) • DSC-EC (55) • DSC-IC (62) • DSD-EC (27) • DSD-IC (28) • DSTR-EC (76) • DSTR-IC (78)


Chipbreaker Selection

Chipbreaker Selection					
G			B		
	versatile			good chip control for heat-resistant alloy	
BG			DT		
	chip control for difficult-to-cut steel			to reduce machine load	

ISCARDEEPDRILL

SGP

Drilling Head Sub-Guide Pads




Designation	OAL	OAW	OAH
SGP-01	10.00	6.00	3.00
SGP-02	10.00	8.00	4.50
SGP-03	10.00	10.00	5.00
SGP-04	20.00	14.00	7.00

- Select an outer cartridge and pad for the required enlarged diameter.

ISCARDEEPDRILL

GPP

Drilling Head Guide
Pad Protectors



Designation	OAL	OAW	OAH
GPP-06	8.00	8.00	4.50
GPP-07	10.00	10.00	6.00
GPP-08	14.00	14.00	7.50
GPP-09	18.00	18.00	9.00

- Select an outer cartridge and pad for the required enlarged diameter.

Recommended claming torque

Insert Screw	
	(N·m)
SR 11201753-2	1
SR 11201753-3	1.3
SR 11201753-7	2.3
SR 11201753-9	3.5
SR 11201753-7	5

Cartridge Screw	
	(N·m)
SR 11201752-1	3.5
SR 11201753-5	2.3
SR 11201753-5	3.5
SR 11201756-7	3
SR 11201756-10	2.2
SR 11201756-11	2.2
SR 11201756-12	3
SR 11201756-15	5

Guide Pad Screw	
	(N·m)
SR 14-571/5	3.5
SR 34-506-C	2.3
LS1206SSS	3






ISCARDEEPCDRILL

GPS


Deep Drilling Solid Carbide Guide Pads



Designation	Dimensions				Tough $\longleftrightarrow$ Hard		
	OAW	OAL	OAH	RE	IC928	IC950	IC908
GPS-04-16-045-DC ⁽¹⁾	4.00	16.00	1.80	4.50			•
GPS-04-16-050-DC ⁽¹⁾	4.00	16.00	1.80	5.00			•
GPS-04-16-055-DC ⁽¹⁾	4.00	16.00	2.00	5.50	•		•
GPS-05-18-060-DC ⁽¹⁾	5.00	18.00	2.50	6.00	•		•
GPS-05-18-075-DC ⁽¹⁾	5.00	18.00	2.50	7.50	•		•
GPS-06-20-075-DC ⁽¹⁾	6.00	20.00	3.00	7.50			•
GPS-06-20-075	6.00	20.00	3.00	7.50		•	
GPS-06-20-085-DC ⁽¹⁾	6.00	20.00	3.00	8.50	•		•
GPS-06-20-085	6.00	20.00	3.00	8.50		•	
GPS-06-20-100-DC ⁽¹⁾	6.00	20.00	3.00	10.00	•		•
GPS-06-20-100	6.00	20.00	3.00	10.00		•	
GPS-06-20-120-DC ⁽¹⁾	6.00	20.00	3.00	12.00	•		•
GPS-06-20-120	6.00	20.00	3.00	12.00		•	
GPS-07-20-120-DC ⁽¹⁾	7.00	20.00	3.50	12.00	•		•
GPS-07-20-120	7.00	20.00	3.50	12.00		•	
GPS-08-25-155-DC ⁽¹⁾	8.00	25.00	4.50	15.50	•		•
GPS-08-25-155	8.00	25.00	4.50	15.50		•	
GPS-10-30-200-DC ⁽¹⁾	10.00	30.00	4.50	20.00	•		•
GPS-10-30-200	10.00	30.00	4.50	20.00		•	
GPS-10-35-200-DC ⁽¹⁾	10.00	35.00	6.00	20.00	•		•
GPS-10-35-200	10.00	35.00	6.00	20.00		•	
GPS-12-35-250-DC ⁽¹⁾	12.00	35.00	5.50	25.00	•		•
GPS-12-35-250	12.00	35.00	5.50	25.00		•	
GPS-14-40-250-DC ⁽¹⁾	14.00	40.00	7.50	25.00	•		•
GPS-14-40-250	14.00	40.00	7.50	25.00		•	
GPS-18-40-300-DC ⁽¹⁾	18.00	40.00	9.00	30.00	•		•

⁽¹⁾ DC - Double Chamfer

Universal Marking for Deep Drilling Tools




Guide Pad Grade Recommendation


Priority	Oil Coolant			Water Based Coolant		
	1	2	3	1	2	3
ISO-P	IC950	IC908	IC928	IC928	IC908	-
ISO-K	IC950	IC908	IC928	IC928	IC908	-
ISO-M	IC928	IC908	IC950	IC928	IC908	-
ISO-S	IC928	IC908	IC950	IC928	IC908	-

Technical Information - Cartridge Style Trepanning Head Diameter Settings


The Drill Head diameter is set and inspected with a master insert in our final inspection. However, the inserts in the market have a tolerance fluctuation so each time you change or index the insert, the diameter must be adjusted as per the following method.




1. When a corner change is made on the insert, it must be adjusted to the correct size or damage can be caused to the head body or work piece material




2. The dimensional guide pad must be slid forward to measure the diameter
 - 2.1 Loosen the lock screw and slide the guide pad forward
 - 2.2 Re-tighten the lock screw at the measuring position




3. Measure the diameter with a micrometer
We recommend setting the tool diameter at h8 tolerance to the cutting diameter
If the diameter is incorrect, go to step 4
If it's correct, go to step 5




4. Adjust the peripheral cartridge
 - 4.1 First loosen the lock screw of the peripheral cartridge and then tighten it slightly



- 4.2 Proceed to adjust the diameter, using the 2 adjust screws and measure with a micrometer



- 4.3 When set to the size, retighten the lock screw
 - 4.4 Recheck the diameter with a micrometer. If it remains out of tolerance, repeat the procedure from step 4-1
Please make sure to tighten the lock screw firmly before using. If loose, the cartridge may move and cause serious problems during machining




5. Slide the dimensional guide pad back to the original position and tighten the lock screw
6. Replace the inner cartridge and tighten the lock screw
Please check that all the lock screws are firmly tightened as they may come loose if vibration occurs during drilling



ISCAR DEEP DRILL

SHIM GPS

Shims for GPS Pads



Designation	OAW	OAL
SHIMSET-GP04	4.00	15.90
SHIMSET-GP05	5.00	18.00
SHIMSET-GP06	6.00	20.00

- A shim set contains 5 shims in thicknesses of 0.01mm, 0.02mm, 0.03mm, 0.04 mm and 0.05mm respectively
- Adjusting shims are sold by set only, and are not to be sold separately


Shim Combinations for Various Diameters

Diameter Adjustments (mm)	Shim (s) for Measuring Guide Pad	Shim (s) for Supporting Guide Pad	Number of Shim Sets Needed
+0.01	0.01	0.01	2
+0.02	0.02	0.02	2
+0.03	0.03	0.01+0.02	1
+0.04	0.04	0.01+0.03	1
+0.05	0.05	0.02+0.03	1
+0.06	0.01+0.05	0.02+0.04	1
+0.07	0.02+0.05	0.03+0.04	1
+0.08	0.03+0.05	0.04+0.04	2
+0.09	0.04+0.05	0.04+0.05	2
+0.10	0.05+0.05	0.04+0.04+0.02	2

Assembly Instructions

STEP 1

Measure the DTD drill diameter between the measuring guide pad and the insert cutting edge. If a pre setter is not available, use a micrometer or caliper. For a precise drill diameter measurement, it is recommended to test drill a hole and measure the hole diameter.




STEP 2

Select the shim combinations according to the chart above to obtain the required hole diameter. Take into consideration that the actual diameter of the drilled hole tends to be slightly larger (usually +20 µm to +30 µm) than the drill's nominal diameter — i.e. add 20 µm-30 µm to the measured drill diameter in Step 1 before the final drill diameter.



STEP 3

Remove the guide pads.



STEP 4

Install the adjusting shims underneath the guide pads, respectively. Put the guide pads back on the tool.




STEP 5

Measure the drill diameter again to confirm that the required diameter is obtained on the DTD.



STEP 6


Drill a hole to confirm that the required hole diameter is achieved.



ISCARDEEPPDRILL

TS***

Drill Tubes - STS System - Inner
Single-Start Thread Connection



Designation	d Range	DCONMS	DCONWS	LSCWS	L min	L max
TS001 L=(0-2950)MM	8.00-8.99	7.10	6.00	16.00	0.0	2950.0
TS002 L=(0-2950)MM	9.00-9.99	8.30	7.20	16.00	0.0	2950.0
TS003 L=(0-2950)MM	10.00-10.99	9.00	7.60	16.00	0.0	2950.0
TS004 L=(0-2950)MM	11.00-11.99	10.00	8.60	16.00	0.0	2950.0
TS005 L=(0-2950)MM	12.00-13.49	11.00	9.10	16.00	0.0	2950.0
TS006 L=(0-2950)MM	13.50-14.79	12.00	10.80	16.00	0.0	2950.0

• These products are made to order on request • Indicate overall length (L) when ordering • Ordering example: TS004-L1500

Universal Marking for Deep Drilling Tools

single tube
system

1ST : single-start thread
2ST : double-start thread
4ST : four-start thread

S I 4ST D.425 d39 L1600 TBE -nPCS METRIC
S I 4ST D1.673 d1.535 L62.992 TBE -nPCS INCH

I: inner thread
O: outer thread


tube ØD

thread pilot Ød

BLANK: thread on one end only
TBE : same thread on at both ends

tube L

BLANK: single piece construction
-n pcs : n jointed tubes






ISCARDEEPDRILL

TS-I**

Drill Tubes - STS System - Inner
2 or 4- Start Thread Connection



Designation	d Range	DCONMS	DCONWS	LSCWS	L min	L max
TS-I01 L=(0-3700)MM ⁽¹⁾	12.60-13.60	11.00	9.60	22.00	0.0	3700.0
TS-I02 L=(0-3700)MM ⁽¹⁾	13.61-14.60	12.00	10.60	22.00	0.0	3700.0
TS-I03 L=(0-3700)MM ⁽¹⁾	14.61-15.59	13.00	11.60	22.00	0.0	3700.0
TS-I0 L=(0-3700)MM	15.60-16.70	14.00	12.60	21.00	0.0	3700.0
TS-I1 L=(0-3700)MM	16.71-17.70	15.00	13.60	21.00	0.0	3700.0
TS-I2 L=(0-3700)MM	17.71-18.90	16.00	14.50	22.00	0.0	3700.0
TS-I3 L=(0-3700)MM	18.91-20.00	17.00	15.50	22.00	0.0	3700.0
TS-I4 L=(0-3700)MM	20.01-21.80	18.00	16.00	27.50	0.0	3700.0
TS-I5 L=(0-3700)MM	21.81-24.10	20.00	18.00	30.00	0.0	3700.0
TS-I6 L=(0-3700)MM	24.11-26.40	22.00	19.50	30.00	0.0	3700.0
TS-I7 L=(0-3700)MM	26.41-28.70	24.00	21.00	30.00	0.0	3700.0
TS-I8 L=(0-3700)MM	28.71-31.00	26.00	23.50	33.00	0.0	3700.0
TS-I9 L=(0-3700)MM	31.01-33.30	28.00	25.50	33.00	0.0	3700.0
TS-I10 L=(0-3700)MM	33.31-36.20	30.00	28.00	33.00	0.0	3700.0
TS-I11 L=(0-3700)MM	36.21-39.60	33.00	30.00	40.00	0.0	3700.0
TS-I12 L=(0-3700)MM	39.61-43.00	36.00	33.00	40.00	0.0	3700.0
TS-I13 L=(0-3700)MM	43.01-47.00	39.00	36.00	40.00	0.0	3700.0
TS-I14 L=(0-3700)MM	47.01-51.70	43.00	39.00	40.00	0.0	3700.0
TS-I15 L=(0-3700)MM	51.71-56.20	47.00	43.00	44.00	0.0	3700.0
TS-I16 L=(0-3700)MM	56.21-60.60	51.00	47.00	44.00	0.0	3700.0
TS-I17 L=(0-3700)MM	60.61-64.99	56.00	51.00	44.00	0.0	3700.0
TS-I18 L=(0-3700)MM	65.00-66.99	56.00	52.00	75.00	0.0	3700.0
TS-I19 L=(0-3700)MM	67.00-72.99	62.00	58.00	75.00	0.0	3700.0
TS-I20 L=(0-3700)MM	73.00-79.99	68.00	63.00	75.00	0.0	3700.0
TS-I21 L=(0-3700)MM	80.00-86.99	75.00	70.00	97.00	0.0	3700.0
TS-I22 L=(0-3700)MM	87.00-99.99	82.00	77.00	97.00	0.0	3700.0
TS-I23 L=(0-3700)MM	100.00-111.99	94.00	89.00	97.00	0.0	3700.0
TS-I24 L=(0-3700)MM	112.00-123.99	106.00	101.00	118.00	0.0	3700.0
TS-I25 L=(0-3700)MM	124.00-135.99	118.00	113.00	118.00	0.0	3700.0
TS-I26 L=(0-3700)MM	136.00-147.99	130.00	125.00	118.00	0.0	3700.0
TS-I27 L=(0-3700)MM	148.00-159.99	142.00	137.00	139.00	0.0	3700.0
TS-I28 L=(0-3700)MM	160.00-171.99	154.00	149.00	139.00	0.0	3700.0
TS-I29 L=(0-3700)MM	172.00-183.99	166.00	161.00	139.00	0.0	3700.0
TS-I30 L=(0-3700)MM	184.00-195.99	178.00	173.00	144.00	0.0	3700.0
TS-I31 L=(0-3700)MM	196.00-207.99	190.00	185.00	144.00	0.0	3700.0
TS-I32 L=(0-3700)MM	208.00-219.99	202.00	197.00	144.00	0.0	3700.0
TS-I33 L=(0-3700)MM	220.00-231.99	214.00	208.00	164.00	0.0	3700.0
TS-I34 L=(0-3700)MM	232.00-243.99	226.00	220.00	164.00	0.0	3700.0



• These products are made to order on request • Indicate overall length (L) when ordering • Ordering example: TS-I12-L2000

⁽¹⁾ 2 Start thread connection

For tools, see pages: DSD-EF-FB (18) • DSD-EF-FT (9) • DSTR-EC (76)


Universal Marking for Deep Drilling Tools

single tube
system



TS-O**

Drill Tubes - STS System - Outer
Single-Start Thread Connection




Designation	d Range	DCONMS	DCONWS	LSCWS	L min	L max
TS-O0 L=(0-3700)MM	14.50-15.00	12.00	11.50	23.00	0.0	3700.0
TS-O1 L=(0-3700)MM	15.01-15.50	12.00	11.80	23.00	0.0	3700.0
TS-O2 L=(0-3700)MM	15.51-16.00	13.00	12.40	23.00	0.0	3700.0
TS-O3 L=(0-3700)MM	16.01-16.50	13.00	12.70	23.00	0.0	3700.0
TS-O4 L=(0-3700)MM	16.51-17.25	14.00	13.40	23.00	0.0	3700.0
TS-O5 L=(0-3700)MM	17.26-18.00	14.00	13.70	23.00	0.0	3700.0
TS-O6 L=(0-3700)MM	18.01-19.00	15.00	14.40	23.00	0.0	3700.0
TS-O7 L=(0-3700)MM	19.01-19.99	16.50	15.40	23.00	0.0	3700.0
TS-O8 L=(0-3700)MM	20.00-21.99	18.00	16.50	26.00	0.0	3700.0
TS-O9 L=(0-3700)MM	22.00-24.99	20.00	19.00	26.00	0.0	3700.0
TS-O10 L=(0-3700)MM	25.00-26.99	22.00	20.00	26.00	0.0	3700.0
TS-O11 L=(0-3700)MM	27.00-29.99	24.00	22.00	26.00	0.0	3700.0
TS-O12 L=(0-3700)MM	30.00-31.99	26.00	24.00	26.00	0.0	3700.0
TS-O13 L=(0-3700)MM	32.00-33.99	30.00	27.00	26.00	0.0	3700.0
TS-O14 L=(0-3700)MM	34.00-36.99	30.00	27.00	41.00	0.0	3700.0
TS-O15 L=(0-3700)MM	37.00-39.99	33.00	30.00	41.00	0.0	3700.0
TS-O16 L=(0-3700)MM	40.00-43.99	36.00	33.00	41.00	0.0	3700.0
TS-O17 L=(0-3700)MM	44.00-46.99	39.00	37.00	41.00	0.0	3700.0
TS-O18 L=(0-3700)MM	47.00-51.99	43.00	41.00	41.00	0.0	3700.0
TS-O19 L=(0-3700)MM	52.00-56.99	47.00	44.00	41.00	0.0	3700.0
TS-O20 L=(0-3700)MM	57.00-60.99	51.00	49.00	41.00	0.0	3700.0
TS-O21 L=(0-3700)MM	61.00-67.99	56.00	53.00	41.00	0.0	3700.0
TS-O22 L=(0-2950)MM	68.00-74.99	62.00	59.00	41.00	0.0	2950.0
TS-O23 L=(0-3700)MM	75.00-80.99	68.00	65.00	71.00	0.0	3700.0
TS-O24 L=(0-3700)MM	81.00-90.99	75.00	71.00	71.00	0.0	3700.0
TS-O25 L=(0-3700)MM	91.00-98.99	82.00	79.00	71.00	0.0	3700.0
TS-O26 L=(0-3700)MM	99.00-110.99	94.00	90.00	71.00	0.0	3700.0
TS-O27 L=(0-3700)MM	111.00-122.99	106.00	102.00	71.00	0.0	3700.0
TS-O28 L=(0-3700)MM	123.00-134.99	118.00	114.00	71.00	0.0	3700.0
TS-O29 L=(0-3700)MM	135.00-148.99	130.00	126.00	71.00	0.0	3700.0
TS-O30 L=(0-3700)MM	149.00-161.99	142.00	139.00	71.00	0.0	3700.0
TS-O31 L=(0-3700)MM	162.00-173.99	154.00	151.00	86.00	0.0	3700.0
TS-O32 L=(0-3700)MM	174.00-185.99	166.00	163.00	86.00	0.0	3700.0
TS-O33 L=(0-3700)MM	186.00-197.99	178.00	175.00	86.00	0.0	3700.0
TS-O34 L=(0-3700)MM	198.00-209.99	190.00	187.00	86.00	0.0	3700.0
TS-O35 L=(0-3700)MM	210.00-221.99	202.00	199.00	86.00	0.0	3700.0
TS-O36 L=(0-3700)MM	222.00-233.99	214.00	211.00	86.00	0.0	3700.0
TS-O37 L=(0-3700)MM	234.00-245.99	226.00	223.00	86.00	0.0	3700.0

• These products are made to order on request • Indicate overall length (L) when ordering • Ordering example: TS-036-L1100

For tools, see pages: DSD-IF-FB (19) • DSD-IF-FT (9) • DSTR-IC (78)

Universal Marking for Deep Drilling Tools






ISCARDEEPDRILL

TDO-I (D18.41-65.00)

Double Tube Drill System
with 4-Start Thread
Connection Outer Tubes






Designation	d Range	DCONMS	DCONWS	LSCWS	Int Tube	d	D5	L min	L max
TDO-I0 L=(0-3700)MM	18.41-20.00	18.00	16.00	27.50	TDI-N0	12.00	10.00	0.0	3700.0
TDO-I1 L=(0-3700)MM	20.01-21.80	19.50	18.00	30.00	TDI-N1	14.00	12.00	0.0	3700.0
TDO-I2 L=(0-3700)MM	21.81-24.10	21.50	19.50	30.00	TDI-N2	15.00	13.00	0.0	3700.0
TDO-I3 L=(0-3700)MM	24.11-26.40	23.50	21.00	30.00	TDI-N3	16.00	14.00	0.0	3700.0
TDO-I4 L=(0-3700)MM	26.41-28.70	26.00	23.50	33.00	TDI-N4	18.00	16.00	0.0	3700.0
TDO-I5 L=(0-3700)MM	28.71-31.00	28.00	25.50	33.00	TDI-N5	20.00	18.00	0.0	3700.0
TDO-I6 L=(0-3700)MM	31.01-33.30	30.50	28.00	33.00	TDI-N6	22.00	20.00	0.0	3700.0
TDO-I7 L=(0-3700)MM	33.31-36.20	33.00	30.00	40.00	TDI-N7	24.00	22.00	0.0	3700.0
TDO-I8 L=(0-3700)MM	36.21-39.60	35.50	33.00	40.00	TDI-N8	26.00	24.00	0.0	3700.0
TDO-I9 L=(0-3700)MM	39.61-43.00	39.00	36.00	40.00	TDI-N9	29.00	27.00	0.0	3700.0
TDO-I10 L=(0-3700)MM	43.01-47.00	42.50	39.00	40.00	TDI-N10	32.00	30.00	0.0	3700.0
TDO-I11 L=(0-3700)MM	47.01-51.70	46.50	43.00	44.00	TDI-N11	35.00	32.00	0.0	3700.0
TDO-I12 L=(0-3700)MM	51.71-56.20	51.00	47.00	44.00	TDI-N12	39.00	36.00	0.0	3700.0
TDO-I13 L=(0-3700)MM	56.21-65.00	55.50	51.00	44.00	TDI-N13	43.00	40.00	0.0	3700.0

- These products are made to order on request
- Please indicate overall length (L) when ordering
- Ordering example: TDO-I13-L1100
- For 18.41-65.00 diameter range, the inner tube should be 30 mm longer than the outer tube

For tools, see pages: DDC-EA (66) • DDC-EC (69)

Universal Marking for Deep Drilling Tools


double tube
system



ISCARDEEPDRILL

TDO-I (D65.00-171.99)

Double Tube Drill System
with 4-Start Thread
Connection Outer Tubes







Designation	d Range	DCONMS	DCONWS	LSCWS	Int Tube	d	L min	L max
TDO-I14 L=(0-3700)MM	65.00-66.99	56.00	52.00	75.00	TDI-N14	40.00	0.0	3700.0
TDO-I15 L=(0-2950)MM	67.00-72.99	62.00	58.00	75.00	TDI-N15	44.00	0.0	2950.0
TDO-I16 L=(0-3700)MM	73.00-79.99	68.00	63.00	75.00	TDI-N16	48.00	0.0	3700.0
TDO-I17 L=(0-3700)MM	80.00-86.99	75.00	70.00	97.00	TDI-N17	54.00	0.0	3700.0
TDO-I18 L=(0-3700)MM	87.00-99.99	82.00	77.00	97.00	TDI-N18	60.00	0.0	3700.0
TDO-I19 L=(0-3700)MM	100.00-111.99	94.00	89.00	97.00	TDI-N19	70.00	0.0	3700.0
TDO-I20 L=(0-3700)MM	112.00-123.99	106.00	101.00	118.00	TDI-N20	80.00	0.0	3700.0
TDO-I21 L=(0-3700)MM	124.00-135.99	118.00	113.00	118.00	TDI-N21	80.00	0.0	3700.0
TDO-I22 L=(0-3700)MM	136.00-147.99	130.00	125.00	118.00	TDI-N22	90.00	0.0	3700.0
TDO-I23 L=(0-3700)MM	148.00-159.99	142.00	137.00	139.00	TDI-N23	100.00	0.0	3700.0
TDO-I24 L=(0-3700)MM	160.00-171.99	154.00	149.00	139.00	TDI-N24	120.00	0.0	3700.0

- These products are made to order on request • Indicate overall length (L) when ordering • Ordering example: TDO-I18-L1150
 - For 65.00-123.99 diameter range, the inner tube should be 190 mm longer than the outer tube
 - For 124.00-183.99 diameter range, the inner tube should be 220 mm longer than the outer tube
- For tools, see pages: DDC-EC (69) • DDD-EC (29)

Universal Marking for Deep Drilling Tools

double tube
system



Machining Recommendations

Ground Brazed Solid Drill Heads DSD-E0, DSD-E1, DSD-E2/E3, DDD-E3						
ISO	Material		Condition	Tensile Strength [N/mm²]	Hardness HB	Material Group No. ⁽¹⁾
P	non-alloy steel and cast steel, free cutting steel	<0.25% C	annealed	420	125	1
		≥0.25% C	annealed	650	190	2
		<0.55% C	quenched and tempered	850	250	3
		≥0.55% C	annealed	750	220	4
			quenched and tempered	1000	300	5
	low alloy and cast steel (less than 5% of alloying elements)	annealed		600	200	6
		quenched and tempered	930	275	7	
			1000	300	8	
			1200	350	9	
	high alloyed steel, cast steel and tool steel	annealed		680	200	10
		quenched and tempered		1100	325	11
	stainless steel and cast steel	ferritic/martensitic		680	200	12
		martensitic		820	240	13
M	stainless steel and cast steel		austenitic, duplex	600	180	14
K	grey cast iron (GG)		ferritic/pearlitic		180	15
			pearlitic/martensitic		260	16
	nodular cast iron (GGG)		ferritic		160	17
			pearlitic		250	18
	malleable cast iron		ferritic		130	19
			pearlitic		230	20
N	aluminum-wrought alloys		not hardenable		60	21
			hardenable		100	22
	aluminum-cast alloys	≤12% Si	not hardenable		75	23
			hardenable		90	24
		>12% Si	high temperature		130	25
	copper alloys	>1% Pb	free cutting		110	26
		brass		90	27	
			electrolitic copper		100	28
	non-metallic	duroplastics, fiber plastics				29
hard rubber				30		
S	high temp. alloys	Fe based	annealed		200	31
			hardened		280	32
		Ni or Co based	annealed		250	33
			hardened		350	34
			cast		320	35
	titanium alloys	pure		400		36
		alpha+beta alloys hardened		1050		37
H	hardened steel		hardened		55 HRC	38
			hardened		60 HRC	39
	chilled cast iron		cast		400	40
	cast iron		hardened		55 HRC	41

⁽¹⁾ Based on ISO 513 and VDI 3323 standards

Ground Brazed Solid Drill Heads DSD-E0, DSD-E1, DSD-E2/E3, DDD-E3					
Dia. Range	8.00-20.00	12.60-20.00	20.01-31.00	31.01-43.00	43.01-65.00
Drill Type	DSD-E0/E1	DSD-E2/E3, DDD-E3			
V _c (m/min)	Feed Rate f (mm/rev)				
70-120	0.05-0.13	0.08-0.15	0.10-0.17	0.13-0.20	0.16-0.30
70-120	0.05-0.13	0.08-0.15	0.10-0.17	0.13-0.20	0.16-0.30
40-70	0.05-0.13	0.08-0.15	0.10-0.17	0.13-0.20	0.16-0.30
70-120	0.05-0.13	0.08-0.15	0.10-0.17	0.13-0.20	0.16-0.30
55-100	0.05-0.10	0.08-0.12	0.10-0.15	0.13-0.17	0.15-0.28
70-100	0.05-0.13	0.08-0.15	0.10-0.17	0.13-0.20	0.16-0.30
55-100	0.05-0.10	0.08-0.12	0.10-0.15	0.13-0.17	0.15-0.28
55-100	0.05-0.10	0.08-0.12	0.10-0.15	0.13-0.17	0.15-0.28
55-100	0.05-0.10	0.08-0.12	0.10-0.15	0.13-0.17	0.15-0.28
50-85	0.05-0.13	0.08-0.15	0.10-0.17	0.13-0.20	0.16-0.30
55-100	0.05-0.10	0.08-0.12	0.10-0.15	0.13-0.17	0.15-0.28
60-100	0.05-0.13	0.08-0.15	0.10-0.28	0.13-0.30	0.16-0.35
60-100	0.05-0.13	0.08-0.15	0.10-0.28	0.13-0.30	0.16-0.35
60-100	0.05-0.12	0.05-0.12	0.08-0.25	0.10-0.28	0.15-0.33
80-100	0.05-0.13	0.08-0.15	0.10-0.17	0.13-0.20	0.16-0.30
80-100	0.05-0.13	0.08-0.15	0.10-0.17	0.13-0.20	0.16-0.30
60-100	0.05-0.13	0.06-0.13	0.08-0.18	0.10-0.20	0.15-0.25
60-100	0.05-0.13	0.06-0.13	0.08-0.18	0.10-0.20	0.15-0.25
50-100	0.05-0.13	0.06-0.13	0.08-0.18	0.10-0.20	0.15-0.25
50-100	0.05-0.13	0.06-0.13	0.08-0.18	0.10-0.20	0.15-0.25
65-130	0.05-0.13	0.08-0.15	0.10-0.20	0.15-0.25	0.16-0.30
65-100	0.05-0.13	0.08-0.15	0.10-0.20	0.15-0.25	0.16-0.30
65-130	0.05-0.13	0.08-0.15	0.10-0.20	0.15-0.25	0.16-0.30
65-130	0.05-0.13	0.08-0.15	0.10-0.20	0.15-0.25	0.16-0.30
65-130	0.05-0.13	0.08-0.15	0.10-0.20	0.15-0.25	0.16-0.30
65-130	0.05-0.13	0.08-0.15	0.10-0.20	0.15-0.25	0.16-0.30
65-130	0.05-0.13	0.08-0.15	0.10-0.20	0.15-0.25	0.16-0.30
65-130	0.05-0.13	0.08-0.15	0.10-0.20	0.15-0.25	0.16-0.30
65-130	0.05-0.13	0.08-0.15	0.10-0.20	0.15-0.25	0.16-0.30
10-50	0.05-0.12	0.06-0.12	0.08-0.15	0.12-0.18	0.15-0.25
10-50	0.05-0.12	0.06-0.12	0.08-0.15	0.12-0.18	0.15-0.25
10-50	0.05-0.12	0.06-0.12	0.08-0.15	0.12-0.18	0.15-0.25
10-50	0.05-0.12	0.06-0.12	0.08-0.15	0.12-0.18	0.15-0.25
10-50	0.05-0.12	0.06-0.12	0.08-0.15	0.12-0.18	0.15-0.25
30-50	0.05-0.10	0.05-0.10	0.08-0.12	0.10-0.15	0.12-0.20
30-50	0.05-0.10	0.05-0.10	0.08-0.12	0.10-0.15	0.12-0.20
30-50	0.05-0.10	0.05-0.10	0.08-0.12	0.10-0.15	0.12-0.20
30-50	0.05-0.10	0.05-0.10	0.08-0.12	0.10-0.15	0.12-0.20
30-50	0.05-0.10	0.05-0.10	0.08-0.12	0.10-0.15	0.12-0.20
30-50	0.05-0.10	0.05-0.10	0.08-0.12	0.10-0.15	0.12-0.20



Machining Recommendations

Indexable Drill Heads DSD-EC, DDD-EC, DSD-IC								
ISO	Material	Condition	Tensile Strength [N/mm ²]	Material Group No. ⁽¹⁾	Hardness HB	Chipbreaker		
						First Choice	Fracture	Wear
P	non-alloy steel and cast steel, free cutting steel	<0.25% C annealed	420	1	125	G IC908	BG IC806	B IC9025
		≥0.25% C annealed	650	2	190			
		<0.55% C quenched and tempered	850	3	250			
		annealed	750	4	220			
		quenched and tempered	1000	5	300			
	low alloy and cast steel (less than 5% of alloying elements)	annealed	600	6	200	G IC908	BG IC806	B IC9025
		quenched and tempered	930	7	275			
			1000	8	300			
			1200	9	350			
	high alloyed steel, cast steel and tool steel	annealed	680	10	200	G IC908	BG IC806	B IC9025
		quenched and tempered	1100	11	325	IC908	IC806	IC9025
	stainless steel and cast steel	ferritic/martensitic	680	12	200	G IC908	BG IC806	B IC9025
		martensitic	820	13	240	IC908	IC806	IC9025
M	stainless steel and cast steel	austenitic, duplex	600	14	180	G IC806	B IC908	B IC9025
K	grey cast iron (GG)	ferritic/pearlitic		15	180	G IC908	G IC806	B IC9025
		pearlitic/martensitic		16	260			
	nodular cast iron (GGG)	ferritic		17	160			
		pearlitic		18	250			
	malleable cast iron	ferritic		19	130			
		pearlitic		20	230			
N	aluminum-wrought alloys	not hardenable		21	60	G IC908	G IC806	B IC9025
		hardenable		22	100			
	aluminum- cast alloys	≤12% Si not hardenable		23	75			
		hardenable		24	90			
		>12% Si high temperature		25	130			
	copper alloys	>1% Pb free cutting		26	110			
		brass		27	90			
		electrolitic copper		28	100			
	non-metallic	duroplastics, fiber plastics		29				
		hard rubber		30				
S	high temp. alloys	Fe based annealed		31	200	B IC806	B IC908	B IC9025
		hardened		32	280			
		Ni or Co annealed		33	250			
		hardened		34	350			
		cast		35	320			
	titanium alloys	pure	400	36				
		alpha+beta alloys hardened	1050	37				
H	hardened steel	hardened 55 HRC		38		B IC806	B IC908	B IC908
		hardened 60 HRC		39				
	chilled cast iron	cast		40	400			
	cast iron	hardened 55 HRC		41				

⁽¹⁾ Based on ISO 513 and VDI 3323 standards

Indexable Drill Heads DSD-EC, DDD-EC, DSD-IC					
Dia. Range	38.00-39.99	40.00-51.99	52.00-63.99	64.00-84.99	85.00-293.00
V _c (m/min)	Feed Rate f (mm/rev)				
60-120	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
60-120	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
60-120	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
60-120	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
60-120	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
60-100	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
60-100	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
50-100	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
50-100	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
60-120	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
60-120	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
60-110	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
60-110	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
60-110	0.08-0.15	0.10-0.20	0.13-0.23	0.15-0.25	0.18-0.30
80-140	0.20-0.30	0.20-0.30	0.24-0.32	0.24-0.32	0.25-0.40
80-140	0.20-0.30	0.20-0.30	0.24-0.32	0.24-0.32	0.25-0.40
80-140	0.20-0.30	0.20-0.30	0.24-0.32	0.24-0.32	0.25-0.40
80-140	0.20-0.30	0.20-0.30	0.24-0.32	0.24-0.32	0.25-0.40
80-140	0.20-0.30	0.20-0.30	0.24-0.32	0.24-0.32	0.25-0.40
80-140	0.20-0.30	0.20-0.30	0.24-0.32	0.24-0.32	0.25-0.40
100-200	0.08-0.20	0.10-0.25	0.13-0.28	0.15-0.30	0.18-0.33
100-200	0.08-0.20	0.10-0.25	0.13-0.28	0.15-0.30	0.18-0.33
100-200	0.08-0.20	0.10-0.25	0.13-0.28	0.15-0.30	0.18-0.33
100-200	0.08-0.20	0.10-0.25	0.13-0.28	0.15-0.30	0.18-0.33
100-200	0.08-0.20	0.10-0.25	0.13-0.28	0.15-0.30	0.18-0.33
100-200	0.08-0.20	0.10-0.25	0.13-0.28	0.15-0.30	0.18-0.33
100-200	0.08-0.20	0.10-0.25	0.13-0.28	0.15-0.30	0.18-0.33
100-200	0.08-0.20	0.10-0.25	0.13-0.28	0.15-0.30	0.18-0.33
20-65	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
20-65	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
20-65	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
30-100	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
30-100	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
30-100	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
30-100	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.18-0.28
30-80	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.15-0.28
30-80	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.15-0.28
30-80	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.15-0.28
30-80	0.06-0.13	0.08-0.18	0.13-0.23	0.13-0.23	0.15-0.28

Machining Recommendations

Indexable Counterboring Heads DSC-EA, DSC-EC, DSC-IA, DSC-IC, DDC-EA / Trepanning Heads					
ISO	Material	Condition	Tensile Strength [N/mm ²]	Hardness HB	Material Group No. ⁽¹⁾
P	non-alloy steel and cast steel, free cutting steel	<0.25% C annealed	420	125	1
		≥0.25% C annealed	650	190	2
		<0.55% C quenched and tempered	850	250	3
		≥0.55% C annealed	750	220	4
		≥0.55% C quenched and tempered	1000	300	5
	low alloy and cast steel (less than 5% of alloying elements)	annealed	600	200	6
		quenched and tempered	930	275	7
			1000	300	8
			1200	350	9
	high alloyed steel, cast steel and tool steel	annealed	680	200	10
		quenched and tempered	1100	325	11
	stainless steel and cast steel	ferritic/martensitic	680	200	12
		martensitic	820	240	13
M	stainless steel and cast steel	austenitic, duplex	600	180	14
K	grey cast iron (GG)	ferritic/pearlitic		180	15
		pearlitic/martensitic		260	16
	nodular cast iron (GGG)	ferritic		160	17
		pearlitic		250	18
	malleable cast iron	ferritic		130	19
		pearlitic		230	20
N	aluminum-wrought alloys	not hardenable		60	21
		hardenable		100	22
	aluminum-cast alloys	≤12% Si not hardenable		75	23
		hardenable		90	24
		>12% Si high temperature		130	25
	copper alloys	>1% Pb free cutting		110	26
		brass		90	27
		electrolitic copper		100	28
	non-metallic	duroplastics, fiber plastics			29
		hard rubber			30
S	high temp. alloys	Fe based annealed		200	31
		hardened		280	32
		Ni or Co based annealed		250	33
		hardened		350	34
		cast		320	35
	titanium alloys	pure	400		36
		alpha+beta alloys hardened	1050		37
H	hardened steel	hardened		55 HRC	38
		hardened		60 HRC	39
	chilled cast iron	cast		400	40
	cast iron	hardened		55 HRC	41

(1) Based on ISO 513 and VDI 3323 standards


Indexable Counterboring Heads DSC-EA, DSC-EC, DSC-IA, DSC-IC, DDC-EA				Trepanning Heads	
Width of Cut (mm)	1-3	3-8	8-23	Dia. Range	120-400
V _c (m/min)	Feed Rate f (mm/rev)			V _c (m/min)	Feed Rate f (mm/rev)
60-140	0.10-0.30	0.15-0.30	0.10-0.30	80-100	0.12-0.30
60-120	0.10-0.30	0.15-0.30	0.10-0.30	80-100	0.12-0.30
60-120	0.10-0.30	0.15-0.30	0.10-0.30	80-100	0.12-0.30
50-100	0.10-0.30	0.15-0.30	0.10-0.30	80-100	0.12-0.30
50-100	0.10-0.30	0.15-0.30	0.10-0.30	80-100	0.12-0.30
60-130	0.10-0.30	0.15-0.30	0.10-0.30	70-100	0.12-0.30
60-120	0.10-0.30	0.15-0.30	0.10-0.30	70-100	0.12-0.30
60-100	0.10-0.30	0.15-0.30	0.10-0.30	60-100	0.12-0.30
60-100	0.10-0.30	0.15-0.30	0.10-0.30	60-100	0.12-0.30
50-100	0.10-0.30	0.15-0.30	0.10-0.30	70-100	0.12-0.30
60-100	0.10-0.30	0.15-0.30	0.10-0.30	60-100	0.12-0.30
60-100	0.10-0.30	0.15-0.30	0.10-0.30	50-90	0.12-0.30
60-100	0.10-0.30	0.15-0.30	0.10-0.30	50-90	0.12-0.30
60-100	0.10-0.30	0.15-0.30	0.10-0.30	50-90	0.12-0.30
60-120	0.10-0.30	0.15-0.30	0.10-0.30	80-100	0.12-0.30
50-120	0.10-0.30	0.15-0.30	0.10-0.30	60-100	0.12-0.30
60-120	0.10-0.30	0.15-0.30	0.10-0.30	50-100	0.12-0.30
60-120	0.10-0.30	0.15-0.30	0.10-0.30	50-100	0.12-0.30
60-120	0.10-0.30	0.15-0.30	0.10-0.30	80-100	0.12-0.30
60-120	0.10-0.30	0.15-0.30	0.10-0.30	80-100	0.12-0.30
70-200	0.10-0.40	0.15-0.30	0.10-0.30	65-130	0.10-0.30
60-200	0.10-0.40	0.10-0.40	0.10-0.40	65-130	0.10-0.30
60-200	0.10-0.40	0.10-0.40	0.10-0.40	65-130	0.10-0.30
60-200	0.10-0.40	0.10-0.40	0.10-0.40	65-130	0.10-0.30
60-200	0.10-0.40	0.10-0.40	0.10-0.40	65-130	0.10-0.30
60-200	0.10-0.40	0.10-0.40	0.10-0.40	65-130	0.10-0.30
60-200	0.10-0.40	0.10-0.40	0.10-0.40	65-130	0.10-0.30
60-200	0.10-0.40	0.10-0.40	0.10-0.40	65-130	0.10-0.30
40-80	0.10-0.30	0.15-0.30	0.10-0.30	20-65	0.10-0.20
40-80	0.10-0.30	0.15-0.30	0.10-0.30	20-65	0.10-0.20
40-80	0.10-0.30	0.15-0.30	0.10-0.30	20-65	0.10-0.20
60-100	0.10-0.30	0.15-0.30	0.10-0.30	30-100	0.10-0.20
60-100	0.10-0.30	0.15-0.30	0.10-0.30	30-100	0.10-0.20
50-100	0.10-0.30	0.15-0.30	0.10-0.30	70-100	0.12-0.30
50-100	0.10-0.30	0.15-0.30	0.10-0.30	70-100	0.12-0.30
60-100	0.10-0.30	0.15-0.30	0.10-0.30	30-100	0.10-0.20
60-100	0.10-0.30	0.15-0.30	0.10-0.30	30-100	0.10-0.20
60-100	0.10-0.30	0.15-0.30	0.10-0.30	30-100	0.10-0.20
60-100	0.10-0.30	0.15-0.30	0.10-0.30	30-100	0.10-0.20



Technical Information - Drill Setup


Rotating Drill

- Can be applied on symmetrical and non-symmetrical workpieces
- Drill to bushing center misalignment should not exceed 0.02 mm



Stationary Drill



- Applied on symmetrical workpieces
- Improved hole straightness and bushing wear
- Drill to bushing center misalignment should not exceed 0.02 mm




Drill Bushing and Workpiece Tolerance Relative Positioning

Pre-Drilled Hole


A large pre-drilled hole (larger than D-A) ensures precise hole size and center location.




Recommended Coolant Pressure and Volume ≤50 mm




Recommended Coolant Pressure and Volume >50 mm



Machine Power



Machine Thrust Force



Technical Information - NC Cycle






Use the NC cycle as instructed below to optimize tool performance more safely.

	1. Start NC operation cycle
	2. Oil pressure head moves until it touches the workpiece ① Set the starting point of the main axis of the tool so that the guide pad remains inside the guide bush when the oil pressure head moves forward
	3. Move tool workpiece ② Move the tool 3 to 5 mm from the edge of the workpiece If the available NC machine can support this approach, the operation process may start from this point
	4. Start cutting - Start coolant supply - Start rotating (tool / workpiece / tool & workpiece) - Start feeding
	5. Stop cutting - Stop feeding - Stop rotating (tool / workpiece / tool & workpiece) - Stop coolant supply ③ Stop rotation when the outer tip is at the edge of the workpiece
	6. Tool main axis back to starting point
	7. Oil pressure head back to starting point



Technical Information - Notes for Guide Bushing Installation

Many of the problems in BTA drilling are caused by incorrect use of the guide bushing. The shape, type and tolerance greatly affect cutting accuracy and tool life. Please note the following when using one in your application.



Tool Diameter D (mm)	G6 Tolerance (mm)
8.00 - 10.00	+0.005 ~ +0.014
10.01 - 18.00	+0.006 ~ +0.017
18.01 - 30.00	+0.007 ~ +0.020
30.01 - 50.00	+0.009 ~ +0.025
50.01 - 80.00	+0.010 ~ +0.029
80.01 - 120.00	+0.012 ~ +0.034
120.01 - 180.00	+0.014 ~ +0.039
180.01 - 245.99	+0.015 ~ +0.044

Deep Hole Drilling Systems

Problem	Possible Cause	Solution
The drill breaks or insert chips	- chip evacuation problems - center misalignment of drill to workpiece	- check that the coolant passages are clear and that the venturi slots are not damaged - check center alignment of drill to workpiece - check workpiece and drill clamping rigidity
Poor surface finish	- workpiece or drill clamping rigidity problem - inadequate coolant oil - cutting speed too low	- improve workpiece or drill clamping - check the coolant oil and replace if necessary - increase the cutting speed
Excessive leakage of the coolant	- chips block the fluid passages - the drill was incorrectly assembled, or the venturi slots of the internal tube are located in the wrong direction	- clear the chips - check all connections and the direction of the internal tube
Insufficient coolant flow at the cutting zone, despite correct fluid supply	- chips block the fluid passages - worn bushing or sealing device - venturi slots are too wide (worn) - internal tube shorter than the external tube	- clear the chips - check the bushing and seal and replace if necessary - replace the internal tube - replace the internal tube to one with a correct length
Chips jam in the front end of the drill	insufficient coolant flow	adjust the fluid flow by raising the pressure; check the filter and fluid quality

Connection Adapters

Various kinds of rotating and non-rotating drill connectors are available upon request.



Oil Pressure Heads

Oil pressure heads are available on request.



Special Heads

Special form heads for trepanning or any other special contours can be produced on request.



Coolant

Successful deep hole drilling is achieved by an optimal combination of the tool, the machine and the coolant. Coolant plays an essential role in achieving secure and cost-efficient deep hole drilling operations. Therefore, it is very important to choose the correct type of coolant and use it appropriately.

Coolant

Coolant plays an essential role in lubricating tools, cooling cutting edges, chips and guide pads, as well as evacuating chips when drilling. It also improves tool life, surface finish and cutting accuracy when continuously supplied during the machining process.

1 Lubrication



Lubrication of cutting edges and guide pads is necessary in deep hole drilling. For efficient lubrication, it is recommended to use EP (Extreme Pressure) additives which contain sulfur or chlorine.

2 Temperature reduction

The ability to cool down the cutting edge and chips depends on such characteristics as thermal conductivity and relative heat. Coolant with good cooling ability increases tool life, but water-soluble coolant is not preferred in deep hole drilling because it reduces effectiveness. If water-soluble coolant is used, the recommended concentration is 10% (dilution rate 1/10) or more.

3 Chip evacuation

Coolant helps push chips through the back end of the boring bar (for STS) or inner tube (for DTS) until the chips are separated from the workpiece in general cutting conditions. The flow and the pressure of coolant are also important in order to control chip evacuation.



Coolant Unit

A coolant unit is also important to obtain the best effect from the coolant.

1 Coolant pressure and volume should be fixed and continuous.

An ideal coolant unit sets the coolant pressure valves and volume while monitoring the condition with gauges. A system that can detect trapped chips by a pressure gauge and the screw pumps with an inverter controller are both recommended.

2 Coolant temperature should be maintained

Coolant is heated by factors, such as:


- cutting edge
- friction on guide pad
- contact time of heated chips and coolant
- pump

Maintaining coolant temperature is important to keeping stable cutting conditions, chip formation and cutting accuracy. The temperature should be lower than 40°C (100°F) for EP additives to provide sufficient lubrication. Therefore, the coolant temperature should be kept between 30 - 40°C (90 - 100°F) throughout the cutting operation.

3 Filtering

Unwanted particles are contained in coolant after the cutting operations, thus filtration is necessary to remove them. The filter size should be selected carefully to catch particles but not EP additives. Filter size depends on the coolant, but around 10 - 20 µm is generally suggested. For iron-based workpieces, a magnetic separator is helpful as it decreases the frequency of filter maintenance.

Flow Chart of Coolant in Deep Hole Drilling



Requested Information Form for Deep Hole Drill Design

Company name _____	Telephone no. _____
Address _____	Date _____
Contact person _____	Customer no. _____

Workpiece

Product name: _____ Hole diameter: _____

Hole depth: _____ No. of holes: _____ Tolerance (of hole): _____

Surface finish (Rz, Ra...): _____ Deviation (mm/100): _____ Straightness (mm/100): _____

Material

Material (DIN, AISI, JIS...): _____

Hardness (HB, HS, HRC...): _____

Condition: ☐ Quenched ☐ Tempered ☐ Cast ☐ Annealed

☐ Other _____

Machine

Machine supplier name: _____

Machine type/model: ☐ NC lathe ☐ Machining center ☐ Other _____

Rigidity: ☐ Good ☐ Normal ☐ Poor

Spindle power (kW): _____

Tool and/or workpiece rotation (TR/WR):

☐ Tool and workpiece ☐ Rotating workpiece (WR) ☐ Rotating tool (TR)

Type of Coolant

Water based: ☐ Soluble ☐ Emulsion _____%

Oil based: ☐ Coolant Pressure (bar): _____ Coolant Volume (L/min): _____

Tool Drill Head

Drill diameter: _____ (mm/inch)

Thread: ☐ Inner ☐ Outer ☐ Brazed

Indexable: ☐ Adjustable ☐ Direct mount Coating: ☐ Coated ☐ Uncoated

☐ Solid drilling ☐ Counterboring

Pre-drilled hole size: _____ (mm/inch)

Bottom finishing: ☐ Full ball R ☐ Flat bottom R ☐ Corner R ☐ Other _____

Trepanning: ☐ Y ☐ N

Tube outer diameter: _____ (mm/inch) Core size diameter: _____ (mm/inch)

Please fill in and return to your **ISCAR** representative.



Requested Information Form for Deep Hole Drill Design (Continued)

Tube

Outside diameter: _____ (mm/inch) Total Length: _____ (mm/inch)

Internal Thread: _____

External Thread: 4 ☐ Starts 2 ☐ Starts 1 ☐ Starts

Tube Thread: 1 ☐ End ☐ Both ends

Inner Tube Length: _____ (mm/inch)

Inner Tube Slit: 1 ☐ End ☐ Both ends

Drilling System & Boring Conditions

☐ Single Tube System: ☐ Blind Hole Drilling ☐ Double Tube System

☐ Cross Hole Drilling: ☐ Through Hole Drilling

Please Sketch Your Drilling Application

General Production Information

Quantity of parts per year: _____

Grade, tool life, etc.: _____

Performance expectation: V_c = _____ m/min N = _____ RPM F = _____ mm/min f = _____ mm/rev

Cutting data: _____

Description of Present System in Use:

Please fill in and return to your **ISCAR** representative.

GUNDRILLS






Contents

TRI-DEEP	105
GD-DH, GD-DHL, GDH-MKT	105
SUMOGUN	119
MNSNT	119
Solid Carbide Gundrills	125

GD-DH (10.00-11.50)

Gundrills Carrying Indexable Inserts with Single Chip Splitting Cutting Edge and a Wiper for High Hole Surface Quality



Designation	DC	LU	LF	PL	DCONMS	BD	LS	MILD ⁽¹⁾
GD-DH 10.00-15D-M20-06	10.00	159.30	184.50	1.800	20.00	9.60	50.0	ZSGT 06
GD-DH 10.00-20D-M20-06	10.00	211.80	237.00	1.800	20.00	9.60	50.0	ZSGT 06
GD-DH 10.00-25D-M20-06	10.00	264.30	289.50	1.800	20.00	9.60	50.0	ZSGT 06
GD-DH 10.50-15D-M20-06	10.50	166.80	193.00	1.800	20.00	10.00	50.0	ZSGT 06
GD-DH 10.50-20D-M20-06	10.50	221.80	248.00	1.800	20.00	10.00	50.0	ZSGT 06
GD-DH 10.50-25D-M20-06	10.50	276.80	303.00	1.800	20.00	10.00	50.0	ZSGT 06
GD-DH 11.00-15D-M20-06	11.00	181.80	209.00	1.800	20.00	10.60	50.0	ZSGT 06
GD-DH 11.00-20D-M20-06	11.00	241.80	269.00	1.800	20.00	10.60	50.0	ZSGT 06
GD-DH 11.00-25D-M20-06	11.00	301.80	329.00	1.800	20.00	10.60	50.0	ZSGT 06
GD-DH 11.50-15D-M20-06	11.50	181.80	209.00	1.800	20.00	11.10	50.0	ZSGT 06
GD-DH 11.50-20D-M20-06	11.50	241.80	269.00	1.800	20.00	11.10	50.0	ZSGT 06
GD-DH 11.50-25D-M20-06	11.50	301.80	329.00	1.800	20.00	11.10	50.0	ZSGT 06

- Note: Gundrills supplied with up to 1650 mm length on request.
 - Inserts and guide pads to be ordered separately (not included with the tools).
 - For user guide and cutting conditions, see pages 113-118
 - Preventative measures: Do NOT operate the deep hole drill at full speed before engaging the guide hole. Enter the guide hole slowly at a speed of 50 - 100 rpm.
- ⁽¹⁾ Master insert identification

For inserts, see pages: ZSGT (111)

Spare Parts



Tool Diameter		Insert			Guide Pad		
Min	Max	Insert	Screw	Wrench	GP X 2pcs	Screw X 2pcs	Wrench
10.00	10.99	ZSGT 060204R-DT	SR-M2.5X0.35L3.8	T-7/5	GPS-04-16-045-DC	CSTB-2	T-6/5
11.00	11.80				GPS-04-16-050-DC		
11.81	11.99	LOGT 060204R-DT	SR 10503833L040				


Recommended tightening torque: SR-M2.5X0.35L3.8=1.1 Nm, SR 10503833L040=1.3 Nm, CSTB-2=0.6 Nm





GD-DH (12-13.5)

Gundrills Carrying Indexable Inserts with 2 Chip Splitting Cutting Edges and a Wiper for High Hole Surface Quality




Designation	DC	LF	PL	LU	DCONMS	BD	LS	Insert
GD-DH 12.00-M20-15D-06	12.00	225.00	1.800	196.80	20.00	11.50	50.0	LOGT 06..
GD-DH 12.00-M20-20D-06	12.00	280.00	1.800	251.80	20.00	11.50	50.0	LOGT 06..
GD-DH 12.00-M20-25D-06	12.00	343.00	1.800	314.80	20.00	11.50	50.0	LOGT 06..
GD-DH 12.50-M20-15D-06	12.50	226.00	1.800	196.80	20.00	12.00	50.0	LOGT 06..
GD-DH 12.50-M20-20D-06	12.50	291.00	1.800	261.80	20.00	12.00	50.0	LOGT 06..
GD-DH 12.50-M20-25D-06	12.50	356.00	1.800	326.80	20.00	12.00	50.0	LOGT 06..
GD-DH 13.00-M25-15D-06	13.00	238.00	1.800	204.80	25.00	12.50	56.0	LOGT 06..
GD-DH 13.00-M25-20D-06	13.00	305.00	1.800	271.80	25.00	12.50	56.0	LOGT 06..
GD-DH 13.00-M25-25D-06	13.00	373.00	1.800	339.80	25.00	12.50	56.0	LOGT 06..
GD-DH 13.50-M25-15D-06	13.50	245.00	1.800	211.80	25.00	13.00	56.0	LOGT 06..
GD-DH 13.50-M25-20D-06	13.50	315.00	1.800	281.80	25.00	13.00	56.0	LOGT 06..

- Note: Gundrills can be supplied with up to 2400 mm length on request.
- Inserts and guide pads to be ordered separately (not included with the tools).
- For user guide and cutting conditions, see pages 113-115, 117-118
- Preventative measures: Do NOT operate the deep hole drill at full speed before engaging the guide hole. Enter the guide hole slowly at a speed of 50 - 100 rpm.

For inserts, see pages: LOGT (111)

GPS

Deep Drilling Solid Carbide Guide Pads




Designation	Dimensions				Tough ↔ Hard	
	OAW	RE	OAL	OAH	IC928	IC908
GPS-04-16-055-DC	4.0	5.50	16.00	2.0	●	●

Spare Parts

Diameter Range	Insert	Insert Clamping Screw	Key	N-m	Solid Carbide Guide Pad	Guide Pad Clamping Screw	Key	N-m
12.00-13.99	LOGT 060204R-DT	SR 10503833L040	T-7F	0.9	GPS-04-16-055-DC	TS 20043/HG-P M2X0.4	Wrench IP-6/5	0.65

Universal Marking for Deep Drilling Tools



***** [Lot no.]


Example:

Metric: D14.00 L/D15 d25X56M

Inch: D0.551 L/D15 d0.984X2.205M

GD-DHL (12-13)

Gundrills Carrying Indexable Inserts with 2 Chip Splitting Cutting Edges and a Wiper for High Hole Surface Quality



Designation	DC	LU	OAL	DCONMS	BD	PL	LS	MID ⁽¹⁾
GD-DHL 12.00X800-U03	12.00	713.80	801.80	19.05	11.50	1.80	70.0	LOGT 060204R-DT
GD-DHL 12.00X800-22	12.00	733.80	801.80	20.00	11.50	1.80	50.0	LOGT 060204R-DT
GD-DHL 12.00X800-34	12.00	733.80	801.80	20.00	11.50	1.80	50.0	LOGT 060204R-DT
GD-DHL 12.00X1000-U03	12.00	913.80	1001.80	19.05	11.50	1.80	70.0	LOGT 060204R-DT
GD-DHL 12.00X1000-22	12.00	933.80	1001.80	20.00	11.50	1.80	50.0	LOGT 060204R-DT
GD-DHL 12.00X1000-34	12.00	933.80	1001.80	20.00	11.50	1.80	50.0	LOGT 060204R-DT
GD-DHL 12.00X1650-U03	12.00	1563.80	1651.80	19.05	11.50	1.80	70.0	LOGT 060204R-DT
GD-DHL 12.00X1650-22	12.00	1583.80	1651.80	20.00	11.50	1.80	50.0	LOGT 060204R-DT
GD-DHL 12.00X1650-34	12.00	1583.80	1651.80	20.00	11.50	1.80	50.0	LOGT 060204R-DT
GD-DHL 13.00X800-U04	13.00	711.80	801.80	25.40	12.50	1.80	70.0	LOGT 060204R-DT
GD-DHL 13.00X800-23	13.00	725.80	801.80	25.00	12.50	1.80	56.0	LOGT 060204R-DT
GD-DHL 13.00X800-35	13.00	725.80	801.80	25.00	12.50	1.80	56.0	LOGT 060204R-DT
GD-DHL 13.00X1000-U04	13.00	911.80	1001.80	25.40	12.50	1.80	70.0	LOGT 060204R-DT
GD-DHL 13.00X1000-23	13.00	925.80	1001.80	25.00	12.50	1.80	56.0	LOGT 060204R-DT
GD-DHL 13.00X1000-35	13.00	925.80	1001.80	25.00	12.50	1.80	56.0	LOGT 060204R-DT
GD-DHL 13.00X1650-U04	13.00	1561.80	1651.80	25.40	12.50	1.80	70.0	LOGT 060204R-DT
GD-DHL 13.00X1650-23	13.00	1575.80	1651.80	25.00	12.50	1.80	56.0	LOGT 060204R-DT
GD-DHL 13.00X1650-35	13.00	1575.80	1651.80	25.00	12.50	1.80	56.0	LOGT 060204R-DT


- Note: Gundrills can be supplied with up to 2400 mm length on request.
- Inserts and guide pads to be ordered separately (not included with the tools).
- For user guide and cutting conditions, see pages 113-115, 117-118
- Preventative measures: Do NOT operate the deep hole drill at full speed before engaging the guide hole. Enter the guide hole slowly at a speed of 50 - 100 rpm.

⁽¹⁾ Master insert identification

For inserts, see pages: LOGT (111)

GPS

Deep Drilling Solid Carbide Guide Pads




Designation	Dimensions				Tough → Hard	
	OAW	RE	OAL	OAH	IC928	IC908
GPS-04-16-055-DC	4.0	5.50	16.00	2.0	•	•

Spare Parts

Diameter Range	Insert	Insert Clamping Screw	Key	N-m	Solid Carbide Guide Pad	Guide Pad Clamping Screw	Key	N-m
12.00-13.99	LOGT 060204R-DT	SR 10503833L040	T-7F	0.9	GPS-04-16-055-DC	TS 20043/HG-P M2X0.4	Wrench IP-6/5	0.65

Universal Marking for Deep Drilling Tools



D.****
D

L***
L/D

d**
d1

X**
d2

XX
Driver Type

Example:


Metric: D14.00 L1000 d25X56WD

Inch: D0.551 L39.37 d0.984X2.205WD

***** [Lot no.]


GD-DH

Gundrills Carrying Triangular Inserts with 3 Chip Splitting Cutting Edges and a Wiper for High Hole Surface Quality




Designation	DC	LU	DCONMS	BD	LF	PL	LS	Insert
GD-DH 14.00-15D-M25-07	14.00	227.00	25.00	13.50	261.00	1.95	56.0	TOGT 07..
GD-DH 14.00-20D-M25-07	14.00	302.00	25.00	13.50	336.00	1.95	56.0	TOGT 07..
GD-DH 14.00-25D-M25-07	14.00	377.00	25.00	13.50	411.00	1.95	56.0	TOGT 07..
GD-DH 14.50-15D-M25-07	14.50	227.00	25.00	14.00	262.00	1.95	56.0	TOGT 07..
GD-DH 14.50-20D-M25-07	14.50	302.00	25.00	14.00	337.00	1.95	56.0	TOGT 07..
GD-DH 14.50-25D-M25-07	14.50	377.00	25.00	14.00	412.00	1.95	56.0	TOGT 07..
GD-DH 15.00-15D-M25-07	15.00	242.00	25.00	14.50	278.00	1.95	56.0	TOGT 07..
GD-DH 15.00-20D-M25-07	15.00	322.00	25.00	14.50	358.00	1.95	56.0	TOGT 07..
GD-DH 15.00-25D-M25-07	15.00	402.00	25.00	14.50	438.00	1.95	56.0	TOGT 07..
GD-DH 16.00-10D-M25-08-N	16.00	172.20	25.00	15.50	209.00	2.20	56.0	TOGT 08..
GD-DH 16.00-15D-M25-08-N	16.00	257.20	25.00	15.50	294.00	2.20	56.0	TOGT 08..
GD-DH 16.00-25D-M25-08-N	16.00	427.20	25.00	15.50	464.00	2.20	56.0	TOGT 08..
GD-DH 16.50-10D-M25-08-N	16.50	172.20	25.00	15.50	209.00	2.20	56.0	TOGT 08..
GD-DH 16.50-15D-M25-08-N	16.50	257.20	25.00	15.50	294.00	2.20	56.0	TOGT 08..
GD-DH 16.50-25D-M25-08-N	16.50	427.20	25.00	15.50	464.00	2.20	56.0	TOGT 08..
GD-DH 17.00-10D-M25-08-N	17.00	182.20	25.00	16.20	220.00	2.20	56.0	TOGT 08..
GD-DH 17.00-15D-M25-08-N	17.00	272.20	25.00	16.20	310.00	2.20	56.0	TOGT 08..
GD-DH 17.00-25D-M25-08-N	17.00	452.20	25.00	16.20	490.00	2.20	56.0	TOGT 08..
GD-DH 17.50-15D-M25-08-N	17.50	272.20	25.00	16.20	310.00	2.20	56.0	TOGT 08..
GD-DH 17.50-25D-M25-08-N	17.50	452.20	25.00	16.20	490.00	2.20	56.0	TOGT 08..
GD-DH 18.00-10D-M25-08-N	18.00	193.00	25.00	16.20	232.00	2.20	56.0	TOGT 08..
GD-DH 18.00-15D-M25-08-N	18.00	288.00	25.00	17.20	327.00	2.20	56.0	TOGT 08..
GD-DH 18.00-25D-M25-08-N	18.00	478.00	25.00	17.20	517.00	2.20	56.0	TOGT 08..
GD-DH 18.50-15D-M25-09	18.50	288.00	25.00	17.20	327.00	3.00	56.0	TOGT 09..
GD-DH 18.50-25D-M25-09	18.50	478.00	25.00	17.20	517.00	3.00	56.0	TOGT 09..
GD-DH 19.00-10D-M25-09	19.00	203.00	25.00	18.20	243.00	3.00	56.0	TOGT 09..
GD-DH 19.00-15D-M25-09	19.00	303.00	25.00	18.20	343.00	3.00	56.0	TOGT 09..
GD-DH 19.00-25D-M25-09	19.00	503.00	25.00	18.20	543.00	3.00	56.0	TOGT 09..
GD-DH 19.50-15D-M25-09	19.50	303.00	25.00	18.20	343.00	3.00	56.0	TOGT 09..
GD-DH 19.50-25D-M25-09	19.50	503.00	25.00	18.20	543.00	3.00	56.0	TOGT 09..
GD-DH 20.00-10D-M32-09	20.00	213.20	32.00	19.00	255.00	3.00	60.0	TOGT 09..
GD-DH 20.00-15D-M32-09	20.00	318.20	32.00	19.00	360.00	3.00	60.0	TOGT 09..
GD-DH 20.00-25D-M32-09	20.00	528.20	32.00	19.00	570.00	3.00	60.0	TOGT 09..
GD-DH 21.00-10D-M32-10	21.00	223.20	32.00	20.00	266.00	3.20	60.0	TOGT 10..
GD-DH 21.00-15D-M32-10	21.00	333.20	32.00	20.00	376.00	3.20	60.0	TOGT 10..
GD-DH 21.00-25D-M32-10	21.00	553.20	32.00	20.00	596.00	3.20	60.0	TOGT 10..
GD-DH 22.00-10D-M32-11	22.00	233.40	32.00	21.00	278.00	3.40	60.0	TOGT 11..
GD-DH 22.00-15D-M32-11	22.00	348.40	32.00	21.00	393.00	3.40	60.0	TOGT 11..
GD-DH 22.00-25D-M32-11	22.00	578.40	32.00	21.00	623.00	3.40	60.0	TOGT 11..
GD-DH 23.00-10D-M32-11	23.00	243.40	32.00	22.00	289.00	3.40	60.0	TOGT 11..
GD-DH 23.00-15D-M32-11	23.00	363.40	32.00	22.00	409.00	3.40	60.0	TOGT 11..
GD-DH 23.00-25D-M32-11	23.00	603.40	32.00	22.00	649.00	3.40	60.0	TOGT 11..
GD-DH 24.00-10D-M32-11	24.00	253.40	32.00	23.00	301.00	3.40	60.0	TOGT 11..
GD-DH 24.00-15D-M32-11	24.00	378.40	32.00	23.00	426.00	3.40	60.0	TOGT 11..
GD-DH 24.00-25D-M32-11	24.00	628.40	32.00	23.00	676.00	3.40	60.0	TOGT 11..
GD-DH 25.00-10D-M32-11	25.00	263.60	32.00	24.00	312.00	3.40	60.0	TOGT 11..
GD-DH 25.00-15D-M32-11	25.00	393.60	32.00	24.00	442.00	3.40	60.0	TOGT 11..
GD-DH 25.00-25D-M32-11	25.00	653.60	32.00	24.00	702.00	3.40	60.0	TOGT 11..
GD-DH 26.00-10D-M40-12	26.00	273.60	40.00	25.00	324.00	3.60	70.0	TOGT 12..
GD-DH 26.00-15D-M40-12	26.00	408.60	40.00	25.00	459.00	3.60	70.0	TOGT 12..
GD-DH 26.00-25D-M40-12	26.00	678.60	40.00	25.00	729.00	3.60	70.0	TOGT 12..
GD-DH 27.00-10D-M40-12	27.00	283.60	40.00	26.00	335.00	3.60	70.0	TOGT 12..
GD-DH 27.00-15D-M40-12	27.00	423.60	40.00	26.00	475.00	3.60	70.0	TOGT 12..
GD-DH 27.00-25D-M40-12	27.00	703.60	40.00	26.00	755.00	3.60	70.0	TOGT 12..
GD-DH 28.00-10D-M40-12	28.00	283.60	40.00	27.00	337.00	3.60	70.0	TOGT 12..
GD-DH 28.00-15D-M40-12	28.00	423.60	40.00	27.00	477.00	3.60	70.0	TOGT 12..
GD-DH 28.00-25D-M40-12	28.00	703.60	40.00	27.00	757.00	3.60	70.0	TOGT 12..
GD-DH 29.00-10D-M40-13	29.00	294.57	40.00	27.00	360.00	4.57	69.0	TOGT 13..
GD-DH 29.00-20D-M40-13	29.00	584.57	40.00	27.00	650.00	4.57	69.0	TOGT 13..
GD-DH 30.00-10D-M40-13	30.00	314.57	40.00	29.00	383.00	4.57	69.0	TOGT 13..
GD-DH 30.00-20D-M40-13	30.00	624.57	40.00	29.00	693.00	4.57	69.0	TOGT 13..
GD-DH 31.00-10D-M40-13	31.00	314.57	40.00	29.00	383.00	4.57	69.0	TOGT 13..
GD-DH 31.00-20D-M40-13	31.00	624.57	40.00	29.00	693.00	4.57	69.0	TOGT 13..
GD-DH 32.00-10D-M40-13	32.00	324.57	40.00	30.00	395.00	4.57	69.0	TOGT 13..
GD-DH 32.00-20D-M40-13	32.00	644.57	40.00	30.00	715.00	4.57	69.0	TOGT 13..

- Note: Gundrills can be supplied with up to 2400 mm length on request.
- Inserts and guide pads to be ordered separately (not included with the tools).
- For user guide and cutting conditions, see pages 113-115, 117-118
- Preventative measures: Do NOT operate the deep hole drill at full speed before engaging the guide hole. Enter the guide hole slowly at a speed of 50 - 100 rpm.

For inserts, see pages: TOGT-DT (11) • TOGT-GF (11)

Universal Marking for Deep Drilling Tools



Driver Type

M	machining	M20,M25,M32,M40,U19.05,U25.4,U31.75,U38.1,FM32,FM40,FU31.75,FU38.1	
WD	weldon	22,23,24,25,26,99	
WN	whistle notch	U03,U04,U05,U06,34,35,36	
F	flat	FD50C25,FD37C25,C25	
C	cylindrical	95	
CCL	cylindrical clamping	57	

Example:

Metric: D14.00 L/D15 d25X56M


Inch: D0.551 L/D15 d0.984X2.205M

Spare Parts

Diameter Range	Insert	Insert Clamping Screw	Key	N*m	Solid Carbide Guide Pad	Guide Pad Clamping Screw	Key
14.00-15.99	TOGT 070304-DT/GF	SR 14-560/S M2.5X0.45	T-8/5	1.2	GPS-05-18-060-DC	SR 34-508 M2.2X0.45	T-7/5
16.00-18.00	TOGT 080305-DT/GF		T-8/5	1.2	GPS-05-18-075-DC		
18.01-20.00	TOGT 090305-DT/GF		T-8/5	1.2	GPS-06-20-085-DC		
20.01-21.00	TOGT 100305-DT/GF	SR 34-506 M3X0.5	T-9/5	2.0	GPS-06-20-085-DC		
21.01-21.99	TOGT 100305-DT/GF				GPS-06-20-100-DC		
22.00-25.00	TOGT 110405-DT/GF	SR 14-571/S M3.5X0.6	T-10/5	4.8	GPS-06-20-100-DC	SR 34-508 M2.2X0.45	T-7/5
25.01-28.00	TOGT 120405-DT/GF	SR 14-506 M4X0.7	T-15/5	4.8	GPS-06-20-120-DC		
28.01-29.99	TOGT 130408-DT/GF				GPS-06-20-120-DC		
30.00-32.00	TOGT 130408-DT/GF	SR 16-212/L10 M5X0.8	T20/5	10	GPS-07-20-120-DC	CSTB-3L065 M2.2X0.45	T-9/5
32.01-39.00	TOGT 140510-DT/GF				GPS-07-20-120-DC		
39.01-40.00	TOGT 140510-DT/GF				GPS-08-25-155-DC		

**GDH-MKT**

Gundrill Heads Carrying Triangular Inserts with 3 Chip Splitting Cutting Edges and a Wiper for High Hole Surface Quality



Designation	DC	BD	LH
GDH-14.00 MKT	14.00	13.70	50.1
GDH-14.50 MKT	14.50	14.20	50.1
GDH-15.00 MKT	15.00	14.70	50.1
GDH-16.00 MKT	16.00	15.70	50.2
GDH-16.50 MKT	16.50	16.00	50.2
GDH-17.00 MKT	17.00	16.50	50.2
GDH-17.50 MKT	17.50	17.20	50.2
GDH-18.00 MKT	18.00	17.40	50.2
GDH-18.50 MKT	18.50	18.00	50.3
GDH-19.00 MKT	19.00	18.40	50.3
GDH-19.50 MKT	19.50	18.90	50.3
GDH-20.00 MKT	20.00	19.40	50.3
GDH-21.00 MKT	21.00	20.40	50.3
GDH-22.00 MKT	22.00	21.70	50.3
GDH-23.00 MKT	23.00	22.40	50.3
GDH-24.00 MKT	24.00	23.40	50.3
GDH-25.00 MKT	25.00	24.40	50.3
GDH-26.00 MKT	26.00	25.40	50.3
GDH-27.00 MKT	27.00	26.40	50.3
GDH-28.00 MKT	28.00	27.40	50.3

• Inserts and guide pads to be ordered separately (not included with the tools). • For user guide and cutting conditions, see pages 113-115, 117-118


For inserts, see pages: LOGT (111) • TOGT-DT (11) • TOGT-GF (11)

Spare Parts

Gundrill Head Description	Solid Carbide Guide Pad	Guide Pad Screw		Guide Pad Key	Insert Screw		Insert Key
	Description	Description	Qty.	Description	Description	Qty.	Description
GDH-14.00 MKT	GPS-05-18-060-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-560/S M2.5X0.45	1	T-8/5
GDH-14.50 MKT	GPS-05-18-060-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-560/S M2.5X0.45	1	T-8/5
GDH-15.00 MKT	GPS-05-18-060-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-560/S M2.5X0.45	1	T-8/5
GDH-16.00 MKT	GPS-05-18-075-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-560/S M2.5X0.45	1	T-8/5
GDH-16.50 MKT	GPS-05-18-075-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-560/S M2.5X0.45	1	T-8/5
GDH-17.00 MKT	GPS-05-18-075-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-560/S M2.5X0.45	1	T-8/5
GDH-17.50 MKT	GPS-05-18-075-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-560/S M2.5X0.45	1	T-8/5
GDH-18.00 MKT	GPS-05-18-075-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-560/S M2.5X0.45	1	T-8/5
GDH-18.50 MKT	GPS-06-20-085-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-560/S M2.5X0.45	1	T-8/5
GDH-19.00 MKT	GPS-06-20-085-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-560/S M2.5X0.45	1	T-8/5
GDH-19.50 MKT	GPS-06-20-085-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-560/S M2.5X0.45	1	T-8/5
GDH-20.00 MKT	GPS-06-20-085-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 34-506 M3X0.5	1	T-9/5
GDH-21.00 MKT	GPS-06-20-100-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 34-506 M3X0.5	1	T-9/5
GDH-22.00 MKT	GPS-06-20-100-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-571/S M3.5X0.6	1	T-10/5
GDH-22.50 MKT	GPS-06-20-100-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-571/S M3.5X0.6	1	T-10/5
GDH-23.00 MKT	GPS-06-20-100-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-571/S M3.5X0.6	1	T-10/5
GDH-23.50 MKT	GPS-06-20-100-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-571/S M3.5X0.6	1	T-10/5
GDH-24.00 MKT	GPS-06-20-100-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-571/S M3.5X0.6	1	T-10/5
GDH-25.00 MKT	GPS-06-20-120-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-571/S M3.5X0.6	1	T-10/5
GDH-26.00 MKT	GPS-06-20-120-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-506 M4X0.7	1	T-15/5
GDH-27.00 MKT	GPS-06-20-120-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-506 M4X0.7	1	T-15/5
GDH-28.00 MKT	GPS-06-20-120-DC	SR 34-508 M2.2X0.45	2	T-7/5	SR 14-506 M4X0.7	1	T-15/5

ZSGT

Deep Drilling Inserts with
Single Chip Splitting Cutting
Edge and a Wiper




Dimensions					IC948
Designation	W1	RE	PL	S	
ZSGT 060204R-DT	6.00	0.40	1.800	1.50	

For tools, see pages: GD-DH (10.00-11.50) (105)

LOGT

Deep Drilling Inserts with 2 Chip
Splitting Cutting Edges, Positive
Rake Chipbreaker and a Wiper



Dimensions					IC908
Designation	IC	RE	PL	S	
LOGT 060204R-DT	7.00	0.40	1.80	2.00	

For tools, see pages: GD-DH (12-13.5) (106) • GD-DHL (12-13) (107) • GDH-MKT (110)


Spare Parts



Designation	Insert screw	Insert key	N-m
LOGT 060204R-DT	SR 10503833L040	T-7F	0.9

TOGT-DT

Deep Drilling Inserts with 3 Chip
Splitting Cutting Edges, a Positive
Rake Chipbreaker and a Wiper




Dimensions						IC908
Designation	IC	RE	PL	S	Fig.	
TOGT 070304-DT	7.69	0.40	1.95	2.30	1	
TOGT 080305-DT	8.55	0.50	2.20	2.80	1	•
TOGT 090305-DT	8.32	0.50	3.00	3.00	2	•
TOGT 100305-DT	9.23	0.50	3.20	3.30	2	•
TOGT 110405-DT	10.40	0.50	3.40	3.80	2	•
TOGT 120405-DT	11.59	0.50	3.60	4.30	2	•
TOGT 130408-DT	12.85	0.80	4.57	4.76	2	•
TOGT 140510-DT	16.85	1.00	5.43	5.26	2	•

For tools, see pages: DDD-EF-FT (10) • DSD-EF-FT (9) • DSD-IF-FT (9) • GD-DH (108) • GDH-MKT (110)


TRIDEEP
 DEEP DRILLING

TOGT-GF

Deep Drilling Inserts with 3 Chip Splitting Cutting Edges, a Positive Rake Chipbreaker and a Wiper



Designation	Dimensions					IC908
	IC	RE	PL	S	Fig.	
TOGT 070304-GF	7.69	0.40	1.95	2.30	1	●
TOGT 080305-GF	8.55	0.50	2.20	2.80	1	●
TOGT 090305-GF	8.32	0.50	3.00	3.00	2	●
TOGT 100305-GF	9.23	0.50	3.20	3.30	2	●
TOGT 110405-GF	10.40	0.50	3.40	3.80	2	●
TOGT 120405-GF	11.59	0.50	3.60	4.30	2	●
TOGT 130408-GF	12.85	0.80	4.57	4.76	2	●


For tools, see pages: DDD-EF-FT (10) • DSD-EF-FT (9) • DSD-IF-FT (9) • GD-DH (108) • GDH-MKT (110)

Chipbreaker Appearances


		GF	DT
1	rake angle 	$a^{\circ}=25^{\circ}$	$a^{\circ}=20^{\circ}$
2	ID mark 		

Wide Flute Angle

- smooth chip evacuation


Large Oil Hole

- efficient lubrication
- longer life of inserts and guide pads

Brazed Body

Steel Body Tool

- extremely high rigidity
- simple direct mounting setup


Flange

- superior rigidity for higher speeds and feeds


Drilling Process on Machining Centers and Lathe Machines

- 1 Drill a 15 mm pilot hole $D_{+0.05}^{+0.03}$ flat bottom
- 2 Set the TRIDEEP drill into the pilot hole (10 mm depth). $V_c=5-10$ m/min $f=0.5-1.0$ mm/rev
- 3 Initial cutting at a 25 mm DOC (80% feed rate), verify activated coolant ($V_c=100\%$)
- 4 In case of through hole, drill the full hole to a depth of +5 mm
- 5 Retract with slow rotation (5-10 m/min)


- 1 Drill a 15 mm pilot hole flat bottom




- 2 Slow rotation and feed while entering to the pre-hole





- 3 Maintain for 2-3 seconds and activate the cooling system




- 4 Drill +5mm depth through hole



Required Power





Required Coolant Pressure




Deformation by Centrifugal Force

When using gundrill tools for deep drilling, a "whip" phenomenon can occur. This can be predicted based on tool length and cutting speed. If the parameters are in the deformation zone as shown below, cutting speed amending or use of guides for support should be considered to avoid the whip phenomenon.




Recommended Support Guide Shape

A support guide may be needed to assure a stable drilling process. The use of a dedicated shaped guide bush is recommended.



Inquiry Form



1. Tool

Quantity _____

Nominal diameter and tolerance _____

Please fill in dimensions on the sketch.

Driver

For standard drivers please use codes from page 118 _____

☐ Code No.

☐ Special, please attach sketch and specifications.

2. Workpiece

(If possible, attach a drawing)

2.1 Material

 Material description
(DIN material number or any other standard):

Hardness and Properties:

2.2 Hole Type

☐ Blind Hole ☐ Drilling into Pre-hole

☐ Angled Entry

☐ Drilling into Solid ☐ Boring ☐ Angled Exit

Drilling Depth _____mm Hole Tolerance _____

2.3 Application:

 Workpiece: ☐ Stationary ☐ Rotating

 Tool: ☐ Stationary ☐ Rotating


3. Machine

3.1 Technical Data

Machine Type _____

Power _____kW _____

Sketch of drilling application



Note: It may be necessary to change several of the parameters that you indicated, based on our experience with your application.

3.2 Cutting Data:

 Cutting Speed V_c _____m/min

 Revolutions N_{min} _____RPM, N_{max} _____RPM

 Feed F_{min} _____mm/rev,

 F_{max} _____mm/rev

 Feed Rate V_F _____mm/min

Coolant:

☐ Oil ☐ Soluble Oil ☐ Other

Coolant Pressure: _____Bar

Specially Tailored **TRIDEEP** Code Key

GD - DH ## . ## - #### - ##

↓	↓	↓
Dia.	Drilling Length	Shank Type

Cutting Conditions for GD-DH (10.00-11.50)

ISO	Material	Condition	Tensile Strength [N/mm ²]	Hardness HB	Material Group No. ⁽¹⁾	Cutting Speed v _c m/min	ZSGT 06 Feed [mm/rev]
							Feed [mm/rev]
P	non-alloy steel and cast steel, free cutting steel	<0.25% C annealed	420	125	1	80-140	0.05-0.08
		≥0.25% C annealed	650	190	2		
		<0.55% C quenched and tempered	850	250	3		0.05-0.14
		annealed	750	220	4		
		quenched and tempered	1000	300	5		
	low alloy and cast steel (less than 5% of alloying elements)	annealed	600	200	6	80-120	0.05-0.08
		quenched and tempered	930	275	7		
			1000	300	8		
			1200	350	9	80-120	0.05-0.14
	high alloyed steel, cast steel and tool steel	annealed	680	200	10		
	stainless steel and cast steel	quenched and tempered	1100	325	11	60-100	0.05-0.08
		ferritic/martensitic	680	200	12		
		martensitic	820	240	13		
M	stainless steel and cast steel	austenitic, duplex	600	180	14	60-100	0.05-0.08
K	grey cast iron (GG)	ferritic/pearlitic		180	15	80-140	0.05-0.2
		pearlitic/martensitic		260	16		
	nodular cast iron (GGG)	ferritic		160	17		
		pearlitic		250	18		
	malleable cast iron	ferritic		130	19		
		pearlitic		230	20		
N	aluminum-wrought alloys	not hardenable		60	21	100-200	0.05-0.18
		hardenable		100	22		
	aluminum-cast alloys	≤12% Si not hardenable		75	23		
		hardenable		90	24		
		>12% Si high temperature		130	25		
	copper alloys	>1% Pb free cutting		110	26		
		brass		90	27		
		electrolitic copper		100	28		
	non-metallic	duroplastics, fiber plastics			29		
		hard rubber			30		
S	high temp. alloys	Fe based annealed		200	31	20-50	0.04-0.06
		hardened		280	32		
		Ni or Co based annealed		250	33		
		hardened		350	34		
		cast		320	35		
	titanium alloys	pure	400		36	30-60	0.04-0.1
		alpha+beta alloys hardened	1050		37		
H	hardened steel	hardened		55 HRC	38	50-100	0.04-0.06
		hardened		60 HRC	39		
	chilled cast iron	cast		400	40		
	cast iron	hardened		55 HRC	41		

* Coolant recommendations for drilling stainless steel:

- Oil coolant is first choice
- Water soluble coolant requires at least 20% oil concentration

(1) Based on ISO 513 and VDI 3323 standards

Machining Recommendations for TRIDEEP Drills (12.00-32.00mm)

ISO	Material		Condition	Tensile Strength [N/mm ²]	Hardness HB	Material Group No.	LOGT / TOGT																							
							V m/min	Feed per insert size "GF" & "DT"																						
								06	07	08	09		10		11	12	13													
								mm/rev																						
P	non-alloy steel and cast steel, free cutting steel	<0.25% C	annealed	420	125	1	80-120 80-120	0.04-0.08 0.08-0.14	0.04-0.10 0.08-0.16	0.06-0.10 0.08-0.16	0.06-0.10 0.08-0.16	0.06-0.12 0.08-0.18																		
		≥0.25% C	annealed	650	190	2																								
		<0.55% C	quenched and tempered	850	250	3																								
			annealed	750	220	4																								
			quenched and tempered	1000	300	5																								
	low alloy and cast steel (less than 5% of alloying elements)	annealed	600	200	6	0.04-0.12 0.06-0.20																								
			quenched and tempered	930	275							7																		
				1000	300							8																		
				1200	350							9																		
	high alloyed steel, cast steel and tool steel	annealed	680	200	10	0.04-0.08 0.08-0.14		0.04-0.10 0.08-0.16	0.06-0.10 0.08-0.16	0.06-0.10 0.08-0.16	0.06-0.12 0.08-0.18																			
		quenched and tempered	1100	325	11																									
stainless steel and cast steel	ferritic/ martensitic	680	200	12	0.04-0.08 0.08-0.14	0.04-0.10 0.08-0.16	0.06-0.10 0.08-0.16	0.06-0.10 0.08-0.16	0.06-0.12 0.08-0.18																					
	martensitic	820	240	13																										
M	stainless steel and cast steel		austenitic, duplex	600	180	14	50-100 50-100	0.02-0.06 0.04-0.12	0.02-0.06 0.04-0.12	0.02-0.06 0.04-0.12	0.02-0.06 0.04-0.12	0.02-0.06 0.04-0.12																		
K	grey cast iron (GG)		ferritic/pearlitic		180	15	50-100 80-120	0.03-0.15 0.08-0.25	0.03-0.15 0.08-0.25	0.05-0.18 0.08-0.25	0.05-0.18 0.08-0.30	0.05-0.18 0.08-0.30																		
			pearlitic / martensitic		260	16																								
	cast iron nodular (GGG)		ferritic		160	17							50-100 80-120	0.03-0.15 0.08-0.25	0.03-0.15 0.08-0.25	0.05-0.18 0.08-0.25	0.05-0.18 0.08-0.30	0.05-0.18 0.08-0.30												
			pearlitic		250	18																								
	malleable cast iron		ferritic		130	19													50-100 80-120	0.03-0.15 0.08-0.25	0.03-0.15 0.08-0.25	0.05-0.18 0.08-0.25	0.05-0.18 0.08-0.30	0.05-0.18 0.08-0.30						
pearlitic				230	20																									
N	aluminum-wrought alloys		not hardenable		60	21	80-160 80-160	0.03-0.15 0.08-0.20	0.03-0.15 0.08-0.20	0.03-0.18 0.08-0.20	0.05-0.18 0.08-0.20	0.05-0.18 0.08-0.20																		
			hardenable		100	22																								
	aluminum- cast alloys	≤12% Si	not hardenable		75	23							80-160 80-160	0.03-0.15 0.08-0.20	0.03-0.15 0.08-0.20	0.03-0.18 0.08-0.20	0.05-0.18 0.08-0.20	0.05-0.18 0.08-0.20												
		hardenable		90	24																									
	>12% Si	high temperature		130	25	80-160 80-160													0.03-0.15 0.08-0.20	0.03-0.15 0.08-0.20	0.03-0.18 0.08-0.20	0.05-0.18 0.08-0.20	0.05-0.18 0.08-0.20							
		>1% Pb	free cutting		110																			26						
			brass		90																			27						
	copper alloys	electrolitic copper		100	28																			80-160 80-160	0.03-0.15 0.08-0.20	0.03-0.15 0.08-0.20	0.03-0.18 0.08-0.20	0.05-0.18 0.08-0.20	0.05-0.18 0.08-0.20	
non metallic		duroplastics, fiber plastics			29																									
	hard rubber				30		80-160 80-160	0.03-0.15 0.08-0.20	0.03-0.15 0.08-0.20	0.03-0.18 0.08-0.20	0.05-0.18 0.08-0.20	0.05-0.18 0.08-0.20																		
S	high temp. alloys	Fe based	annealed		200								31	20-50 20-50	0.04-0.08 0.08-0.14	0.04-0.10 0.08-0.16	0.06-0.10 0.08-0.16	0.06-0.10 0.08-0.16												0.06-0.12 0.08-0.18
			hardened		280								32																	
		Ni or Co based	annealed		250	33																								
			hardened		350	34																								
			cast		320	35																								
	titanium alloys	pure	400		36	20-50 20-50							0.04-0.08 0.08-0.14						0.04-0.10 0.08-0.16	0.06-0.10 0.08-0.16	0.06-0.10 0.08-0.16	0.06-0.12 0.08-0.18								
alpha+beta alloys hardened		1050		37																										
H	hardened steel		hardened 55 HRC				38	20-50 20-50	0.04-0.08 0.08-0.14	0.04-0.10 0.08-0.16	0.06-0.10 0.08-0.16	0.06-0.10 0.08-0.16		0.06-0.12 0.08-0.18																
			hardened 60 HRC				39																							
	chilled cast iron	cast		400	40		20-50 20-50								0.04-0.08 0.08-0.14	0.04-0.10 0.08-0.16	0.06-0.10 0.08-0.16	0.06-0.10 0.08-0.16					0.06-0.12 0.08-0.18							
cast iron	hardened 55 HRC			41																										

Standard Gundrill Drivers for Machining Centers, Lathes

Drivers

Drivers are available for dedicated deep drilling type machines and CNC machines, for any specified diameter and length. Below are the driver codes and technical data.


Standard Drivers for Gundrill Machines

Driver Type	Drawing	øD x L	Driver Code
Cylindrical DIN1835A DIN6535HA		.75x2.03"	95
		20x50	10
		25x56	11
		1.00x2.28"	96
		1.25x2.28"	97
		32x60	12
Weldon DIN1835B DIN6535HB		.75x2.03"	99
		20x50	22
		25x56	23
		1.00x2.28"	100
		1.25x2.28"	101
		32x60	24
		40x70	25
Whistle Notch DIN1835E		20x50	34
		25x56	35
		32x60	36
		40x70	37
DIN228AK		CM1	45
		CM2	46
		CM3	47
		CM4	48
DIN228BK		CM1	49
		CM2	50
		CM3	51
		CM4	52
Central Clamping Surface 15°		.750x2.75"	56
		25x70	57
		1.00x2.75"	58
		1.25x2.75"	59
		1.50x2.75"	60
Frontal Clamping Surface 15°		16x50	61
Cylindrical with Thread		25x100 M16x1.5	66
		36x120 M24x1.5	67
VDI Design		25x112 M16x1.5	70
		36x135 M24x1.5	71

Driver Type	Drawing	øD x L	Driver Code
Central Clamping Hexagonal		25x70	72
		32x70	73
Central Clamping Tapered		.75x2.75"	76
		20x70	77
Frontal Clamping Surface 2°		1.00x2.75"	80
		1.00x3.94"	81
		1.25x2.75"	82
		1.25x3.94"	83
		1.50x2.75"	84
		1.50x3.94"	85
Trapezoidal Thread		28x126 Tr 28x2	88
		36x162 Tr 36x2	89
Spraymist Driver		25x50	91
		35x60	92

MNSNT

Indexable SUMOCHAM Inserts
and Modular Shank Gundrills



Designation	DCN ⁽¹⁾	DCX ⁽²⁾	LU	PL	THSZMS	BD	BDRED	LPR	FLGT	DRVS ⁽³⁾	SSC ⁽⁴⁾	MIID ⁽⁵⁾	
MNSNT 100-200-MF16X1	10.00	10.40	200.00	2.720	MF16X1	9.70	9.60	274.00	10.00	16.0	10.0	HCP 100	K DCN 10-13.99
MNSNT 105-200-MF16X1	10.50	10.90	200.00	2.720	MF16X1	10.20	10.10	274.00	10.00	16.0	10.0	HCP 105	K DCN 10-13.99
MNSNT 110-200-MF16X1	11.00	11.40	200.00	2.750	MF16X1	10.70	10.60	275.00	10.00	16.0	11.0	HCP 110	K DCN 10-13.99
MNSNT 115-200-MF16X1	11.50	11.90	200.00	2.750	MF16X1	11.20	11.10	275.00	10.00	16.0	11.0	HCP 115	K DCN 10-13.99
MNSNT 120-200-MF16X1	12.00	12.40	200.00	3.160	MF16X1	11.70	11.60	275.00	10.00	16.0	12.0	HCP 120	K DCN 10-13.99
MNSNT 125-200-MF16X1	12.50	12.90	200.00	3.160	MF16X1	12.20	12.10	275.00	12.00	16.0	12.0	HCP 125	K DCN 10-13.99
MNSNT 130-200-MF16X1	13.00	13.40	200.00	3.510	MF16X1	12.70	12.60	276.00	12.00	16.0	13.0	HCP 130	K DCN 10-13.99
MNSNT 135-200-MF16X1	13.50	13.90	200.00	3.510	MF16X1	13.20	13.10	276.00	12.00	16.0	13.0	HCP 135	K DCN 10-13.99
MNSNT 140-200-MF16X1	14.00	14.40	200.00	3.630	MF16X1	13.70	13.60	276.00	12.00	16.0	14.0	HCP 140	K DCN 14-17.99
MNSNT 145-200-MF16X1	14.50	14.90	200.00	3.630	MF16X1	14.20	14.10	276.00	12.00	16.0	14.0	HCP 145	K DCN 14-17.99
MNSNT 130-250-MF16X1	13.00	13.40	250.00	3.510	MF16X1	12.70	12.60	326.00	12.00	16.0	13.0	HCP 130	K DCN 10-13.99
MNSNT 135-250-MF16X1	13.50	13.90	250.00	3.510	MF16X1	13.20	13.10	326.00	12.00	16.0	13.0	HCP 135	K DCN 10-13.99
MNSNT 140-250-MF16X1	14.00	14.40	250.00	3.630	MF16X1	13.70	13.60	326.00	12.00	16.0	14.0	HCP 140	K DCN 14-17.99
MNSNT 145-250-MF16X1	14.50	14.90	250.00	3.630	MF16X1	14.20	14.10	326.00	12.00	18.0	14.0	HCP 145	K DCN 14-17.99
MNSNT 100-400-MF16X1	10.00	10.40	400.00	2.720	MF16X1	9.70	9.60	474.00	10.00	16.0	10.0	HCP 100	K DCN 10-13.99
MNSNT 105-400-MF16X1	10.50	10.90	400.00	2.720	MF16X1	10.20	10.10	474.00	10.00	16.0	10.0	HCP 105	K DCN 10-13.99
MNSNT 110-400-MF16X1	11.00	11.40	400.00	2.750	MF16X1	10.70	10.60	474.00	10.00	16.0	11.0	HCP 110	K DCN 10-13.99
MNSNT 115-400-MF16X1	11.50	11.90	400.00	2.750	MF16X1	11.20	11.10	474.00	10.00	16.0	11.0	HCP 115	K DCN 10-13.99
MNSNT 120-400-MF16X1	12.00	12.40	400.00	3.160	MF16X1	11.70	11.60	475.00	10.00	16.0	12.0	HCP 120	K DCN 10-13.99
MNSNT 125-400-MF16X1	12.50	12.90	400.00	3.160	MF16X1	12.20	12.10	475.00	12.00	16.0	12.0	HCP 125	K DCN 10-13.99
MNSNT 130-400-MF16X1	13.00	13.40	400.00	3.510	MF16X1	12.70	12.60	476.00	12.00	16.0	13.0	HCP 130	K DCN 10-13.99
MNSNT 135-400-MF16X1	13.50	13.90	400.00	3.510	MF16X1	13.20	13.10	476.00	12.00	16.0	13.0	HCP 135	K DCN 10-13.99
MNSNT 140-400-MF16X1	14.00	14.40	400.00	3.630	MF16X1	13.70	13.60	476.00	12.00	16.0	14.0	HCP 140	K DCN 14-17.99
MNSNT 145-400-MF16X1	14.50	14.90	400.00	3.630	MF16X1	14.20	14.10	476.00	12.00	18.0	14.0	HCP 145	K DCN 14-17.99
MNSNT 150-400-MF16X1	15.00	15.90	400.00	3.880	MF16X1	14.70	14.60	484.00	12.00	18.0	15.0	HCP 150	K DCN 14-17.99
MNSNT 160-400-MF20X1	16.00	16.90	400.00	3.910	MF20X1	15.50	15.40	484.00	12.00	18.0	16.0	HCP 160	K DCN 14-17.99
MNSNT 170-400-MF20X1	17.00	17.90	400.00	4.570	MF20X1	16.50	16.40	485.00	12.00	22.0	17.0	HCP 170	K DCN 14-17.99
MNSNT 180-400-MF20X1	18.00	18.90	400.00	4.660	MF20X1	17.50	17.40	486.00	12.00	22.0	18.0	HCP 180	K DCN 18-21.99
MNSNT 190-400-MF20X1	19.00	19.90	400.00	4.660	MF20X1	18.50	18.40	486.00	12.00	22.0	19.0	HCP 190	K DCN 18-21.99
MNSNT 200-400-MF20X1	20.00	20.90	400.00	4.810	MF20X1	19.50	19.40	487.00	12.00	22.0	20.0	HCP 200	K DCN 18-21.99
MNSNT 210-400-MF20X1	21.00	21.90	400.00	4.940	MF20X1	20.50	20.40	503.00	21.00	28.0	21.0	HCP 210	K DCN 18-21.99
MNSNT 220-400-MF20X1	22.00	22.90	400.00	5.200	MF20X1	21.50	21.40	504.00	21.00	28.0	22.0	HCP 220	K DCN 22-26.99
MNSNT 230-400-MF20X1	23.00	23.90	400.00	5.280	MF20X1	22.50	22.40	504.00	21.00	28.0	23.0	HCP 230	K DCN 22-26.99
MNSNT 240-400-MF20X1	24.00	24.90	400.00	5.630	MF20X1	23.50	23.40	505.00	21.00	28.0	24.0	HCP 240	K DCN 22-26.99
MNSNT 250-400-MF20X1	25.00	25.90	400.00	5.700	MF20X1	24.50	24.40	506.00	21.00	28.0	25.0	HCP 250	K DCN 22-26.99

• For user guide and cutting conditions, see pages 120, 122-124

⁽¹⁾ Do not mount smaller drilling heads than the specified range of the drill body

⁽²⁾ Cutting diameter maximum

⁽³⁾ Torque key size

⁽⁴⁾ Seat size code

⁽⁵⁾ Master insert identification

For holders, see pages: GDV (121)

Machining Conditions for MNSNT


ISO	Material		Condition	Tensile Strength [N/mm ²]	Hardness HB	Material Group No.	V (m/min)	SUMOGUN				
								Feed vs. Drill Diameter				
								D=10-11.9	D=12-13.9	D=14-15.9	D=16-19.9	D=20-25.9
							mm/rev					
P	non-alloy steel and cast steel, free cutting steel	<0.25% C	annealed	420	125	1	80-110-140	0.15 0.18 0.21	0.18 0.21 0.24	0.20 0.23 0.27	0.25 0.30 0.35	0.25 0.30 0.35
		≥0.25% C	annealed	650	190	2	80-105-130					
		<0.55% C	quenched and tempered	850	250	3	80-100-120					
			annealed	750	220	4	70-90-110					
		≥0.55% C	quenched and tempered	1000	300	5	50-70-90					
	low alloy steel and cast steel (less than 5% of alloying elements)	annealed	600	200	6	80-100-120	0.14 0.17 0.21	0.16 0.20 0.24	0.18 0.22 0.26	0.23 0.27 0.31	0.25 0.30 0.35	
		quenched and tempered	930	275	7	70-90-110						
			1000	300	8	50-70-90						
			1200	350	9	40-55-70						
	high alloyed steel, cast steel, and tool steel	annealed	680	200	10	50-70-90	0.12 0.14 0.17	0.15 0.17 0.20	0.18 0.20 0.23	0.20 0.22 0.25	0.22 0.24 0.27	
		quenched and tempered	1100	325	11	40-60-80						
	stainless steel and cast steel	ferritic/ martensitic.	680	200	12	40-55-70	0.12 0.13 0.15	0.14 0.15 0.17	0.16 0.18 0.20	0.16 0.19 0.21	0.18 0.21 0.24	
		martensitic	820	240	13							
K	cast iron nodular (GG)	ferritic/pearlitic			180	15	90-125-160	0.20 0.23 0.27	0.25 0.28 0.32	0.30 0.33 0.37	0.35 0.40 0.45	0.35 0.42 0.47
		pearlitic/ martensitic			260	16	80-110-140					
	grey cast iron (GGG)	ferritic			160	17	90-135-180					
		pearlitic			250	18	80-110-140					
	malleable cast iron	ferritic			130	19	90-125-160					
		pearlitic			230	20	80-110-140					
N	aluminum-wrought alloys	not hardenable			60	21	90-155-220	0.25 0.28 0.32	0.30 0.33 0.37	0.35 0.38 0.42	0.40 0.45 0.50	0.45 0.50 0.57
		hardenable			100	22						
	aluminum-cast alloys	≤12% Si	not hardenable		75	23						
			hardenable		90	24						
		>12% Si	high temperature		130	25	80-120-160					

■ Recommended cutting data

- Mandatory use of emulsion or oil when drilling
- For the 400mm long tools please reduce the cutting speed by 20%.

GDV

Shanks for SUMOGUN
Modular Gundrills with
Threaded Connection



Designation	THSZWS	DCONMS	Shank ⁽¹⁾	LS
GDV56-MF16X1-I-WN.75"	MF16X1	19.05	S	69.8
GDV99-MF16X1-I-W.75"	MF16X1	19.05	W	69.8
GDV10-MF16X1-M-C20	MF16X1	20.00	C	50.0
GDV22-MF16X1-M-W20	MF16X1	20.00	W	50.0
GDV80-MF16X1-I-WN1.00"	MF16X1	25.40	WN	69.8
GDV11-MF20X1-M-C25	MF20X1	25.00	C	56.0
GDV23-MF20X1-M-W25	MF20X1	25.00	W	56.0
GDV57-MF20X1-M-WN25	MF20X1	25.00	S	70.0
GDV100-MF20X1-I-W1.00"	MF20X1	25.40	W	57.9
GDV58-MF20X1-I-WN1.00"	MF20X1	25.40	S	69.8
GDV101-MF20X1-I-W1.25"	MF20X1	31.75	W	57.9
GDV97-MF20X1-I-C1.25"	MF20X1	31.75	C	57.9
GDV12-MF20X1-M-C32	MF20X1	32.00	C	60.0
GDV24-MF20X1-M-W32	MF20X1	32.00	W	60.0
GDV13-MF20X1-M-C40	MF20X1	40.00	C	70.0
GDV25-MF20X1-M-W40	MF20X1	40.00	W	70.0

⁽¹⁾ W-Weldon, C-Cylindrical, S-Whistle notch 15°, WN-Whistle notch


For tools, see pages: • MNSNT (119)




Drill Penetration Instructions on Horizontal Milling and Lathe Machines

Note: The following procedure (1-4) is recommended for up to 400 mm hole depths using MNSNT ...-400... drill.

- 1 Drill a pilot hole 1xD deep with a short drill in the same diameter as of the **SUMOGUN** drill.
- 2 Enter the pre-hole at slow speed (50 RPM) and reduced feed rate to within 1 - 2 mm of pre-hole depth.
- 3 Activate the cooling system and increase rotation speed to recommended drilling speed, maintain for 2-3 seconds, then continue at recommended drilling feed. **No pecking is required.** Apply maximum possible coolant flow rate.
- 4 After having reached the required depth, reduce speed to 50-100 RPM while exiting from the hole.



Pressure and Coolant Flow Rate for SUMOGUN



SUMOGUN Drilling Range


Q l/min P bar GUNDRILL Machines
Milling and Turning Machines

Gundrill Lubrication and Cooling



The best performance is obtained by using oil. On equipment that uses water-soluble fluids (i.e. machining centers and CNC machines) a concentration between 10% and 15% is recommended.

Guidelines for Optimal Gundrill Performance

- Coolant pressure and flow.
- It is recommended to use a strong coolant flow for efficient chip flushing and cooling of the cutting edge.
- Filtration: It is recommended to use a filter under 20 μ m.
- **Note:** Improper filtration may result in interrupted flow of the lubricating oil. This creates a sticky surface on the bearing pads and leads to premature wear of the tool and overloading the coolant pump and spindle seals.
- The coolant temperature should be between 20 and 22° C.
Note: Above 50° C the viscosity of the coolant is reduced by 50% and becomes ineffective.



■ stationary workpiece – rotating tool
■ rotating workpiece – stationary tool




$L = 20 \times D$

1- The support bushing should be according to tube diameter (D3) (see below)

Bushing

Based on modified DIN 179 specify the "d" diameter of the drill head. Carbide bushing is delivered only on request.




$d = \text{Drill diameter} + 0.02$

Guide Bushing

A guide bushing is an essential component for a proper gundrill operation. The function of the guide bushing is to direct the SUMOGUN into the material during penetration. The diameter of the guide bushing should be within 20 microns larger than the diameter of the drill. Dedicated gundrill machines are equipped with a guide bushing system.


Support Bushing

D3 indicate the tube diameter



Support Bushing				
D3	Ext. Ø "D"	Ext. Ø "D1"	Length "L"	Length "L1"
9.6 - 16,399	20	26	20	12
9.6 - 25,999	30	38	26	16
9.6 - 25,999	45	50	26	16

SUMOGUN Inquiry Form



1. Tool

Quantity _____

Nominal diameter and tolerance _____

Please fill in dimensions on the sketch.

Driver

For standard drivers please use designation from page 121

Special Driver

☐ Code No. _____

☐ Special, please attach sketch and specifications.

2. Workpiece

(If possible, please attach a drawing)

2.1 Material

Material description (DIN material number or any other standard): _____

Hardness and Properties: _____

☐ Short Chips ☐ Long Chips

2.2 Hole Type

☐ Blind Hole ☐ Drilling into Pre-hole

☐ Angled Entry ☐ Drilling into Solid

☐ Boring ☐ Angled Exit


Drilling Depth _____ mm Hole Tolerance _____

2.3 Application:

Workpiece: ☐ Stationary ☐ Rotating

Tool: ☐ Stationary ☐ Rotating

Sketch of Drilling Application



Note: It may be necessary to change several of the parameters that you indicated, based on our experience with your application.

3. Machine

3.1 Technical Data

Machine Type _____

Power: _____ kW

3.2 Cutting Data:

Cutting Speed V_c _____ m/min

Revolutions Nmin _____ RPM, Nmax _____ RPM

Feed Fmin _____ mm/rev,

Fmax _____ mm/rev

Feed Rate VF _____ mm/min

Coolant:


☐ Oil ☐ Soluble Oil ☐ Other

Coolant Pressure: _____ Bar

Drill Body Type		Hole Diameter	Length	Metric Fine Pitch	Dwg. Number	Tool Type	
SNT	Steel body	Ø10.00-25.99	Drilling Depth	1=M16 1=M20	4 last digits	Code	Type
						No code	Standard shape and size
						GP	Guide Pads
						SC	Special Connector
						PT	P-Tube


MN	###	-	XXX	-	XXX	-	MF	1	GP	-	XXXX
----	-----	---	-----	---	-----	---	----	---	----	---	------

Drilling Head Mounting Procedure




When using a gundrill on a lathe machine, a short solid carbide centering drill should be used prior to the gundrill. Once the gundrill enters the pre-drilled hole, it is self-guided.


1 Drilling a pre-hole (drill diameter $+0.02$ mm)




Never try to penetrate the workpiece by using a gundrill



2 Gundrill penetration through the pre-hole




A shallow pre-hole can't lead the unbalanced gundrill




Drill Penetration Instructions


1 Rotate the drill counterclockwise prior to and during hole penetration



2 Stop the drill rotation and start the coolant




3 Rotate the drill clockwise prior to drilling operation



The Influence of a Tool Vs. Workpiece Rotation

Rotating tool	Rotating workpiece	Rotating tool & workpiece
Worst	Medium	Best

The maximum misalignment between the drill bushing and the workpiece center line should not exceed 0.02 mm (.0008").



Single Flute Gundrill

ISCAR's gundrill consists of a single-piece carbide head, a flute and a driver through which coolant flows to the working end where it is most needed. Chips are evacuated along the V-shaped external flute.

Drilling Head

The carbide head is tapered on its length to reduce friction. The taper angle depends on the type of material to be drilled. For high precision drilling, the taper should be reduced to a minimum.

Note that when the head is resharpened, the diameter of the drill changes, affecting the hole tolerance.

Flute

The cross-section of the flute is V-shaped with coolant holes. It is made of hardened steel that is highly resistant to twisting. This cross-section provides the optimal conditions for twist resistance, coolant flow and chip evacuation.

Driver

The driver ensures the connection between the gundrill and the machine tool, (see page 128 for detailed driver information).


Advantages

- Drilling precision of IT7 to IT9 tolerances can be reached
- Excellent straightness and concentricity
- Maintains high precision hole center alignment
- Surface roughness of R0.4 - R1.6 is easily obtained
- Reboring operations are often unnecessary

Carbide Tipped Gundrill Range

Drill Diameter	Max. Flute Length
2.50 to 3.09	1100
3.10 to 5.99	2500
6.00 to 11.39	3000
11.40 to 40.00	3500

Overall length=flute length+driver length (see page 130)



ISCAR's advanced gundrill technology provides superior geometric and dimensional quality for both deep and shallow drilling. The drills are available in the range of 2.5 to 40 mm.

Single Flute Solid Carbide Gundrills

Another type of gundrill is made with an integral tip and flute, made of solid carbide with either a steel or a carbide driver. These drills are designed for conventional machines, machining centers and lathes. This style of gundrill is available from 0.9-16 mm and can be used on various types of materials. It provides superior rigidity and optimal coolant flow rates. As a result of its rigidity, up to 100% higher feed rate can be reached.

When using the small diameter drills, it is crucial to adhere closely to the recommended drilling parameters.

Solid Carbide Gundrill Range


(with or without brazed steel driver)

Drill Diameter	Max. Flute Length
0.9 to 16.00	300 mm


Standard Gundrill Head Sharpening Angles

Subject to the required tolerance, cutting performance and desired chip shape, the following standard sharpening angles are recommended (shown in figures 1 and 2).


1 Standard sharpening for 0.9 to 4 mm drill diameters



2 Standard sharpening for 4 to 32 mm drill diameters



3 Standard sharpening for 32 to 40 mm drill diameters




Note: For special or semi-standard gundrills, special geometries will be offered to match the application.

Standard Gundrill Head Profiles

Drilling capacity and finish of the drilled hole are dependent on the geometrical shape of the drill head. Both the profile and the sharpening must be matched to the workpiece material. The profile is defined when the tool is manufactured. Although regrounding may change the cutting geometry, the profile should remain the same.

General Sketch




All cross section profile parameters such as: P, La and must be precisely matched to the workpiece material properties.

Profile G (Universal)




Standard form for most material types, particularly for materials with a tendency to shrink. Recommended for high precision bore tolerance and straightness. Maintains precise exit hole size. Recommended when extra burnishing is required.

Profile A




Suitable for cast iron (usually coated) and aluminum alloys. Can be used for cross drilling, angular entry or exit and for interrupted cut. Large coolant gaps between pads.

Profile B




Excellent size control, for high precision hole tolerance. Used for cast iron and aluminum alloys.

Profile C




Used for angled entry or exit. Large back taper, for shrinking materials such as high temperature and titanium alloys and stainless steel. Large coolant gaps between pads.

Profile D




Suitable for cast iron only. Very effective in grey cast iron (usually coated).

Profile E




General use, for alloys and stainless steel. This profile eliminates the problem of the tool sticking in the hole after the outer corner dulls. Especially suitable for crankshaft and other forged materials. Recommended for accurate hole straightness.

Profile H



Recommended for all nonferrous and cast iron materials up to 5 mm diameter. Sometimes used for wood and plastic with larger back taper.

Profile I









Used for aluminum and brass for best hole finish. For intersecting holes and interrupted cut or when extra outer diameter support and burnishing is required.












Standard Gundrill Drivers for Machining Centers, Lathes

Drivers


Drivers are available for dedicated and CNC machines for any specified diameter and length.
Below are the driver codes and technical data.

Driver Type	Drawing	DXL	Driver code				
				BRAZED GUNDRILL		SOLID CARBIDE GUNDRILL	
				Max. cutting diameter	F = CYLINDRICAL TUBE		F = Straightening extension
					Equal or less than max. cutting diameter	More than max. diameter	
Cylindrical DIN1835A DIN6535HA		4x28	N°1	2.749	10	20	18
		5x28	N°2	3.249	10	20	15
		6x36	N°3	4.249	10	20	14
		8x36	N°4	5.749	10	20	14
		10x40	N°5	7.299	10	20	15
		12x45	N°6	8.999	10	20	15
		.50x1.78"	N°94	9.699	10	20	15
		14x45	N°7	10.999	10	20	15
		16x48	N°8	12.399	10	20	15
		18x48	N°9	14.399	10	20	15
		.75x2.03"	N°95	14.899	10	20	15
		20x50	N°10	15.899	10	20	
		25x56	N°11	19.509	10	25	
		1.00x2.28"	N°96	19.509	10	25	
		1.25x2.28"	N°97	25.609	10	25	
		32x60	N°12	25.609	10	25	
		40x70	N°13	32.609	10	25	
		50x80	N°14	40	10	25	
		63x90	N°15	40	10	25	
Weldon DIN1835B DIN6535HB	 	6x36	N°16	2.749	10	20	15
		8x36	N°17	3.249	10	20	15
		10x40	N°18	7.299	10	20	15
		12x45	N°19	8.999	10	20	15
		.50x1.78"	N°98	9.699	10	20	15
		16x48	N°20	12.399	10	20	15
		18x48	N°21	14.399	10	20	15
		.75x2.03"	N°99	14.899	10	20	15
		20x50	N°22	15.899	10	20	15
		25x56	N°23	19.509	10	25	
		1.00x2.28"	N°100	19.509	10	25	
		1.25x2.28"	N°101	25.609	10	25	
		32x60	N°24	25.609	10	25	
		40x70	N°25	32.609	10	25	
		50x80	N°26	40	10	25	
		63x90	N°27	40	10	25	
Whistle Notch DIN1835E		6x36	N°28	2.749	10	20	
		8x36	N°29	3.249	10	20	
		10x40	N°30	7.299	10	20	15
		12x45	N°31	8.999	10	20	15
		16x48	N°32	12.399	10	20	15
		18x48	N°33	14.399	10	20	15
		20x50	N°34	15.899	10	20	15
		25x56	N°35	19.509	10	25	
		32x60	N°36	25.609	10	25	
		40x70	N°37	32.609	10	25	
Whistle Notch DIN6535HE		6x36	N°38	2.749	10	20	15
		8x36	N°39	3.249	10	20	15
		10x40	N°40	7.299	10	20	15
		12x45	N°41	8.999	10	20	15
		16x48	N°42	12.399	10	20	15
		18x48	N°43	14.399	10	20	15
		20x50	N°44	15.899	10	20	15


Standard Drivers for Gundrill Machines

Driver Type	Drawing	DXL	Driver code				
				BRAZED GUNDRILL			SOLID CARBIDE GUNDRILL
				Max. cutting diameter	F = CYLINDRICAL TUBE Equal or less than max. cutting diameter	More than max. diameter	
DIN228AK		CM1	N°45	9.599	10	20	
		CM2	N°46	14.599	10	20	
		CM3	N°47	21.499	10	25	
		CM4	N°48	29.499	10	25	
DIN228BK		CM1	N°49	9.599	10	20	
		CM2	N°50	14.599	10	20	
		CM3	N°51	21.499	10	25	
		CM4	N°52	29.499	10	25	
Central Clamping Surface 15°		6x30	N°53	2.749	10	20	20
		10x40	N°54	7.299	10	20	15
		16x45	N°55	12.399	10	20	
		.750x2.75"	N°56	14.899	10	20	
		25x70	N°57	19.509	10	25	
		1.00x2.75"	N°58	19.509	10	25	
		1.25x2.75"	N°59	25.609	10	25	
Frontal Clamping Surface 15°		16x50	N°61	12.399	10	20	
Cylindrical with Thread		10x50 M6X0.5	N°62	7.299	10	20	15
		10x60 M6X0.5	N°63	7.299	10	20	
		.50x1.97" M6x0.5	N°64	8.999	10	20	15
		16x80 M10X1	N°65	12.399	10	20	15
		25x100 M16x1.5	N°66	19.509	10	25	
		36x120 M24x1.5	N°67	30.609	10	25	
VDI Design		10x68 M6x0.5	N°68	6.749	10	20	
		16x90 M10x1	N°69	10.799	10	20	15
		25x112 M16x1.5	N°70	19.509	10	25	
		36x135 M24x1.5	N°71	30.609	10	25	
Central Clamping Hexagonal		25x70	N°72	19.509	10	25	
		32x70	N°73	25.609	10	25	
Central Clamping Tapered		.50x1.50"	N°74	8.599	10	20	15
		16x70	N°75	12.099	10	20	15
		.75x2.75"	N°76	14.099	10	20	
		20x70	N°77	16.099	10	20	15
Frontal Clamping Surface 2°		.50x1.50"	N°78	9.699	10	20	
		.75x2.75"	N°79	14.899	10	20	
		1.00x2.75"	N°80	19.509	10	25	
		1.00x3.94"	N°81	19.509	10	25	
		1.25x2.75"	N°82	25.609	10	25	
		1.25x3.94"	N°83	25.609	10	25	
		1.50x2.75"	N°84	32.609	10	25	
Trapezoidal Thread		16x112 Tr 16x1.5	N°86	13.599	10	20	
		20x126 Tr 20x2	N°87	17.099	10	20	
		28x126 Tr 28x2	N°88	25.599	10	25	
		36x162 Tr 36x2	N°89	32.599	10	25	
Spraymist Driver		16x40	N°90	12.399	10	20	
		25x50	N°91	19.509	10	25	
		35x60	N°92	26.599	10	25	

Standard Gundrill Length Calculations



Standard Gundrill Carbide Head Length



- D= cutting diameter
- H= carbide length
- N= regrinding area = $H-D$
- W= hole depth
- B= chip evacuation area = For typical gundrill machines, 250 mm
= for machining centers, $2xD$ (minimum 15 mm)
- F= 10 mm.
- LA = driver length
- LS = flute length
- L= overall length

Example

Drilling of a $\varnothing 10 \times 500$ depth hole on a gundrill machine with $\varnothing 25 \times 70$ mm driver code No. 57 (See page 129)
 $D=10$ $W=500$ $LA=70$ $B=250$ (or per experience)
 $L=N+W+B+F+LA$
 $L=(35-10)+500+250+13+70=858$ (OAL)
 $LS=N+W+B=770$ (flute length)


Ordering Code

For example:
D and Ls are available as standard
STGD-10000-0858-57-IC08

Diameter Range	Head Length
2.50-3.80	20
3.80-4.05	23
4.05-5.05	25
5.05-6.55	30
6.55-11.05	35
11.05-18.35	40
18.35-21.35	45
21.35-23.35	50
23.35-26.35	55
26.35-32.00	65

Note: regrindable length= $H-D$

Pressure and Coolant Flow Rate for Gundrills



■ Q l/min ■ P bar

Gundrill Lubrication and Cooling

The best performance is obtained by using oil. On equipment that uses water-soluble fluids (i.e. machining centers and CNC machines), a concentration between 10% and 15% is recommended.


Guidelines for Optimal Gundrill Performance

- It is recommended to use a strong coolant flow for efficient chip flushing and cooling of the cutting edge.
- It is recommended to use a filter under $20 \mu m$.
- Note: Improper filtration may result in interrupted flow of lubricating oil. This creates a sticky surface on the bearing pads and leads to premature wear of the tool and overloading the coolant pump and spindle seals.
- The coolant temperature should be between 20 and 22° C.
Note: Above 50° C the viscosity of the coolant is reduced by 50% and becomes ineffective.

Drilling Tolerances Obtainable In Deep Hole Drilling


Deep Drilling Tolerances

Gundrill configurations when used under recommended conditions can produce holes with tolerances of IT8-IT9. When operating under optimal conditions, even better tolerances can be achieved.



Surface Quality


Surface quality of 0.2 Ra can be achieved when using gundrills under recommended conditions.



Concentricity and Straightness

The resulting quality depends on different factors such as:


- Drilling depth and diameter
- Type of machining and cutting parameters
- Quality and uniformity of the workpiece material
- Machine tool conditions
- Gundrill support



■ stationary workpiece – rotating tool
■ rotating workpiece – stationary tool

Circularity

The geometric quality of bores obtained from deep hole drill bits is clearly higher than that obtained with the use of twist drills. It is possible to obtain precision with deviations of less than 4 μm .



Drilling Depth




Gundrill Inquiry Form

1. Tool

Quantity _____

Nominal diameter and tolerance _____

Please fill in dimensions on the sketch below.




Driver

For standard drivers please use codes from page 128

☐ Code No.

☐ Special, please attach sketch and specifications.

 Grind: ☐ special (fill in the dimensions and angles below).

 $\alpha_1 =$ _____ $\alpha F_1 =$ _____ $\psi_1 =$ _____

 $\alpha_2 =$ _____ $bF_1 =$ _____ $\psi_2 =$ _____

 $\alpha_3 =$ _____ $as =$ _____ $\gamma =$ _____


☐ Standard (see page 126)

Coating:

- ☐ TiN ☐ TiCN ☐ TiN+TiCN ☐ Other
☐ IC208 (TiN) ☐ IC308 (TiCN) ☐ IC508 (TiCN+TiN)
☐ IC908 (TiAlN) ☐ TiAlN

Type:

Please circle the required type. See page 127.



2. Workpiece

(If possible, please attach a drawing)

2.1 Material

Material description (DIN material number or any other standard): _____

Hardness and Properties: _____

- ☐ Short Chips ☐ Long Chips

2.2 Hole Type

- ☐ Blind Hole ☐ Drilling into Pre-hole

- ☐ Angled Entry ☐ Drilling into Solid

- ☐ Boring ☐ Angled Exit

Drilling Depth _____ mm Hole Tolerance _____

2.3 Application:

 Workpiece: ☐ Stationary ☐ Rotating

 Tool: ☐ Stationary ☐ Rotating

3. Machine

3.1 Technical Data

Machine Type: _____

Power _____ kW

3.2 Cutting Data:

 Cutting Speed V_c _____ m/min

 Revolutions N_{min} _____ RPM, N_{max} _____ RPM

 Feed F_{min} _____ mm/rev,

 F_{max} _____ mm/rev

 Feed Rate V_F _____ mm/min

Coolant:

- ☐ Oil ☐ Soluble Oil ☐ Other

Coolant Pressure _____ Bar

Sketch of drilling application



Note: It may be necessary to change several of the parameters that you indicated based on our experience with your application.

Typical Gundrill Applications - Main Drilling Methods




Figure 1




Figure 2

User Guide

The gundrill is not a self-centering tool. Therefore, an external means must be used to guide it to the point of entry into the workpiece. It is recommended that the machine tool be equipped with a means for guiding the gundrill, preferably during the entire drilling process.

An alternative method is a pre-drilled guide hole (figure 2), which is common for machining centers. Once the drill has been fully engaged into this hole, it continues to be self-guided.

The guide pads contribute to the high degree of accuracy and provide burnishing of the drilled hole.

Typical Gundrill Applications - Chip Evacuation and Coolant Flow




Figure 3

Boring with chip evacuation and coolant flowing opposite the boring direction




Figure 4

Drilling of solid material with chip evacuation and coolant flow opposite the drilling direction




Figure 5

Boring with chip evacuation in the boring direction





Figure 6


Boring with a staged tool chip evacuation and coolant flow in the boring direction

Deep Hole Machine Accessories



Bushing

Based on modified DIN 179 specify the "d" diameter of the drill. Carbide bushing is delivered only on request.




$d = \text{Drill diameter} + 0.02$

Guide Bushings

As the gundrill is not a self-centering tool and its radial rigidity is low (due to diameter to length ratio), a guide bushing is an essential component for a proper gundrill operation. The function of the guide bushing is to direct the gundrill into the material during penetration. The diameter of the guide bushing should be within 20 microns larger than the diameter of the drill. Dedicated gundrill machines are equipped with a guide bushing system.

Sealing Disk

Supplied with a single sealing disk or a protection sheet. Indicate the dimensions needed for your requirements.



Sealing Disk


Tool Ø "d"	Ext. Ø "D"	Thick. "B"
2 to 6	20	3
3,1 to 15,559	32	4
15,6 to 25,999	40	4
26 to 40	90	4

Sealing Disk with Protection

Tool Ø "d1"	Ext. Ø "D"	Thick. "B"
2,9 - 5,249	20	7
5,25 - 14,449	32	11
14,45 - 25,999	40	12
26 - 41	90	12

Support Bushing

Indicate the "d" diameter of the drill.




Support Bushing

Tool Ø "d1"	Ext. Ø "D"	Ext. Ø "D1"	Length "L"	Length "L1"
1,9 - 16,399	20	26	20	12
1,9 - 25,999	30	38	26	16
1,9 - 34	45	50	26	16

Support Bushing with "V" Form

Indicate the "d" diameter of the drill.



Support Bushing with "V" Form

Tool Ø "d1"	Ext. Ø "D"	Ext. Ø "D1"	Length "L"	Length "L1"
1,9 - 16,399	20	26	20	12
1,9 - 23,799	30	38	26	16

Gundrill Recommended Machining Conditions

ISO	Material	Condition	Tensile Strength [N/mm ²]	Hardness HB	Material Group No. ⁽¹⁾
P	<0.25% C	annealed	420	125	1
	≥0.25% C	annealed	650	190	2
	non-alloy steel and cast steel, free cutting steel	<0.55% C	quenched and tempered	850	3
		≥0.55% C	annealed	750	4
	low alloy and cast steel (less than 5% of alloying elements)	quenched and tempered	1000	300	5
			600	200	6
		quenched and tempered	930	275	7
			1000	300	8
	high alloyed steel, cast steel and tool steel	annealed	1200	350	9
		quenched and tempered	680	200	10
	stainless steel and cast steel	annealed	1100	325	11
		ferritic/martensitic	680	200	12
		martensitic	820	240	13
M	stainless steel and cast steel	austenitic, duplex	600	180	14
K	grey cast iron (GG)	ferritic/pearlitic		180	15
		pearlitic/martensitic		260	16
	nodular cast iron (GGG)	ferritic		160	17
		pearlitic		250	18
	malleable cast iron	ferritic		130	19
		pearlitic		230	20
N	aluminum-wrought alloys	not hardenable		60	21
		hardenable		100	22
	aluminum-cast alloys	≤12% Si	not hardenable	75	23
		>12% Si	hardenable	90	24
	copper alloys	>1% Pb	high temperature	130	25
		free cutting		110	26
		brass		90	27
		electrolitic copper		100	28
	non-metallic	duroplastics, fiber plastics			29
		hard rubber			30
S	high temp. alloys	Fe based	annealed	200	31
		Ni or Co based	hardened	280	32
			annealed	250	33
			hardened	350	34
	titanium alloys	cast		320	35
		pure	400		36
		alpha+beta alloys hardened	1050		37
H	hardened steel	hardened		55 HRC	38
		hardened		60 HRC	39
	chilled cast iron	cast		400	40
	cast iron	hardened		55 HRC	41


(1) Based on ISO 513 and VDI 3323 standards

Cutting Speed V _c (m/min)	Feed (mm/rev) vs. Drill Diameter (mm)					
	Ø2.5-4	Ø4-6	Ø6-10	Ø10-15	Ø15-30	Ø30 and more
70-100	0.0033-0.012 / 0.0089-0.024	0.0089-0.024 / 0.015-0.039	0.015-0.039 / 0.025-0.071	0.025-0.071 / 0.037-0.11	0.037-0.11 / 0.055-0.19	0.061-0.23
60-80	0.0025-0.0094 / 0.0056-0.021	0.0056-0.021 / 0.011-0.036	0.011-0.036 / 0.023-0.063	0.023-0.063 / 0.034-0.097	0.034-0.097 / 0.063-0.16	0.078-0.2
60-80	0.0025-0.0094 / 0.0056-0.021	0.0056-0.021 / 0.011-0.036	0.011-0.036 / 0.023-0.063	0.023-0.063 / 0.034-0.097	0.034-0.097 / 0.063-0.16	0.078-0.2
40-60						
40-60	0.0038-0.0064 / 0.008-0.016	0.008-0.016 / 0.014-0.028	0.014-0.028 / 0.026-0.053	0.026-0.053 / 0.042-0.084	0.042-0.084 / 0.087-0.15	0.11-0.18
40-60	0.0038-0.0064 / 0.008-0.016	0.008-0.016 / 0.014-0.028	0.014-0.028 / 0.026-0.053	0.026-0.053 / 0.042-0.084	0.042-0.084 / 0.087-0.15	0.11-0.18
70-100	0.0034-0.013 / 0.0092-0.031	0.0092-0.031 / 0.017-0.056	0.017-0.056 / 0.031-0.1	0.031-0.1 / 0.045-0.16	0.045-0.16 / 0.076-0.24	0.092-0.29
100-150	0.0029-0.037 / 0.011-0.12	0.011-0.12 / 0.019-0.22	0.019-0.22 / 0.042-0.4	0.042-0.4 / 0.067-0.6	0.067-0.6 / 0.11-0.9	0.14-1
80-120	0.0041-0.013 / 0.008-0.029	0.008-0.029 / 0.012-0.057	0.012-0.057 / 0.023-0.1	0.023-0.1 / 0.035-0.16	0.035-0.16 / 0.063-0.25	0.078-0.3
40-60	0.0019-0.0022 / 0.0052-0.0056	0.0052-0.0056 / 0.012-0.013	0.012-0.013 / 0.024-0.027	0.024-0.027 / 0.036-0.043	0.036-0.043 / 0.065-0.076	0.079-0.093
25-50	0.0019-0.0022 / 0.0052-0.0056	0.0052-0.0056 / 0.012-0.013	0.012-0.013 / 0.024-0.027	0.024-0.027 / 0.036-0.043	0.036-0.043 / 0.065-0.076	0.079-0.093
25-50	0.0019-0.0022 / 0.0052-0.0056	0.0052-0.0056 / 0.012-0.013	0.012-0.013 / 0.024-0.027	0.024-0.027 / 0.036-0.043	0.036-0.043 / 0.065-0.076	0.079-0.093

Gundrill Troubleshooting Guide

Hole Problems	Possible Causes																							
	Poor clamping	Insufficient coolant flow	Low coolant pressure	Incorrect coolant type	Feed fluctuations	Too high feed	Too low feed	Spindle speed too high	Spindle speed too low	Material structure	Material shrinking due to heat	Workpiece thin wall section	Misalignment	Undersized hole	Rough cutting edge finish	Built up edge	Worn out edge	Interrupted chip flow	Too small flute clearance	Incorrect drill profile	Incorrect head angles	Vibrations	Oversized bushing	A gap between bushing and workpiece
Oversize	+	+				+							+			+		+		+	+	+	+	+
Undersize			+							+										+	+		+	+
Rough surface finish		+	+	+	+	+			+	+	+		+		+	+	+		+	+	+	+	+	+
Runout	+				+	+			+	+	+	+	+		+		+	+	+	+	+	+	+	+
Conical entrance					+															+	+	+	+	+
Curved hole axis	+				+	+				+	+	+	+		+		+	+	+	+	+	+	+	+

Drill Problems																									
Breakage	+	+	+		+	+		+		+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Chipping					+		+			+					+		+		+	+					+
Poor drill life		+	+	+	+	+	+	+		+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
Excessive margin wear	+			+				+					+	+			+	+	+	+		+		+	+
Excessive corner wear				+				+		+	+				+	+	+		+	+	+		+	+	+
Excessive flank wear		+	+		+		+	+					+	+			+	+		+	+		+	+	+
Drill heat		+			+		+	+		+			+	+				+	+			+	+	+	+
Flute bending					+	+		+					+				+		+	+	+		+	+	+
Damaged wear pad				+			+		+	+			+	+			+	+	+	+	+		+	+	+
Built-up edge				+	+	+	+		+	+					+		+		+	+	+		+	+	+
Cratering				+		+			+	+					+		+		+	+	+		+	+	+



SOLID CARBIDE DRILLS






SOLIDDRILL

SCD-SXC16

Solid Carbide Drills with
Internal Coolant Channels,
Drilling Depth 16xD



Designation	Dimensions								IC908
	DC	DCONMS	OAL	LU	LCF	LS	PL	ULDR ⁽¹⁾	
SCD 030-055-060 SXC16	3.00	6.00	100.00	55.00	60.0	36.0	0.495	16.0	●
SCD 032-055-060 SXC16	3.20	6.00	100.00	55.00	60.0	36.0	0.528	16.0	●
SCD 033-055-060 SXC16	3.30	6.00	100.00	55.00	60.0	36.0	0.545	16.0	●
SCD 035-054-060 SXC16	3.50	6.00	100.00	54.00	60.0	36.0	0.578	16.0	●
SCD 038-069-060 SXC16	3.80	6.00	115.00	69.00	75.0	36.0	0.627	16.0	●
SCD 040-069-060 SXC16	4.00	6.00	115.00	69.00	75.0	36.0	0.660	16.0	●
SCD 042-068-060 SXC16	4.20	6.00	115.00	68.00	75.0	36.0	0.693	16.0	●
SCD 045-083-060 SXC16	4.50	6.00	130.00	83.00	90.0	36.0	0.743	16.0	●
SCD 047-082-060 SXC16	4.70	6.00	130.00	82.00	90.0	36.0	0.776	16.0	●
SCD 048-082-060 SXC16	4.80	6.00	130.00	82.00	90.0	36.0	0.792	16.0	●
SCD 050-082-060 SXC16	5.00	6.00	130.00	82.00	90.0	36.0	0.825	16.0	●
SCD 055-099-060 SXC16	5.50	6.00	150.00	99.00	108.0	36.0	0.908	16.0	●
SCD 058-099-060 SXC16	5.80	6.00	150.00	99.00	108.0	36.0	0.957	16.0	●
SCD 060-099-060 SXC16	6.00	6.00	150.00	99.00	108.0	36.0	0.990	16.0	●
SCD 065-115-080 SXC16	6.50	8.00	165.00	115.00	125.0	36.0	1.073	16.0	●
SCD 068-114-080 SXC16	6.80	8.00	165.00	114.00	125.0	36.0	1.122	16.0	●
SCD 070-114-080 SXC16	7.00	8.00	165.00	114.00	125.0	36.0	1.155	16.0	●
SCD 075-128-080 SXC16	7.50	8.00	180.00	128.00	140.0	36.0	1.238	16.0	●
SCD 078-128-080 SXC16	7.80	8.00	180.00	128.00	140.0	36.0	1.287	16.0	●
SCD 080-128-080 SXC16	8.00	8.00	180.00	128.00	140.0	36.0	1.320	16.0	●
SCD 085-147-100 SXC16	8.50	10.00	205.00	147.00	160.0	40.0	1.403	16.0	●
SCD 088-146-100 SXC16	8.80	10.00	205.00	146.00	160.0	40.0	1.452	16.0	●
SCD 090-146-100 SXC16	9.00	10.00	205.00	146.00	160.0	40.0	1.485	16.0	●
SCD 098-165-100 SXC16	9.80	10.00	225.00	165.00	180.0	40.0	1.617	16.0	●
SCD 100-165-100 SXC16	10.00	10.00	225.00	165.00	180.0	40.0	1.650	16.0	●
SCD 102-174-120 SXC16	10.20	12.00	240.00	174.00	190.0	45.0	1.683	16.0	●
SCD 108-173-120 SXC16	10.80	12.00	240.00	173.00	190.0	45.0	1.782	16.0	●
SCD 110-173-120 SXC16	11.00	12.00	240.00	173.00	190.0	45.0	1.815	16.0	●
SCD 115-197-120 SXC16	11.50	12.00	265.00	197.00	215.0	45.0	1.898	16.0	●
SCD 120-197-120 SXC16	12.00	12.00	265.00	197.00	215.0	45.0	1.980	16.0	●
SCD 123-211-140 SXC16	12.30	14.00	280.00	211.00	230.0	45.0	2.030	16.0	●
SCD 130-210-140 SXC16	13.00	14.00	280.00	210.00	230.0	45.0	2.145	16.0	●
SCD 133-225-140 SXC16	13.30	14.00	295.00	225.00	245.0	45.0	2.195	16.0	●
SCD 135-224-140 SXC16	13.50	14.00	295.00	224.00	245.0	45.0	2.228	16.0	●
SCD 140-224-140 SXC16	14.00	14.00	295.00	224.00	245.0	45.0	2.310	16.0	●
SCD 145-233-160 SXC16	14.50	16.00	305.00	233.00	255.0	48.0	2.393	16.0	●
SCD 150-232-160 SXC16	15.00	16.00	305.00	232.00	255.0	48.0	2.475	16.0	●
SCD 155-251-160 SXC16	15.50	16.00	325.00	251.00	275.0	48.0	2.558	16.0	●
SCD 160-251-160 SXC16	16.00	16.00	325.00	251.00	275.0	48.0	2.640	16.0	●
SCD 165-295-180 SXC16	16.50	18.00	370.00	295.00	320.0	48.0	2.723	16.0	●
SCD 170-294-180 SXC16	17.00	18.00	370.00	294.00	320.0	48.0	2.805	16.0	●
SCD 175-293-180 SXC16	17.50	18.00	370.00	293.00	320.0	48.0	2.888	16.0	●
SCD 180-293-180 SXC16	18.00	18.00	370.00	293.00	320.0	48.0	2.970	16.0	●
SCD 185-302-200 SXC16	18.50	20.00	380.00	302.00	330.0	50.0	3.053	16.0	●
SCD 195-320-200 SXC16	19.50	20.00	400.00	320.00	350.0	50.0	3.218	16.0	●
SCD 200-320-200 SXC16	20.00	20.00	400.00	320.00	350.0	50.0	3.300	16.0	●


• For user guide and cutting conditions, see page 142

⁽¹⁾ Usable length diameter ratio

SOLIDDRILL

SCD-SXC20

Solid Carbide Drills with
Internal Coolant Channels,
Drilling Depth 20xD



Designation	Dimensions								IC908
	DC	DCONMS	OAL	LU	LCF	LS	PL	ULDR ⁽¹⁾	
SCD 030-075-060 SXC20	3.00	6.00	120.00	75.00	80.0	36.0	0.495	20.0	●
SCD 032-075-060 SXC20	3.20	6.00	120.00	75.00	80.0	36.0	0.528	20.0	●
SCD 033-075-060 SXC20	3.30	6.00	120.00	75.00	80.0	36.0	0.545	20.0	●
SCD 035-074-060 SXC20	3.50	6.00	120.00	74.00	80.0	36.0	0.578	20.0	●
SCD 038-084-060 SXC20	3.80	6.00	130.00	84.00	90.0	36.0	0.627	20.0	●
SCD 040-084-060 SXC20	4.00	6.00	130.00	84.00	90.0	36.0	0.660	20.0	●
SCD 042-103-060 SXC20	4.20	6.00	160.00	103.00	110.0	36.0	0.693	20.0	●
SCD 045-103-060 SXC20	4.50	6.00	160.00	103.00	110.0	36.0	0.743	20.0	●
SCD 047-112-060 SXC20	4.70	6.00	160.00	112.00	120.0	36.0	0.776	20.0	●
SCD 048-112-060 SXC20	4.80	6.00	160.00	112.00	120.0	36.0	0.792	20.0	●
SCD 050-112-060 SXC20	5.00	6.00	160.00	112.00	120.0	36.0	0.825	20.0	●
SCD 055-131-060 SXC20	5.50	6.00	185.00	131.00	140.0	36.0	0.908	20.0	●
SCD 058-131-060 SXC20	5.80	6.00	185.00	131.00	140.0	36.0	0.957	20.0	●
SCD 060-131-060 SXC20	6.00	6.00	185.00	131.00	140.0	36.0	0.990	20.0	●
SCD 065-150-080 SXC20	6.50	8.00	210.00	150.00	160.0	36.0	1.073	20.0	●
SCD 068-149-080 SXC20	6.80	8.00	210.00	149.00	160.0	36.0	1.122	20.0	●
SCD 070-149-080 SXC20	7.00	8.00	210.00	149.00	160.0	36.0	1.155	20.0	●
SCD 075-168-080 SXC20	7.50	8.00	230.00	168.00	180.0	36.0	1.238	20.0	●
SCD 078-168-080 SXC20	7.80	8.00	230.00	168.00	180.0	36.0	1.287	20.0	●
SCD 080-168-080 SXC20	8.00	8.00	230.00	168.00	180.0	36.0	1.320	20.0	●
SCD 085-182-100 SXC20	8.50	10.00	260.00	182.00	195.0	40.0	1.403	20.0	●
SCD 088-216-100 SXC20	8.80	10.00	290.00	216.00	230.0	40.0	1.452	20.0	●
SCD 090-216-100 SXC20	9.00	10.00	290.00	216.00	230.0	40.0	1.485	20.0	●
SCD 098-215-100 SXC20	9.80	10.00	290.00	215.00	230.0	40.0	1.617	20.0	●
SCD 100-215-100 SXC20	10.00	10.00	290.00	215.00	230.0	40.0	1.650	20.0	●
SCD 102-252-120 SXC20	10.20	12.00	315.00	252.00	268.0	45.0	1.683	20.0	●
SCD 108-251-120 SXC20	10.80	12.00	315.00	251.00	268.0	45.0	1.782	20.0	●
SCD 110-251-120 SXC20	11.00	12.00	315.00	251.00	268.0	45.0	1.815	20.0	●
SCD 115-250-120 SXC20	11.50	12.00	315.00	250.00	268.0	45.0	1.898	20.0	●
SCD 120-250-120 SXC20	12.00	12.00	315.00	250.00	268.0	45.0	1.980	20.0	●
SCD 123-261-140 SXC20	12.30	14.00	325.00	261.00	280.0	45.0	2.030	20.0	●
SCD 130-260-140 SXC20	13.00	14.00	325.00	260.00	280.0	45.0	2.145	20.0	●
SCD 133-285-140 SXC20	13.30	14.00	355.00	285.00	305.0	45.0	2.195	20.0	●
SCD 135-284-140 SXC20	13.50	14.00	355.00	284.00	305.0	45.0	2.228	20.0	●
SCD 140-284-140 SXC20	14.00	14.00	355.00	284.00	305.0	45.0	2.310	20.0	●
SCD 145-298-160 SXC20	14.50	16.00	370.00	298.00	320.0	48.0	2.393	20.0	●
SCD 150-297-160 SXC20	15.00	16.00	370.00	297.00	320.0	48.0	2.475	20.0	●
SCD 155-326-160 SXC20	15.50	16.00	400.00	326.00	350.0	48.0	2.558	20.0	●
SCD 160-326-160 SXC20	16.00	16.00	400.00	326.00	350.0	48.0	2.640	20.0	●

• For user guide and cutting conditions, see page 142

⁽¹⁾ Usable length diameter ratio

Recommended Machining Conditions for SCD-SXC16 & SCD-SXC20 Solid Carbide Drills

ISO	Material	Condition	Material Group No.	Tensile Strength [N/mm ²]	Hardness HB	Cutting Speed V _c (m/min)	Cutting Diameter				
							Feed (mm/rev)				
							3.0-5.0	5.1-8.0	8.1-10.0	10.1-16	16.1-20
P	non-alloy steel and cast steel, free cutting steel	<0.25% C	1	420	125	70-90	0.1-0.18	0.14-0.24	0.16-0.26	0.18-0.3	0.2-0.35
		≥0.25% C	2	650	190						
		<0.55% C	3	850	250						
		≥0.55% C	4	750	220						
		quenched and tempered	5	1000	300						
	low alloy and cast steel (less than 5% of alloying elements)	annealed	6	600	200	75-85	0.1-0.18	0.14-0.24	0.16-0.26	0.18-0.3	0.2-0.35
		quenched and tempered	7	930	275						
		quenched and tempered	8	1000	300						
		quenched and tempered	9	1200	350						
	high alloyed steel, cast steel and tool steel	annealed	10	680	200	75-85	0.1-0.18	0.14-0.24	0.16-0.26	0.18-0.3	0.2-0.35
		quenched and tempered	11	1100	325						
	stainless steel and cast steel	ferritic/martensitic	12	680	200	60-70	0.08-0.14	0.1-0.18	0.12-0.2	0.14-0.22	0.16-0.24
		martensitic	13	820	240						
M	stainless steel and cast steel	austenitic, duplex	14	600	180	55-65	0.06-0.14	0.08-0.16	0.1-0.18	0.12-0.2	0.14-0.24
K	gray cast iron (GG)	ferritic / pearlitic	15		180	80-100	0.14-0.24	0.16-0.26	0.18-0.0.3	0.2-0.35	0.25-0.45
		pearlitic / martensitic	16		260						
	nodular cast iron (GGG)	ferritic	17		160						
		pearlitic	18		250						
	malleable cast iron	ferritic	19		130						
		pearlitic	20		230						
S	high temperature alloys	Fe based	31		200	35-45	0.06-0.12	0.08-0.16	0.1-0.18	0.12-0.2	0.12-0.22
			32		280	35-45	0.06-0.12	0.08-0.16	0.1-0.18	0.12-0.2	0.12-0.22
		Ni or Co based	33		250	30-40	0.06-0.12	0.08-0.16	0.1-0.18	0.12-0.2	0.12-0.22
			34		350	30-40	0.06-0.12	0.08-0.16	0.1-0.18	0.12-0.2	0.12-0.22
			35		320	30-40	0.06-0.12	0.08-0.16	0.1-0.18	0.12-0.2	0.12-0.22
	titanium alloys	pure	36	RM 400	190	35-45	0.06-0.12	0.08-0.16	0.1-0.18	0.12-0.2	0.12-0.22
		alpha+beta alloys, hardened	37	RM 1050	310	35-45	0.06-0.12	0.08-0.16	0.1-0.18	0.12-0.2	0.12-0.22

TIPS & TRICKS for DEEP HOLE DRILLING

Using a G73 peck cycle helps Chip evacuation in deep hole drilling & materials which have a poor chip formation.

16xD - 50xD must utilize a Pilot hole drill.

40xD - 50xD can utilize a 20xD intermediary drill if deemed necessary.

TIR & tool alignment with material are the most important factors in deep hole Drilling.


Use high pressure coolant when deep hole drilling.

Slow the feedrate to 50% when breaking through the material.

In through holes, the tool exit should not exceed 2-3 mm.

Recommended Drilling Procedure for Deep Hole Drilling


- 1 Drill a pilot hole 1-2xD deep with a short drill. The pilot drill should be 0.03-0.05 mm larger than the long drill and its point angle should also be larger (over 135°).
- 2 Enter the pre-hole using low feed and rotate at low speed (50-100 RPM) to within 1 - 2 mm of pre-hole depth.
- 3 Activate the coolant system and increase rotation speed to the recommended cutting parameter, maintain for 2-3 seconds, then continue at recommended drilling feed. **No pecking is required.**
- 4 After having reached the required depth, reduce speed to 50-100 RPM before retracting from the hole.



SOLIDDRILL

SCD-SXC30

Solid Carbide Drills with
Internal Coolant Channels,
Drilling Depth 30xD



Designation	Dimensions								IC908
	DC	DCONMS	OAL	LU	LCF	LS	PL	ULDR ⁽²⁾	
SCD 030-097-060 SXC30	3.00	6.00	150.00	97.00	105.0	40.0	0.495	30.0	●
SCD 032-097-060 SXC30	3.20	6.00	150.00	97.00	105.0	40.0	0.528	30.0	●
SCD 033-127-060 SXC30	3.30	6.00	185.00	127.00	135.0	45.0	0.544	30.0	●
SCD 035-127-060 SXC30	3.50	6.00	185.00	127.00	135.0	45.0	0.578	30.0	●
SCD 038-127-060 SXC30 ⁽¹⁾	3.80	6.00	185.00	127.00	135.0	45.0	0.627	30.0	●
SCD 040-127-060 SXC30	4.00	6.00	185.00	127.00	135.0	45.0	0.660	30.0	●
SCD 042-127-060 SXC30	4.20	6.00	185.00	127.00	135.0	45.0	0.693	30.0	●
SCD 045-157-060 SXC30	4.50	6.00	215.00	157.00	165.0	45.0	0.743	30.0	●
SCD 047-157-060 SXC30 ⁽¹⁾	4.70	6.00	215.00	157.00	165.0	45.0	0.775	30.0	●
SCD 048-157-060 SXC30	4.80	6.00	215.00	157.00	165.0	45.0	0.792	30.0	●
SCD 050-157-060 SXC30	5.00	6.00	215.00	157.00	165.0	45.0	0.825	30.0	●
SCD 055-172-060 SXC30	5.50	6.00	230.00	172.00	180.0	45.0	0.907	30.0	●
SCD 058-172-060 SXC30 ⁽¹⁾	5.80	6.00	230.00	172.00	180.0	45.0	0.957	30.0	●
SCD 060-172-060 SXC30	6.00	6.00	230.00	172.00	180.0	45.0	0.990	30.0	●
SCD 065-207-080 SXC30	6.50	8.00	280.00	207.00	215.0	60.0	1.072	30.0	●
SCD 068-222-080 SXC30	6.80	8.00	280.00	222.00	230.0	45.0	1.122	30.0	●
SCD 070-222-080 SXC30	7.00	8.00	280.00	222.00	230.0	45.0	1.155	30.0	●
SCD 075-222-080 SXC30 ⁽¹⁾	7.50	8.00	280.00	222.00	230.0	45.0	1.238	30.0	●
SCD 078-257-080 SXC30 ⁽¹⁾	7.80	8.00	315.00	257.00	265.0	45.0	1.287	30.0	●
SCD 080-257-080 SXC30	8.00	8.00	315.00	257.00	265.0	45.0	1.320	30.0	●
SCD 085-287-100 SXC30	8.50	10.00	350.00	287.00	295.0	50.0	1.402	30.0	●
SCD 088-322-100 SXC30 ⁽¹⁾	8.80	10.00	380.00	322.00	330.0	45.0	1.452	30.0	●
SCD 090-322-100 SXC30	9.00	10.00	380.00	322.00	330.0	45.0	1.485	30.0	●
SCD 098-322-100 SXC30	9.80	10.00	380.00	322.00	330.0	45.0	1.617	30.0	●
SCD 100-322-100 SXC30	10.00	10.00	380.00	322.00	330.0	45.0	1.650	30.0	●

• For cutting conditions, see page 144

⁽¹⁾ On request

⁽²⁾ Usable length diameter ratio




Recommended Machining Conditions for SCD-SXC30 Solid Carbide Drills

ISO	Material	Condition	Tensile Strength [N/mm ²]	Hardness HB	Material No.	Cutting Speed V _c (m/min)	Cutting Diameter Feed (mm/rev)						
							3.0-5.0	5.0-8.0	8.0-10.0				
P	non-alloy steel and cast steel, free cutting steel	<0.25% C	annealed	420	125	1	65-75	0.08-0.16	0.12-0.2	0.16-0.24			
		≥0.25% C	annealed	650	190	2							
		<0.55% C	quenched and tempered	850	250	3							
		≥0.55% C	annealed	750	220	4							
			quenched and tempered	1000	300	5							
	low alloy steel and cast steel (less than 5% of alloying elements)	annealed	600	200	6								
		quenched and tempered		930	275	7							
				1000	300	8							
				1200	350	9							
	high alloyed steel, cast steel, and tool steel	annealed	680	200	10	60-70	45-55	0.06-0.12	0.08-0.16	0.1-0.18			
		quenched and tempered	1100	325	11								
	stainless steel and cast steel	ferritic/martensitic	680	200	12								
		martensitic	820	240	13								
M	stainless steel and cast steel	austenitic, duplex	600	180	14	35-45					0.06-0.12	0.08-0.16	0.1-0.18
K	grey cast iron (GG)	ferritic / pearlitic		180	15	75-85					0.14-0.22	0.18-0.30	0.22-0.40
		pearlitic / martensitic		260	16								
	cast iron nodular (GGG)	ferritic		160	17								
		pearlitic		250	18								
	malleable cast iron	ferritic		130	19								
		pearlitic		230	20								
S	high temperature alloys	Fe based	annealed		200	31	35-50	0.06-0.12	0.08-0.16	0.1-0.18			
			hardened		280	32							
		Ni or Co based	annealed		250	33	30-45	0.06-0.12	0.08-0.16	0.1-0.18			
			hardened		350	34							
			cast		320	35							
	titanium alloys	pure	400	190	36	35-50	0.06-0.12	0.08-0.16	0.1-0.18				
		alpha+beta alloys, hardened	1050	310	37								

SCD-SXC40

Solid Carbide Drills with
Internal Coolant Channels,
Drilling Depth 40xD



Designation	Dimensions								IC908
	DC	DCONMS	OAL	LU	LCF	LS	PL	ULDR ⁽²⁾	
SCD 030-132-060 SXC40	3.00	6.00	190.00	132.00	140.0	45.0	0.495	40.0	●
SCD 038-172-060 SXC40 ⁽¹⁾	3.80	6.00	230.00	172.00	180.0	45.0	0.627	40.0	●
SCD 040-172-060 SXC40	4.00	6.00	230.00	172.00	180.0	45.0	0.660	40.0	●
SCD 042-172-060 SXC40	4.20	6.00	230.00	172.00	180.0	45.0	0.693	40.0	●
SCD 045-212-060 SXC40	4.50	6.00	270.00	212.00	220.0	45.0	0.743	40.0	●
SCD 047-212-060 SXC40 ⁽¹⁾	4.70	6.00	270.00	212.00	220.0	45.0	0.775	40.0	●
SCD 048-212-060 SXC40	4.80	6.00	270.00	212.00	220.0	45.0	0.792	40.0	●
SCD 050-212-060 SXC40	5.00	6.00	270.00	212.00	220.0	45.0	0.825	40.0	●
SCD 055-232-060 SXC40	5.50	6.00	290.00	232.00	240.0	45.0	0.907	40.0	●
SCD 058-232-060 SXC40 ⁽¹⁾	5.80	6.00	290.00	232.00	240.0	45.0	0.957	40.0	●
SCD 060-232-060 SXC40	6.00	6.00	290.00	232.00	240.0	45.0	0.990	40.0	●
SCD 065-282-080 SXC40	6.50	8.00	340.00	282.00	290.0	45.0	1.072	40.0	●
SCD 068-312-080 SXC40	6.80	8.00	370.00	312.00	320.0	45.0	1.122	40.0	●
SCD 070-312-080 SXC40	7.00	8.00	370.00	312.00	320.0	45.0	1.155	40.0	●
SCD 075-312-080 SXC40 ⁽¹⁾	7.50	8.00	370.00	312.00	320.0	45.0	1.238	40.0	●
SCD 078-342-080 SXC40 ⁽¹⁾	7.80	8.00	400.00	342.00	350.0	45.0	1.287	40.0	●
SCD 080-342-080 SXC40	8.00	8.00	400.00	342.00	350.0	45.0	1.320	40.0	●

• For user guide and cutting conditions, see pages 145-146

⁽¹⁾ On request

⁽²⁾ Usable length diameter ratio

Recommended Machining Conditions for SCD-SXC40 & SCD-SXC50 Solid Carbide Drills


ISO	Material	Condition	Tensile Strength [N/mm²]	Hardness HB	Material No.	Cutting Speed V _c (m/min)	Cutting Diameter Feed (mm/rev)					
							3.0-4.0	4.1-5.0	5.1-6.0	6.1-7.0	7.1-8.0	
P	non-alloy steel and cast steel, free cutting steel	<0.25% C annealed	420	125	1	55-65	0.06-0.12	0.06-0.14	0.08-0.16	0.10-0.18	0.12-0.2	
		≥0.25% C annealed	650	190	2							
		<0.55% C quenched and tempered	850	250	3							
		annealed	750	220	4							
		≥0.55% C quenched and tempered	1000	300	5							
	low alloy steel and cast steel (less than 5% of alloying elements)	annealed	600	200	6	45-65	0.06-0.10	0.06-0.12	0.08-0.14	0.10-0.16	0.12-0.18	
		quenched and tempered	930	275	7							
			1000	300	8							
			1200	350	9							
	high alloyed steel, cast steel, and tool steel	annealed	680	200	10	35-55	0.04-0.08	0.06-0.10	0.06-0.12	0.08-0.14	0.10-0.16	
		quenched and tempered	1100	325	11							
	stainless steel and cast steel	ferritic/martensitic	680	200	12	30-45	0.04-0.08	0.06-0.10	0.06-0.12	0.08-0.14	0.10-0.16	
		martensitic	820	240	13							
M	stainless steel and cast steel	austenitic, duplex	600	180	14	25-45	0.04-0.08	0.06-0.10	0.06-0.12	0.08-0.14	0.10-0.16	
K	grey cast iron (GG)	ferritic / pearlitic		180	15	60-70	0.10-0.18	0.12-0.20	0.14-0.22	0.14-0.24	0.16-0.26	
		pearlitic / martensitic		260	16							
	cast iron nodular (GGG)	ferritic		160	17	55-65						
		pearlitic		250	18							
	malleable cast iron	ferritic		130	19	50-60						
		pearlitic		230	20							
S	high temperature alloys	Fe based	annealed		200	31	30-35	0.04-0.08	0.06-0.10	0.06-0.12	0.08-0.14	0.10-.0.16
			hardened		280	32						
		Ni or Co based	annealed		250	33	25-30	0.04-0.08	0.06-0.10	0.06-0.12	0.08-0.14	0.10-.0.16
			hardened		350	34						
	cast			320	35							
	titanium alloys	pure	400	190	36	30-35	0.04-0.08	0.06-0.10	0.06-0.12	0.08-0.14	0.10-.0.16	
		alpha+beta alloys, hardened	1050	310	37							



SOLIDDRILL

SCD-SXC50

Solid Carbide Drills with
Internal Coolant Channels,
Drilling Depth 50xD



Designation	Dimensions								IC908
	DC	DCONMS	OAL	LU	LCF	LS	PL	ULDR ⁽²⁾	
SCD 040-217-060 SXC50	4.00	6.00	270.00	217.00	225.0	40.0	0.660	50.0	●
SCD 042-217-060 SXC50	4.20	6.00	270.00	217.00	225.0	40.0	0.693	50.0	●
SCD 045-267-060 SXC50	4.50	6.00	320.00	267.00	275.0	40.0	0.743	50.0	●
SCD 047-267-060 SXC50 ⁽¹⁾	4.70	6.00	320.00	267.00	275.0	40.0	0.775	50.0	●
SCD 048-267-060 SXC50	4.80	6.00	320.00	267.00	275.0	40.0	0.792	50.0	●
SCD 050-267-060 SXC50	5.00	6.00	320.00	267.00	275.0	40.0	0.825	50.0	●
SCD 055-302-060 SXC50	5.50	6.00	360.00	302.00	310.0	45.0	0.907	50.0	●
SCD 058-302-060 SXC50 ⁽¹⁾	5.80	6.00	360.00	302.00	310.0	45.0	0.957	50.0	●
SCD 060-302-060 SXC50	6.00	6.00	360.00	302.00	310.0	45.0	0.990	50.0	●


• For user guide and cutting conditions, see pages 145-146

⁽¹⁾ On request

⁽²⁾ Usable length diameter ratio

Recommended Drilling Procedure for Deep Hole Drilling

- 1 Drill a pilot hole 1-2xD deep with a short drill. The pilot drill should be 0.03-0.05 mm larger than the long drill and its point angle should also be larger (over 135°).
- 2 Enter the pre-hole using low feed and rotate at low speed (50-100 RPM) to within 1 - 2 mm of pre-hole depth.
- 3 Activate the coolant system and increase rotation speed to the recommended cutting parameter, maintain for 2-3 seconds, then continue at recommended drilling feed. **No pecking is required.**
- 4 After having reached the required depth, reduce speed to 50-100 RPM before retracting from the hole.



- 40xD & 50xD must utilize a 20xD intermediary drill along with pilot drill.

- In through holes, the tool exit should not exceed 2-3 mm.

Alphabetical Index

C	CAID	33
	CAOD	33
D	DDC-EA	66
	DDC-EC	69
	DDD-E3	48
	DDD-EC	29
	DDD-EF-FB	20
	DDD-EF-FT	10
	DSC-EA	52
	DSC-EC	55
	DSC-IA	60
	DSC-IC	62
	DSD-E0	46
	DSD-E1	46
	DSD-E2/E3	47
	DSD-EC	27
	DSD-EF-FB	18
	DSD-EF-FT	9
	DSD-IC	28
	DSD-IF-FB	19
	DSD-IF-FT	9
	DSTR-EC	76
	DSTR-IC	78
G	GD-DH	108
	GD-DH (10.00-11.50)	105



	GD-DH (12-13.5)	106
	GD-DHL (12-13)	107
	GDH-MKT	110
	GDV	121
	GPP	31
	GPS	12, 23, 32
L	LOGT	111
M	MNSNT	119
N	NPHT	21
	NPMT	22
	NPMX 0803 RB/RG	30
R	RGP	62
S	SCD-SXC16	140
	SCD-SXC20	141
	SCD-SXC30	143
	SCD-SXC40	145
	SCD-SXC50	146
	SGP	31
	SHIM GPS	84
T	TDO-I (D18.41-65.00)	88
	TDO-I (D65.00-171.99)	89
	TOGT-DT	11, 111
	TOGT-GF	11, 112
	TPMX	30
	TS***	85
	TS-I**	86
	TS-O**	87
X	XPMT-45	53
Z	ZSGT	111

ISCAR LTD.**Israel****Headquarters**

Tel +972 (0)4 997 0311
Fax+972 (0)4 987 3741
headquarter@iscar.co.il

Argentina

ISCAR TOOLS ARGENTINA SA
Tel +54 114 912 2200
Fax+54 114 912 4411
admin@iscararg.com.ar

Australia

ISCAR AUSTRALIA PTY. LTD
Tel +61 (0) 2 8848 3500
Fax+61 (0) 2 8848 3511
iscaraus@iscar.com.au

Austria

ISCAR AUSTRIA GmbH
Tel +43 7252 71200-0
Fax+43 7252 71200-999
office@iscar.at

Belarus

JV ALC "TWINING-M"
Tel +375 17 506-32-38
+375 17 506-33-31/65
Tel/Fax +375 17 506-32-37
info@twing.by
www.twing.by

Belgium

n.v. ISCAR BENELUX s.a.
Tel +32 (0) 2 464 2020
Fax+32 (0) 2 522 5121
info@iscar.be

Bosnia

(Representative Office)
Tel +387 32 201 100
Fax+387 32 201 101
info@iscar.ba

Brazil

ISCAR DO BRASIL COM. LTDA.
Tel +55 19 3826-7100
Fax+55 19 3826-7171
DDG 0800 701 8877
iscar@iscarbrasil.com.br

Bulgaria

ISCAR BULGARIA
Tel/Fax +359 431 62557
aa_iscar@infotel.bg

Canada

ISCAR TOOLS INC.
Tel +1 905 829 9000
Fax+1 905 829 9100
admin@iscar.ca

Chile

J&A INTERNATIONAL
Tel +56 2 2232 5838
amedina@jya.cl
www.jya.cl

China

ISCAR CHINA
Tel +86 21 8024 8888
iscar@iscar.com.cn

Colombia

ISCAR Andina
Tel +57 310 380 9932
Tel/fax +57 1 896 65 78
iscar@iscar.com.co

Croatia

ISCAR ALATI d.o.o.
Tel +385 (0) 1 33 23 301
Fax+385 (0) 1 33 76 145
podrska@iscar.hr

Cyprus

WAMET (Demetriades) Ltd.
Tel +357 (0) 2 336660/5498
Fax+357 (0) 2 333386
wamet@cytanet.com.cy

Czech Republic

ISCAR CR s.r.o.
Tel +420 377 420 625
Fax+420 377 420 630
iscar@iscar.cz

Denmark

KJ VAERKTOEJ AS/ISCAR DENMARK
Tel +45 70 11 22 44
Fax+45 46 98 67 10
kj@kj.dk

Ecuador

ISCAR Andina
Tel/fax +57 1 821 93 38
iscar@iscar.com.co
atencioncliente@iscar.com.co

Estonia

KATOMSK AS
Tel +372 6775 671
Fax+372 6720 266
aleksei@katomsk.ee

Finland

ISCAR FINLAND OY
Tel +358-(0)9-439 1420
Fax+358-(0)9-466 328
info@iscar.fi

France

ISCAR FRANCE SAS
Tel +33 (0)1 30 12 92 92
Fax+33 (0)1 30 12 95 82
info@iscar.fr

Germany

ISCAR Germany GmbH
Tel +49 (0) 72 43 9908-0
Fax+49 (0) 72 43 9908-93
gmbh@iscar.de
www.iscar.de

Greece

INTERNATIONAL TOOLS
K.-X. GEORGOPOULOS & SIA O.E
Tel +30 210 346 0133
Fax+30 210 342 5621
info@internationaltools.gr

VIMA

V. Mazlounian & Sons
Tel +30 2310 517-117 / 544-521
Fax+30 2310 529-107
vimaco@otenet.gr
http://www.vimaco.gr

Hong Kong

MTC TOOLING SYSTEMS LTD
Tel +85-2-23054838
Fax+85-2-27988789
yoongkamsing@hotmail.com

Hungary

ISCAR HUNGARY KFT.
Tel +36 28 887 700
Fax+36 28 887 710
iscar@iscar.hu

India

ISCAR India Ltd.
Tel +91 77009 63707
sales@iscar.in

Indonesia

CV MULTI TEKNIK
Tel +62-21-29206242/44/45/59
Fax+62-21-29206243
contact@multi-teknik.co.id

Ireland

HARD METAL MACHINE TOOLS
Tel +353 (0) 1 286 2466
Fax+353 (0) 1 286 1514
phannigan@hardmetal.ie
www.hardmetal.ie

Italy

ISCAR ITALIA srl
Tel +39 02 93 528 1
Fax+39 02 93 528 213
marketing@iscaritalia.it

Japan

ISCAR JAPAN LTD.
Tel +81 6 6835 5471
Fax+81 6 6835 5472
iscar@iscar.co.jp

Latvia

MECHA, UAB
Tel +370 37 407 230
Fax+370 37 407 231
info@mecha.lt

Lithuania

MECHA, UAB
Tel +370 37 407 230
Fax+370 37 407 231
sigitas@mecha.lt

Mexico

ISCAR DE MÉXICO
Tel +52 (442) 214 5505
Fax+52 (442) 214 5510
iscarmex@iscar.com.mx

The Netherlands

ISCAR NEDERLAND B.V.
Tel +31 (0) 182 535523
Fax+31 (0) 182 572777
info@iscar.nl

New Zealand

ISCAR PACIFIC LTD.
Tel +64 (0) 9 573 1280
Fax+64 (0) 9 573 0781
iscar@iscarpac.co.nz

North Macedonia

(Representative Office)
Tel +389 2 309 02 52
Fax+389 2 309 02 54
info@iscar.com.mk

Norway

SVEA MASKINER AS
Tel +47 32277750
Fax+47 32277751
per.martin.bakken@svea.no

Peru

HARTMETALL SAC
Tel: (511) 6612699
otorres@hartmetallgroup.com

Philippines

MESCO
Tel +63 2631 1775
Fax+63 2635 0276
mesco@mesco.com.ph

Poland

ISCAR POLAND Sp. z o.o.
Tel +48 32 735 7700
Fax+48 32 735 7701
iscar@iscar.pl

Portugal

ISCAR Portugal, SA
Tel +351 256 579950
Fax+351 256 586764
info@iscarportugal.pt

Romania

ISCAR Tools SRL
Tel +40 (0)312 286 614
Fax+40 (0)312 286 615
iscar-romania@iscar.com

Russia

Moscow
ISCAR LLC
Tel/fax +7 495 660 91 25/31
iscar@iscar.ru

Serbia

ISCAR TOOLS d.o.o.
Tel +381 11 314 90 38
Fax+381 11 314 91 47
info@iscartools.rs

Singapore

SINO TOOLING SYSTEM
Tel +65 6566 7668
Fax+65 6567 7336
sinotool@singnet.com.sg

Slovakia

ISCAR SR, s.r.o.
Tel +421 (0) 41 5074301
Fax+421 (0) 41 5074311
info@iscar.sk

Slovenia

ISCAR SLOVENIJA d.o.o.
Tel +386 1 580 92 30
Fax+386 1 562 21 84
info@iscar.si

South Africa

ISCAR SOUTH AFRICA (PTY) LTD.
ShareCall 08600-47227
Tel +27 11 997 2700
Fax+27 11 988 9750
iscar@iscarsa.co.za

South Korea

ISCAR KOREA
Tel +82 53 760 7594
Fax+82 53 760 7500
leeyj@taegutec.co.kr

Spain

ISCAR IBERICA SA
Tel +34 93 594 6484
Fax+34 93 582 4458
iscar@iscarib.es

Sweden

ISCAR SVERIGE AB
Tel +46 (0) 18 66 90 60
Fax+46 (0) 18 122 920
info@iscar.se

Switzerland

ISCAR HARTMETALL AG
Tel +41 (0) 52 728 0850
Fax+41 (0) 52 728 0855
office@iscar.ch

Taiwan

ISCAR Taiwan Ltd.
Tel +886 (0)4-24731573
Fax+886 (0)4-24731530
iscar.taiwan@msa.hinet.net

Thailand

ISCAR Thailand Ltd.
Tel +66 (2) 7136633-8
Fax+66 (2) 7136632
iscar@iscarthailand.com

Turkey

ISCAR Kesici Takim
TIC. VE. IML. LTD
Tel +90 (262) 751 04 84 (Pbx)
Fax+90 (262) 751 04 85
iscar@iscar.com.tr

Ukraine

ISCAR UKRAINE LLC
Tel +38 (050) 440 23 91
info@iscar.com.ua

United Arab Emirates

SVRS General Trading LLC
Tel +971 4 342 6699
www.svrs-mena.com

United Kingdom

ISCAR TOOLS LTD.
Tel +44 (0) 121 422 8585
Fax+44 (0) 121 423 2789
sales@iscar.co.uk

United States

ISCAR METALS INC.
Tel +1 817 258 3200
Tech Tel 1-877-BY-ISCAR
Fax+1 817 258 3221
info@iscarmetals.com

Venezuela

FERREINDUSTRIAL ISO-DIN C.A.
Tel +58 2 632 8211/633 4657
Fax+58 2 632 5277
iso-din@cantv.net

Vietnam

ISCAR VIETNAM
(Representative Office)
Tel +84 8 38 123 519/20
Fax+84 8 38 123 521
iscarvn@hcm.fpt.vn

www.iscar.com

Please check ISCAR's online catalog for the most current technical information regarding our products



ISCAR DEEP DRILLING LINES

Metric Catalog



Download **ISCAR WORLD APP**



E-CAT



MACHINING IN TELLIGENTLY